

Switchmode/ High Frequency Rod Core Inductors

R C - 1

Description:

Triad high current rod core inductors provide cost effective energy storage. By conditioning the output signal, the inductor smoothes out the current waveform to provide a more stable current. These low cost inductors are designed to be compatible with automated P.C.B. installation.


Outline Dimensions:

A. Dimensions: As figure show Unit: In inch

B. PIN DIM. : As figure show C. WT Lbs. : 0.03 Oz

Type No.	+/- 10% Inductance	DC Rated Current	+/- 15% DC Resistance
			Ohms
RC-1	5.6 mH	0.250A	6.100

Inductance at a frequency range of 20KHz to 200KHz Rated current 10 amps per pin maximum. Rated current renders approximately 40C temperature rise.



RoHS Compliance: As of manufacturing date February 2005, all standard products meet the requirements of 2002/95/EC, known as the RoHS initiative.

*Upon printing, this document is considered "uncontrolled".Please contact Triad Magnetics 'website for the most current version.

92883

web: www.TriadMagnetics.com Phone 951-277-0757 Fax 951-277-2757 22520B Temescal Canyon Road Corona ,California

Revision: A

Release Date: December 15, 2003

AMEYA360 Components Supply Platform

Authorized Distribution Brand:

























Website:

Welcome to visit www.ameya360.com

Contact Us:

> Address:

401 Building No.5, JiuGe Business Center, Lane 2301, Yishan Rd Minhang District, Shanghai , China

> Sales:

Direct +86 (21) 6401-6692

Email amall@ameya360.com

QQ 800077892

Skype ameyasales1 ameyasales2

Customer Service :

Email service@ameya360.com

Partnership :

Tel +86 (21) 64016692-8333

Email mkt@ameya360.com