



DC POWER CONNECTORS: KPPX Series

Snap and Lock Plug

Product Features

Laptop Computers, Power Supplies and Other Portable Digital Equipment Applications

Snap & Lock Feature Helps to Prevent Accidental Disconnects

3 or 4 Pins Transmit Power, or One Pin Can Be Used For Signal Transmission

For Signal and DC Power Applications

Plugs Supplied in Kits Ready for Assembly

Performance Specifications:

Materials and Finish

Body: ABS, UL 94HB Rated

Insert: Nylon, UL 94V-2 Rated

Inner Shield: Copper Alloy, Nickel Plated

Contacts: Brass, Silver Plated

Electrical Characteristics:

Contact Rating

3 Position: Pin 1 and 2, 48V DC at 7.5A Max.,
Pin 3, 48V DC 1.0A Max.

4 Position: 48V DC 7.5A Max. For All Pins

Insulation Resistance: 50 Megohms Min. at 250V DC

Dielectric Withstanding Voltage: 500V AC For 1 Minute

Contact Resistance: 30 milliohms Max.

Mechanical Characteristics:

Durability: 1000 Cycles

Suggested Wire Awg.: #18 For Power Wires, #24 for Signal Wire

2D Drawing	IGES	STEP	3D PDF
Solder Profile	CofC RoHS Compliant	CofC REACH Compliant	UL Plastic File
Certificate of Origin	Check Stock	Request a Sample	Send Us An Email

Generated Part Number

Part Number Builder

	-		
Series		No. of Contacts	Contact Type

Series

KPPX - Snap and Lock DC Power Plug Cable Mount

Number of Contacts

3 Pin

4 Pin

Contact Type

P - Plug


Mates with:

KPJX, KPJX-PM, and KPJX-CM Series Jacks

Contact Kycon for Other Options

KPPX Series

Dimensions in mm



AMEYA360

Components Supply Platform

Authorized Distribution Brand :



Website :

Welcome to visit www.ameya360.com

Contact Us :

➤ Address :

401 Building No.5, JiuGe Business Center, Lane 2301, Yishan Rd
Minhang District, Shanghai , China

➤ Sales :

Direct +86 (21) 6401-6692

Email amall@ameya360.com

QQ 800077892

Skype ameyasales1 ameyasales2

➤ Customer Service :

Email service@ameya360.com

➤ Partnership :

Tel +86 (21) 64016692-8333

Email mkt@ameya360.com