


|                                                              |                                                                                                                                      |            |
|--------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------|------------|
| Nominal breakdown voltage $V_N$                              | 800                                                                                                                                  | V          |
| Initial values <sup>2)</sup>                                 |                                                                                                                                      |            |
| Static breakdown voltage $V_S$ <sup>1)</sup>                 |                                                                                                                                      |            |
| First ignition value $V_{S, FTE}$ after 24 hours in darkness | $\leq 950$                                                                                                                           | V          |
| Following ignition values $V_{S, FIV}$                       | 704 ... 896                                                                                                                          | V          |
| Electrical life time <sup>3)</sup>                           |                                                                                                                                      |            |
| Breakdown voltage $V_B$                                      |                                                                                                                                      |            |
| First ignition value $V_{B, FTE}$ after 24 hours in darkness | $\leq 1000$                                                                                                                          | V          |
| Ignition time $t_i$ at $V_0$ during life                     | $\leq 60$                                                                                                                            | ms         |
| Following ignition values $V_{B, FIV}$                       | 680 ... 920                                                                                                                          | V          |
| Switching operations                                         |                                                                                                                                      |            |
| at $-40; +150$ °C                                            | 40 000                                                                                                                               | Ignitions  |
| at $+25; +125$ °C                                            | 100 000                                                                                                                              | Ignitions  |
| Test circuit parameters                                      |                                                                                                                                      |            |
| Open circuit voltage $V_0$                                   | 1000                                                                                                                                 | V          |
| Loading resistance R                                         | 68                                                                                                                                   | k $\Omega$ |
| Discharge capacitance C                                      | 100                                                                                                                                  | nF         |
| Inductance L                                                 | 0.5                                                                                                                                  | $\mu$ H    |
| Discharge peak current $I_P$                                 | $\sim 400$                                                                                                                           | A          |
| General technical data                                       |                                                                                                                                      |            |
| Insulation resistance at 100 V                               | $> 100$                                                                                                                              | M $\Omega$ |
| Early ignition values between 500 ... 680 V                  | $\leq 1$                                                                                                                             | %          |
| Breakdown time                                               | $\leq 50$                                                                                                                            | ns         |
| Maximum switching frequency                                  | 400                                                                                                                                  | Hz         |
| Maximum loading current                                      | 50                                                                                                                                   | mA         |
| Weight                                                       | $\sim 2$                                                                                                                             | g          |
| Marking, blue                                                | <b>EPCOS 800 WWY O</b><br>800 - Nominal voltage<br>WW - Calendar week of production<br>Y - Year of production<br>O - Non radioactive |            |





<sup>1)</sup> At delivery AQL 0,65 level II, DIN ISO 2859

<sup>2)</sup> Page 2, Fig. 1 and 2

<sup>3)</sup> Page 2, Fig. 3 and 4

**Fig. 1: QC- test circuit (100% outgoing inspection)**


DUT device under test  
 ICU ignition control unit (sensitivity 10 .. 30 μA)  
 Discharge current 10 – 20 mA

**Fig. 2: Explanation of measurands**

**Fig. 3: QC- test circuit (sampling inspection at 25 °C)**

**Fig. 4: Explanation of measurands**


Not to scale

Dimensions in mm

Non controlled document

© EPCOS AG 2002. Reproduction, publication and dissemination of this data sheet, enclosures hereto and the information contained therein without EPCOS' prior express consent is prohibited.

Purchase orders are subject to the General Conditions for the Supply of Products and Services of the Electrical and Electronics Industry recommended by the ZVEI (German Electrical and Electronic Manufacturers' Association), unless otherwise agreed.

# AMEYA360

## Components Supply Platform

Authorized Distribution Brand :



Website :

Welcome to visit [www.ameya360.com](http://www.ameya360.com)

Contact Us :

➤ Address :

401 Building No.5, JiuGe Business Center, Lane 2301, Yishan Rd  
Minhang District, Shanghai , China

➤ Sales :

Direct +86 (21) 6401-6692

Email [amall@ameya360.com](mailto:amall@ameya360.com)

QQ 800077892

Skype ameyasales1 ameyasales2

➤ Customer Service :

Email [service@ameya360.com](mailto:service@ameya360.com)

➤ Partnership :

Tel +86 (21) 64016692-8333

Email [mkt@ameya360.com](mailto:mkt@ameya360.com)