

## Ultra High Frequency Matched Pair Transistors

The HFA3134 and HFA3135 are Ultra High Frequency Transistor pairs that are fabricated with Intersil Corporation's complementary bipolar UHF-1X process. The NPN transistors exhibit an  $f_T$  of 8.5GHz, while the PNP transistors have an  $f_T$  of 7GHz. Both types exhibit low noise, making them ideal for high frequency amplifier and mixer applications.

Both arrays are matched high frequency transistor pairs. The matching simplifies DC bias problems and it minimizes imbalances in differential amplifier configurations. Their high  $f_T$  enables the design of UHF amplifiers which exhibit exceptional stability.

## Ordering Information

PART NUMBER (BRAND)	TEMP. RANGE (°C)	PACKAGE	PKG. DWG. #
HFA3134IH96 (04/70)	-40 to 85	6 Ld SOT23 Tape and Reel	P6.064
HFA3134IHZ96 (4Z/Z7) (Note)	-40 to 85	6 Ld SOT23 Tape and Reel (Pb-free)	P6.064
HFA3135IH96 (05/90)	-40 to 85	6 Ld SOT23 Tape and Reel	P6.064
HFA3135IHZ96 (5Z/9Z) (Note)	-40 to 85	6 Ld SOT23 Tape and Reel (Pb-free)	P6.064

NOTE: Intersil Pb-free plus anneal products employ special Pb-free material sets; molding compounds/die attach materials and 100% matte tin plate termination finish, which are RoHS compliant and compatible with both SnPb and Pb-free soldering operations. Intersil Pb-free products are MSL classified at Pb-free peak reflow temperatures that meet or exceed the Pb-free requirements of IPC/JEDEC J STD-020.

## Features


- NPN Transistor ( $f_T$ ) ..... 8.5GHz
- NPN Current Gain ( $h_{FE}$ ) ..... 100
- NPN Noise Figure (50Ω) at 1.0GHz. .... 2.6dB
- PNP Transistor ( $f_T$ ) ..... 7GHz
- PNP Current Gain ( $h_{FE}$ ) ..... 57
- PNP Noise Figure (50Ω) at 900MHz ..... 4.6dB
- Small Package (EIAJ-SC74 Compliant) ..... SOT23-6
- Pb-Free Plus Anneal Available (RoHS Compliant)

## Applications


- VHF/UHF Amplifiers
- VHF/UHF Mixers
- IF Converters
- Synchronous Detectors

## Pinouts

**HFA3134  
(SOT23)  
TOP VIEW**



**HFA3135  
(SOT23)  
TOP VIEW**





## HFA3134, HFA3135

### Electrical Specifications $T_A = 25^\circ\text{C}$ (Continued)

PARAMETER	SYMBOL	TEST CONDITIONS	(NOTE 3) TEST LEVEL	MIN	TYP	MAX	UNITS
<b>DYNAMIC CHARACTERISTICS FOR HFA3134 (NPN)</b>							
Noise Figure	NF	$f = 1.0\text{GHz}$ , $I_C = 10\text{mA}$ , $1\text{V} \leq V_{CE} \leq 5\text{V}$ , $Z_S = 50\Omega$	B	-	2.4	-	dB
		$f = 1.0\text{GHz}$ , $I_C = 1\text{mA}$ , $1\text{V} \leq V_{CE} \leq 5\text{V}$ , $Z_S = 50\Omega$	B	-	2.6	-	dB
Current Gain-Bandwidth Product (Note 5)	$f_T$	$I_C = 10\text{mA}$ , $V_{CE} = 5\text{V}$	B	-	8.5	-	GHz
		$I_C = 1\text{mA}$ , $V_{CE} = 5\text{V}$	B	-	3	-	GHz
Power Gain-Bandwidth Product	$f_{MAX}$	$I_C = 10\text{mA}$ , $V_{CE} = 5\text{V}$	B	-	7.5	-	GHz
Base to Emitter Capacitance		$V_{BE} = -0.5\text{V}$	B	-	600	-	fF
Collector to Base Capacitance		$V_{CB} = 3\text{V}$	B	-	500	-	fF

### Electrical Specifications $T_A = 25^\circ\text{C}$

PARAMETER	SYMBOL	TEST CONDITIONS	(NOTE 3) TEST LEVEL	MIN	TYP	MAX	UNITS
<b>DC CHARACTERISTICS FOR HFA3135 (PNP)</b>							
Collector to Base Breakdown Voltage	$V_{(BR)CBO}$	$I_C = -10\mu\text{A}$ , $I_E = 0$	A	12	21	-	V
Collector to Emitter Breakdown Voltage	$V_{(BR)CEO}$	$I_C = -100\mu\text{A}$ , $I_B = 0$	A	4	14	-	V
	$V_{(BR)CER}$	$I_C = -100\mu\text{A}$ , $R_B = 10\text{k}\Omega$	A	11	23	-	V
Emitter to Base Breakdown Voltage (Note 4)	$V_{(BR)EBO}$	$I_E = -10\mu\text{A}$ , $I_C = 0$	B	-	5	-	V
Collector-Cutoff-Current	$I_{CEO}$	$V_{CE} = -6\text{V}$ , $I_B = 0$	A	-5	-	5	nA
Collector-Cutoff-Current	$I_{CBO}$	$V_{CB} = -8\text{V}$ , $I_E = 0$	A	-5	-	5	nA
Emitter-Cutoff-Current	$I_{EBO}$	$V_{EB} = -1\text{V}$ , $I_C = 0$	B	-	TBD	-	pA
Collector to Collector Leakage			B	-	1	-	nA
Collector to Emitter Saturation Voltage	$V_{CE(SAT)}$	$I_C = -10\text{mA}$ , $I_B = -1\text{mA}$	A	-	150	250	mV
Base to Emitter Voltage	$V_{BE}$	$I_C = -10\text{mA}$ , $V_{CE} = -2\text{V}$	A	-	850	1000	mV
Q <sub>1</sub> to Q <sub>2</sub> Base to Emitter Voltage Match	$\Delta V_{BE}$	$I_C = -10\text{mA}$ , $V_{CE} = -2\text{V}$	A	-	1	6	mV
		$I_C = -1\text{mA}$ , $V_{CE} = -2\text{V}$	A	-	1	6	mV
		$I_C = -0.1\text{mA}$ , $V_{CE} = -2\text{V}$	A	-	2	6	mV
DC Forward-Current Transfer Ratio	$h_{FE}$	$I_C = -10\text{mA}$ , $V_{CE} = -2\text{V}$	A	15	40	125	
		$I_C = -1\text{mA}$ , $V_{CE} = -2\text{V}$	A	15	47	125	
		$I_C = -0.1\text{mA}$ , $V_{CE} = -2\text{V}$	A	15	52	125	
		$I_C = -10\text{mA}$ , $V_{CE} = -5\text{V}$	A	15	47	125	
		$I_C = -1\text{mA}$ , $V_{CE} = -5\text{V}$	A	15	53	125	
		$I_C = -0.1\text{mA}$ , $V_{CE} = -5\text{V}$	A	15	57	125	
Q <sub>1</sub> to Q <sub>2</sub> Current Gain Match	$\Delta h_{FE}$	$-1\text{mA} \leq I_C \leq -10\text{mA}$ , $-1\text{V} \leq V_{CE} \leq -5\text{V}$	A	-	1	8	%
Early Voltage	$V_A$	$I_C = -1\text{mA}$ , $\Delta V_{CE} = -3\text{V}$	A	15	24	-	V
Base to Emitter Voltage Drift		$I_C = -10\text{mA}$	C	-	-1.4	-	mV/ $^\circ\text{C}$

# HFA3134, HFA3135

## Electrical Specifications $T_A = 25^\circ\text{C}$ (Continued)

PARAMETER	SYMBOL	TEST CONDITIONS	(NOTE 3) TEST LEVEL	MIN	TYP	MAX	UNITS
<b>DYNAMIC CHARACTERISTICS FOR HFA3135 (PNP)</b>							
Noise Figure	NF	$f = 900\text{MHz}$ , $I_C = -10\text{mA}$ , $-1\text{V} \leq V_{CE} \leq -5\text{V}$ , $Z_S = 50\Omega$	B	-	5.2	-	dB
		$f = 900\text{MHz}$ , $I_C = -1\text{mA}$ , $-1\text{V} \leq V_{CE} \leq -5\text{V}$ , $Z_S = 50\Omega$	B	-	4.6	-	dB
Current Gain-Bandwidth Product	$f_T$	$I_C = -10\text{mA}$ , $V_{CE} = -5\text{V}$	B	-	7	-	GHz
Power Gain-Bandwidth Product	$f_{\text{MAX}}$	$I_C = -10\text{mA}$ , $V_{CE} = -5\text{V}$	B	-	TBD	-	GHz
Base to Emitter Capacitance		$V_{BE} = 0.5\text{V}$	B	-	550	-	fF
Collector to Base Capacitance		$V_{CB} = -3\text{V}$	B	-	400	-	fF

### NOTES:

- Test Level: A. Production Tested; B. Typical or Guaranteed Limit Based on Characterization; C. Design Typical for Information Only.
- Measuring  $V_{EBO}$  can degrade the transistor  $h_{FE}$  and  $h_{FE}$  match.
- See Typical Performance Curves for more information.

## Typical Performance Curves $T_A = 25^\circ\text{C}$ , Unless Otherwise Specified




FIGURE 1. NPN COLLECTOR CURRENT vs COLLECTOR TO EMITTER VOLTAGE




FIGURE 2. NPN COLLECTOR AND BASE CURRENTS vs BASE TO EMITTER VOLTAGE


**Typical Performance Curves**  $T_A = 25^\circ\text{C}$ , Unless Otherwise Specified (Continued)

FIGURE 3. NPN DC CURRENT GAIN vs COLLECTOR CURRENT




FIGURE 4. NPN GAIN BANDWIDTH PRODUCT vs COLLECTOR CURRENT




FIGURE 5. NPN EMITTER CUTOFF CURRENT vs BASE TO EMITTER VOLTAGE

All Intersil U.S. products are manufactured, assembled and tested utilizing ISO9000 quality systems.

Intersil Corporation's quality certifications can be viewed at [www.intersil.com/design/quality](http://www.intersil.com/design/quality)

*Intersil products are sold by description only. Intersil Corporation reserves the right to make changes in circuit design, software and/or specifications at any time without notice. Accordingly, the reader is cautioned to verify that data sheets are current before placing orders. Information furnished by Intersil is believed to be accurate and reliable. However, no responsibility is assumed by Intersil or its subsidiaries for its use; nor for any infringements of patents or other rights of third parties which may result from its use. No license is granted by implication or otherwise under any patent or patent rights of Intersil or its subsidiaries.*

For information regarding Intersil Corporation and its products, see [www.intersil.com](http://www.intersil.com)

# AMEYA360

Components Supply Platform

Authorized Distribution Brand :



Website :

Welcome to visit [www.ameya360.com](http://www.ameya360.com)

Contact Us :

➤ Address :

401 Building No.5, JiuGe Business Center, Lane 2301, Yishan Rd  
Minhang District, Shanghai , China

➤ Sales :

Direct     +86 (21) 6401-6692  
Email       amall@ameya360.com  
QQ         800077892  
Skype       ameyasales1 ameyasales2

➤ Customer Service :

Email       service@ameya360.com

➤ Partnership :

Tel         +86 (21) 64016692-8333  
Email       mkt@ameya360.com