Honeywell

Low-cost Digital Bipolar Hall-effect Sensor ICs, SS41F, SS41G

32312814

Issue A

Datasheet



DESCRIPTION

The SS41F and SS41G are small, versatile digital Hall-effect devices that are operated by the magnetic field from a permanent magnet or an electromagnet, and are designed to respond to alternating North and South poles.

A built-in regulator provides enhanced stability of operation over 4.5 Vdc to 24 Vdc supply voltage range, and internal circuitry is designed to prevent sensor damage in case the supply voltage polarity is accidentally reversed.

The open-collector sinking output voltage is easily interfaced with a wide variety of electronic circuits.

The SS41F is factory tested at 25 °C [77 °F] and the SS41G is factory tested at both 25 °C [77 °F] and 125 °C [257 °F].

Both products are designed for high volume applications.

These products are available in one package style:

 SS41F, SS41G: Flat TO-92-style package with straight leads in bulk packaging which allows for a compact PC board layout

FEATURES

- Small, leaded, flat TO-92-style package allows for a compact PCB layout
- Wide operating voltage range of 4.5 Vdc to 24 Vdc allows these sensors to be used in a variety of applications
- Current consumption of only 5 mA max. at 4.5 Vdc for energy efficiency
- Bipolar magnetics for ring magnet applications with alternating North and South poles
- Robust design: Will operate up to 150 °C [302 °F]
- RoHS-compliant materials meet Directive 2002/95/EC

POTENTIAL APPLICATIONS

Transportation

- Speed and RPM sensing
- Commutation and control of electric motors used in transportation

Industrial and Commercial

- Flow-rate sensing for appliances
- Tachometer counter pickup
- Brushless dc motor commutation
- Motor and fan control for commercial, consumer or industrial equipment

Medical

• Any medical equipment or instruments using electric motors

PORTFOLIO

The SS41F, SS41G are part of Honeywell's family of low-cost digital bipolar Hall-effect sensor ICs, including:

- SS30AT, SS40A, SS50AT
- SS311PT, SS411P
- SS411A, SS413A
- SS51T, SS511AT, SS513AT

Low-cost Digital Bipolar Hall-effect Sensor ICs, SS41F, SS41G

Table 1. SS41F Electrical and Environmental Specifications

(At V_{supply} = 4.5 Vdc to 24.0 Vdc, 20 mA load, T_A = 25 °C [77 °F] except where otherwise specified.

Characteristic	Condition	Min.	Тур.	Max.	Unit
Supply voltage	—	4.5	—	24.0	Vdc
Supply current	—	—	6.8	10.0	mA
Output current	_	—	—	20.0	mA
V _{sat} at 15 mA	$V_{supply} = 12$ Vdc, Bop >170	—	—	0.4	V
Output leakage current	$V_{supply} = 24$ Vdc, Brp \leq -170	_	—	10.0	uA
Rise time	$V_{supply} = 4.5 Vdc$	—	0.5	1.5	us
Fall time	$V_{supply} = 4.5 \text{ Vdc}$	_	0.2	1.5	us
Magnetic characteristics: operate (Bop) release (Brp) differential		 -150 40	40 -40 —	150 — —	Gauss
Operating temperature	_	-40 [-40]	_	150 [302]	°C [°F]
Storage temperature	_	-40 [-40]	_	150 [302]	°C [°F]
ESD (Human Body Model)	per JEDEC JS-001	-3	_	+3	kV
Soldering temperature and time	PC board wave soldering process: 250 °C to 260 °C [482 °F to 500 °F] for 3 s max.				

Table 2. SS41G Electrical and Environmental Specifications (At V_{supply} = 4.5 Vdc to 24.0 Vdc, 20 mA load, T_A = -40 °C to 150 °C [-40 °F to 302 °F] except where otherwise specified.

Characteristic	Condition	Min.	Тур.	Max.	Unit
Supply voltage	_	4.5	_	24.0	Vdc
Supply current: ouptut off output on	-		6.8	10.0 11.3	mA
Output current	_	_	_	20.0	mA
V _{sat} at 20 mA	V _{supply} = 12.0 Vdc, Brp ≥170, 25 °C [77 °F]	_	_	0.4	V
Output leakage current	$V_{supply} = 24.0 \text{ Vdc}, \text{ Brp} \leq -170$	_	_	10.0	μA
Rise time	25 °C [77 °F]	_	0.5	1.5	μs
Fall time	25 °C [77 °F]	_	0.2	1.5	μs
Magnetic characteristics: operate (Bop) operate (Bop) release (Brp) release (Brp) differential	25 °C [77 °F] 25 °C [77 °F] 		40 -40 	150 250 — — —	Gauss
Operating temperature	_	-40 [-40]	_	150 [302]	°C [°F]
Storage temperature	_	-40 [-40]	_	150 [302]	°C [°F]
ESD (Human Body Model)	per JEDEC JS-001	-3	_	+3	kV
Soldering temperature and time	PC board wave soldering process: 250 °C to 260 °C [482 °F to 500 °F] for 3 s max.				

NOTICE

These Hall-effect sensor ICs may have an initial output in either the ON or OFF state if powered up with an applied magnetic field in the differential zone (applied magnetic field >Brp and <Bop). Honeywell recommends allowing 10 µs after supply voltage has reached 3 V for the output voltage to stabilize.

NOTICE

The magnetic field strength (Gauss) required to cause the switch to change state (operate and release) will be as specified in the magnetic characteristics. To test the switch against the specified limits, the switch must be placed in a uniform magnetic field.



Low-cost Digital Bipolar Hall-effect Sensor ICs, SS41F, SS41G

Table 3. SS41F, SS41G Absolute Maximum Specifications

Characteristic	Min.	Тур.	Max.	Unit
Supply voltage	-50.0	—	50.0	V
Applied output voltage	-0.5	—	50.0	V
Output current	_	—	20	mA
Magnetic flux	—	—	no limit	Gauss

NOTICE

Absolute maximum ratings are the extreme limits the device will momentarily withstand without damage to the device. Electrical and mechanical characteristics are not guaranteed if the rated voltage and/or currents are exceeded, nor will the device necessarily operate at absolute maximum ratings.

Figure 1. Magnetic Performance vs Temperature (V_{supply} = 12 Vdc)

Figure 2. Current Sinking Ouptut Block Diagram



Figure 3. Wiring Diagrams



Low-cost Digital Bipolar Hall-effect Sensor ICs, SS41F, SS41G

Figure 4. SS41 F, SS41G Sensor IC Mounting Dimensions (For reference only. mm/in.)



Table 4. Order Guide

Catalog Listing	Description			
SS41F	Low-cost digital bipolar Hall-effect sensor IC, tested at 25 °C [77 °F], flat TO-92-style package, bulk packaging (1000 units per bag)			
SS41G	Low-cost digital bipolar Hall-effect sensor IC, tested at 25 °C [77 °F] and 125 °C [257 °F], flat TO-92-style package, bulk packaging (1000 units per bag)			



Authorized Distribution Brand :



Website :

Welcome to visit www.ameya360.com

Contact Us :

➤ Address :

401 Building No.5, JiuGe Business Center, Lane 2301, Yishan Rd Minhang District, Shanghai , China

- > Sales :
 - Direct +86 (21) 6401-6692
 - Email amall@ameya360.com
 - QQ 800077892
 - Skype ameyasales1 ameyasales2

> Customer Service :

Email service@ameya360.com

> Partnership :

Tel +86 (21) 64016692-8333

Email mkt@ameya360.com