

ADP300 ADP305 High Voltage Differential Probes



Key Features

- 20 MHz and 100 MHz bandwidths
- 1,000 VRMS common mode voltage
- 1,400 Vpeak differential voltage
- EN61010 Cat III
- 80 dB CMRR at 50/60 Hz
- ProBus® system
- Full remote control

ADP30X high-voltage active differential probes are safe, easy-to-use probes ideally suited for measuring power electronics. The ADP300 is good for troubleshooting low-frequency power devices and other circuits where the reference potential is elevated from ground or the location of ground is unknown. The ADP305 is designed for measuring the high-speed floating voltages found in today's power electronics.

Easy-to-use

With the ProBus interface, the ADP30X becomes an integral part of the oscilloscope. The attenuation, offset, and bandwidth limit are all controlled from the oscilloscope front panel or by using the remote control commands. This means the complete measurement setup can be saved and recalled by the oscilloscope, and all measurement values will be correct. The scope provides power to the probe, so there is no need to worry about a separate power supply or changing batteries.

Autozero

The ADP30X offset can be easily set to zero by pushing a button in the oscilloscope's coupling menu, even when connected to live circuits. This makes it easy to get accurate measurements.

Meets EN61010 Category III requirements

Safety is the top priority when you work around high-voltage signals. The ADP300 and ADP305 are both designed to the standards required for Installation Category III. This means in addition to being used on appliances and portable equipment (Cat II), they can be used in fixed-installation environments.

SPECIFICATIONS & ORDERING INFORMATION

Specifications

| • | ADP300 | ADP305 |
|--|--|--|
| Electrical Characteristics | | |
| Bandwidth | 20 MHz | 100 MHz |
| Differential Voltage | 1400 v peak | |
| Common Mode Voltage | 1000 vrms Cat III | |
| Best Low-Frequency Accuracy (probe only) | 1% of reading | |
| CMRR | 50/60 Hz 80 dB (10,000:1) | 100kHz 50 dB (300:1) |
| Max. Slew Rate (referenced to input) | 60,000 V/us | 300,000 V/us |
| AC Noise (referenced to input) | 50 mVRMS | |
| Attenuation | ÷100/÷1000 (automatically selected by scope) | |
| Input Impedance | Between inputs 8 MΩ, 6 pF | Each input to ground 4 M Ω , 1 pF |
| Sensitivity | 1 V/div to 350 V/div | 200 mV/div to 350 V/div |

General Characteristics

| Overall Length | 2 meters | |
|-----------------------|--------------------------|--|
| Input Connectors | 4mm shrouded banana plug | |
| Operating Temperature | 0° C to 50° C | |
| Max Altitude | 2000 meters | |
| Max Relative Humidity | 80% (max 31° C) | |
| Warranty | One year | |

| Standard Accessories | | | |
|-------------------------------------|--------|--|--|
| Instruction Manual | ADP300 | | |
| Certification of Calibration | | | |
| Plunger Hook Clip (1-Red, 1-Blue) | | | |
| Straps for Holding Probe | | | |
| All ADP300 Accessories | ADP305 | | |
| Safety Spade (1-Red, 1-Blue) | | | |
| Plunger Clamp Clip (1-Red, 1-Blue) | | | |
| Plunger Jaw Clip (1-Red, 1-Blue) | | | |
| Safe Alligator Clip (1-Red, 1-Blue) | | | |
| Soft Accessory Case | | | |
| | | | |

Ordering Information

| Product Description | Product Code |
|---|--------------|
| 1,400 V, 20 MHz High-Voltage Differential Probe | AP300 |
| 1,400 V, 100 MHz High-Voltage Differential Probe | AP305 |
| Plunger Hook Clips (Quantity 2 - 1 Red, 1 Blue) | PK30X-1 |
| Safety Alligator Clips (Quantity 2 - 1 Red, 1 Blue) | PK30X-2 |
| Plunger Jaw Clips (Quantity 2 - 1 Red, 1 Blue) | PK30X-3 |
| Plunger Clamp Clips (Quantity 2 - 1 Red, 1 Blue) | PK30X-4 |
| Safety Spade Terminals (Quantity 2 - 1 Red. 1 Blue) | PK30X-5 |

Customer Service

Teledyne LeCroy oscilloscopes and probes are designed, built, and tested to ensure high reliability. In the unlikely event you experience difficulties, our digital oscilloscopes are fully warranted for three years and our probes are warranted for one year. This warranty includes:

- No charge for return shipping
- Long-term 7-year support
- Upgrade to latest software at no charge



Local sales offices are located throughout the world. Visit our website to find the most convenient location.

AMEYA360 Components Supply Platform

Authorized Distribution Brand:

























Website:

Welcome to visit www.ameya360.com

Contact Us:

Address:

401 Building No.5, JiuGe Business Center, Lane 2301, Yishan Rd Minhang District, Shanghai , China

> Sales:

Direct +86 (21) 6401-6692

Email amall@ameya360.com

QQ 800077892

Skype ameyasales1 ameyasales2

Customer Service :

Email service@ameya360.com

Partnership :

Tel +86 (21) 64016692-8333

Email mkt@ameya360.com