

# MBRM130LT1G, NRVBM130LT1G, MBRM130LT3G, NRVBM130LT3G

## Surface Mount Schottky Power Rectifier

### POWERMITE® Power Surface Mount Package

The SchottkyPOWERMITE® employs the Schottky Barrier principle with a barrier metal and epitaxial construction that produces optimal forward voltage drop–reverse current tradeoff. The advanced packaging techniques provide for a highly efficient micro miniature, space saving surface mount Rectifier. With its unique heatsink design, thePOWERMITE® has the same thermal performance as the SMA while being 50% smaller in footprint area, and delivering one of the lowest height profiles, < 1.1 mm in the industry. Because of its small size, it is ideal for use in portable and battery powered products such as cellular and cordless phones, chargers, notebook computers, printers, PDAs and PCMCIA cards. Typical applications are AC–DC and DC–DC converters, reverse battery protection, and “ORing” of multiple supply voltages and any other application where performance and size are critical.

#### Features

- Low Profile – Maximum Height of 1.1 mm
- Small Footprint – Footprint Area of 8.45 mm<sup>2</sup>
- Low V<sub>F</sub> Provides Higher Efficiency and Extends Battery Life
- Supplied in 12 mm Tape and Reel
- Low Thermal Resistance with Direct Thermal Path of Die on Exposed Cathode Heat Sink
- ESD Ratings:
  - ♦ Human Body Model = 3B (> 16 kV)
  - ♦ Machine Model = C (> 400 V)
- AEC–Q101 Qualified and PPAP Capable
- NRVB Prefix for Automotive and Other Applications Requiring Unique Site and Control Change Requirements
- All Packages are Pb–Free\*

#### Mechanical Characteristics:

- POWERMITE® is JEDEC Registered as D0–216AA
- Case: Molded Epoxy
- Epoxy Meets UL 94 V–0 @ 0.125 in
- Weight: 16.3 mg (Approximately)
- Lead and Mounting Surface Temperature for Soldering Purposes: 260°C Maximum for 10 Seconds


\*For additional information on our Pb–Free strategy and soldering details, please download the ON Semiconductor Soldering and Mounting Techniques Reference Manual, SOLDERRM/D.



ON Semiconductor®


<http://onsemi.com>

### SCHOTTKY BARRIER RECTIFIER 1.0 AMPERES, 30 VOLTS



POWERMITE  
CASE 457  
PLASTIC

#### MARKING DIAGRAM



M = Date Code  
BCG = Device Code  
▪ = Pb–Free Package

#### ORDERING INFORMATION

| Device       | Package                | Shipping†               |
|--------------|------------------------|-------------------------|
| MBRM130LT1G  | POWERMITE<br>(Pb–Free) | 3,000 /<br>Tape & Reel  |
| NRVBM130LT1G | POWERMITE<br>(Pb–Free) | 3,000 /<br>Tape & Reel  |
| MBRM130LT3G  | POWERMITE<br>(Pb–Free) | 12,000 /<br>Tape & Reel |
| NRVBM130LT3G | POWERMITE<br>(Pb–Free) | 12,000 /<br>Tape & Reel |

†For information on tape and reel specifications, including part orientation and tape sizes, please refer to our Tape and Reel Packaging Specifications Brochure, BRD8011/D.

# MBRM130LT1G, NRVBM130LT1G, MBRM130LT3G, NRVBM130LT3G

## MAXIMUM RATINGS

| Rating                                                                                                  | Symbol                          | Value      | Unit                   |
|---------------------------------------------------------------------------------------------------------|---------------------------------|------------|------------------------|
| Peak Repetitive Reverse Voltage<br>Working Peak Reverse Voltage<br>DC Blocking Voltage                  | $V_{RRM}$<br>$V_{RWM}$<br>$V_R$ | 30         | V                      |
| Average Rectified Forward Current<br>(At Rated $V_R$ , $T_C = 135^\circ\text{C}$ )                      | $I_O$                           | 1.0        | A                      |
| Peak Repetitive Forward Current<br>(At Rated $V_R$ , Square Wave, 100 kHz, $T_C = 135^\circ\text{C}$ )  | $I_{FRM}$                       | 2.0        | A                      |
| Non-Repetitive Peak Surge Current<br>(Non-Repetitive peak surge current, halfwave, single phase, 60 Hz) | $I_{FSM}$                       | 50         | A                      |
| Storage Temperature                                                                                     | $T_{stg}$                       | -55 to 150 | $^\circ\text{C}$       |
| Operating Junction Temperature                                                                          | $T_J$                           | -55 to 125 | $^\circ\text{C}$       |
| Voltage Rate of Change<br>(Rated $V_R$ , $T_J = 25^\circ\text{C}$ )                                     | $dv/dt$                         | 10,000     | $\text{V}/\mu\text{s}$ |

Stresses exceeding Maximum Ratings may damage the device. Maximum Ratings are stress ratings only. Functional operation above the Recommended Operating Conditions is not implied. Extended exposure to stresses above the Recommended Operating Conditions may affect device reliability.

## THERMAL CHARACTERISTICS

| Characteristic                                         | Symbol      | Value | Unit                      |
|--------------------------------------------------------|-------------|-------|---------------------------|
| Thermal Resistance, Junction-to-Lead (Anode) (Note 1)  | $R_{tjl}$   | 35    | $^\circ\text{C}/\text{W}$ |
| Thermal Resistance, Junction-to-Tab (Cathode) (Note 1) | $R_{tjtab}$ | 23    |                           |
| Thermal Resistance, Junction-to-Ambient (Note 1)       | $R_{tja}$   | 277   |                           |

1. Mounted with minimum recommended pad size, PC Board FR4, See Figures 9 & 10

## ELECTRICAL CHARACTERISTICS

| Characteristic                                                                                                                                       | Symbol | Value                    |                          | Unit |
|------------------------------------------------------------------------------------------------------------------------------------------------------|--------|--------------------------|--------------------------|------|
| Maximum Instantaneous Forward Voltage (Note 2), See Figure 2<br><br>( $I_F = 0.1\text{ A}$ )<br>( $I_F = 1.0\text{ A}$ )<br>( $I_F = 3.0\text{ A}$ ) | $V_F$  | $T_J = 25^\circ\text{C}$ | $T_J = 85^\circ\text{C}$ | V    |
|                                                                                                                                                      |        | 0.30                     | 0.20                     |      |
|                                                                                                                                                      |        | 0.38                     | 0.33                     |      |
|                                                                                                                                                      |        | 0.52                     | 0.50                     |      |
| Maximum Instantaneous Reverse Current (Note 2), See Figure 4<br><br>( $V_R = 30\text{ V}$ )<br>( $V_R = 20\text{ V}$ )<br>( $V_R = 10\text{ V}$ )    | $I_R$  | $T_J = 25^\circ\text{C}$ | $T_J = 85^\circ\text{C}$ | mA   |
|                                                                                                                                                      |        | 0.41                     | 11                       |      |
|                                                                                                                                                      |        | 0.13                     | 5.3                      |      |
|                                                                                                                                                      |        | 0.05                     | 3.2                      |      |

2. Pulse Test: Pulse Width  $\leq 250\text{ }\mu\text{s}$ , Duty Cycle  $\leq 2\%$




Figure 1. Typical Forward Voltage




Figure 2. Maximum Forward Voltage

# MBRM130LT1G, NRVBM130LT1G, MBRM130LT3G, NRVBM130LT3G




Figure 3. Typical Reverse Current




Figure 4. Maximum Reverse Current




Figure 5. Current Derating




Figure 6. Forward Power Dissipation




Figure 7. Capacitance




Figure 8. Typical Operating Temperature Derating\*

\* Reverse power dissipation and the possibility of thermal runaway must be considered when operating this device under any reverse voltage conditions. Calculations of  $T_J$  therefore must include forward and reverse power effects. The allowable operating  $T_J$  may be calculated from the equation:



$$T_J = T_{Jmax} - r(t)(P_f + P_r) \text{ where}$$

$r(t)$  = thermal impedance under given conditions,

$P_f$  = forward power dissipation, and

$P_r$  = reverse power dissipation


This graph displays the derated allowable  $T_J$  due to reverse bias under DC conditions only and is calculated as  $T_J = T_{Jmax} - r(t)P_r$ , where  $r(t) = R_{\theta ja}$ . For other power applications further calculations must be performed.



# MBRM130LT1G, NRVBM130LT1G, MBRM130LT3G, NRVBM130LT3G

## PACKAGE DIMENSIONS

### POWERMITE CASE 457-04 ISSUE E



#### NOTES:

1. DIMENSIONING AND TOLERANCING PER ANSI Y14.5M, 1982.
2. CONTROLLING DIMENSION: MILLIMETER.
3. DIMENSION A DOES NOT INCLUDE MOLD FLASH, PROTRUSIONS OR GATE BURRS. MOLD FLASH, PROTRUSIONS OR GATE BURRS SHALL NOT EXCEED 0.15 (0.006) PER SIDE.

| DIM | MILLIMETERS |       | INCHES    |        |
|-----|-------------|-------|-----------|--------|
|     | MIN         | MAX   | MIN       | MAX    |
| A   | 1.75        | 2.05  | 0.069     | 0.081  |
| B   | 1.75        | 2.18  | 0.069     | 0.086  |
| C   | 0.85        | 1.15  | 0.033     | 0.045  |
| D   | 0.40        | 0.69  | 0.016     | 0.027  |
| F   | 0.70        | 1.00  | 0.028     | 0.039  |
| H   | -0.05       | +0.10 | -0.002    | +0.004 |
| J   | 0.10        | 0.25  | 0.004     | 0.010  |
| K   | 3.60        | 3.90  | 0.142     | 0.154  |
| L   | 0.50        | 0.80  | 0.020     | 0.031  |
| R   | 1.20        | 1.50  | 0.047     | 0.059  |
| S   | 0.50 REF    |       | 0.019 REF |        |

#### STYLE 1:

1. CATHODE
2. ANODE

## SOLDERING FOOTPRINT\*



\*For additional information on our Pb-Free strategy and soldering details, please download the ON Semiconductor Soldering and Mounting Techniques Reference Manual, SOLDERRM/D.

POWERMITE is a registered trademark of and used under a license from Microsemi Corporation.

ON Semiconductor and are registered trademarks of Semiconductor Components Industries, LLC (SCILLC). SCILLC reserves the right to make changes without further notice to any products herein. SCILLC makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does SCILLC assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. "Typical" parameters which may be provided in SCILLC data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. SCILLC does not convey any license under its patent rights nor the rights of others. SCILLC products are not designed, intended, or authorized for use as components in systems intended for surgical implant into the body, or other applications intended to support or sustain life, or for any other application in which the failure of the SCILLC product could create a situation where personal injury or death may occur. Should Buyer purchase or use SCILLC products for any such unintended or unauthorized application, Buyer shall indemnify and hold SCILLC and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that SCILLC was negligent regarding the design or manufacture of the part. SCILLC is an Equal Opportunity/Affirmative Action Employer. This literature is subject to all applicable copyright laws and is not for resale in any manner.

## PUBLICATION ORDERING INFORMATION

**LITERATURE FULFILLMENT:**  
Literature Distribution Center for ON Semiconductor  
P.O. Box 5163, Denver, Colorado 80217 USA  
Phone: 303-675-2175 or 800-344-3860 Toll Free USA/Canada  
Fax: 303-675-2176 or 800-344-3867 Toll Free USA/Canada  
Email: [orderlit@onsemi.com](mailto:orderlit@onsemi.com)

**N. American Technical Support:** 800-282-9855 Toll Free  
USA/Canada  
**Europe, Middle East and Africa Technical Support:**  
Phone: 421 33 790 2910  
**Japan Customer Focus Center**  
Phone: 81-3-5817-1050

**ON Semiconductor Website:** [www.onsemi.com](http://www.onsemi.com)

**Order Literature:** <http://www.onsemi.com/orderlit>

For additional information, please contact your local Sales Representative

# AMEYA360

Components Supply Platform

Authorized Distribution Brand :



Website :

Welcome to visit [www.ameya360.com](http://www.ameya360.com)

Contact Us :

➤ Address :

401 Building No.5, JiuGe Business Center, Lane 2301, Yishan Rd  
Minhang District, Shanghai , China

➤ Sales :

Direct     +86 (21) 6401-6692  
Email      amall@ameya360.com  
QQ         800077892  
Skype      ameyasales1 ameyasales2

➤ Customer Service :

Email      service@ameya360.com

➤ Partnership :

Tel         +86 (21) 64016692-8333  
Email      mkt@ameya360.com