


## 5110F Series Panel Mounted LED Indicator Light

### Description and Features



#### Features

- Super Brite T-1 LED
- Diffused lens allows wide angle viewing
- Low current - only 2 mA.
- Built-in chip resistor operates directly off 5 and 12 volt supply, no external resistor needed.

Mounting: Will snap-fit into Ø.155/.158 hole in panels .031/.062 thick\*

Wire Leads: No. 26 AWG, 6"long, stripped .250

Anode(+): Red lead

Housing: Black Nylon

\*We recommend using an installation tool to press against flange of housing rather than LED.

## Electro-optical Characteristics

Part Number	Color	Typ. Intensity (mcd)	Rated Current (mA)	Continuous Forward Current Max. (mA)	Forward Voltage Typ. (V)	Forward Voltage Max. (V)	Peak Forward Current @ 1ms-300pps (A)	Reverse Break-down Voltage Min. (V)	Peak Wavelength (nm)
5110F1	Red	10	10	30	2.0	3.0	1.0	5	635
5110F5	Green	16	20	30	2.2	3.0	.09	4	562
5110F7	Yellow	6.3	20	30	2.1	3.0	1.0	5	585
5110F1LC	Red	2.5	2	7	1.8	2.2	.007	5	635
5110F5LC	Green	2.1	2	7	1.8	2.2	.007	5	565
5110F7LC	Yellow	1.8	2	7	1.9	2.7	.007	5	583
5110F1-5V	Red	8.0	10	20	5	7.5	-	5	655
5110F3-5V	Amber	8.0	10	15	5	7.5	-	5	583
5110F5-5V	Green	8.0	10	15	5	7.5	-	5	565
5110F1-12V	Red	8	13	20	12	15	-	5	655
5110F3-12V	Amber	8	13	20	12	15	-	5	583
5110F5-12V	Green	8	13	20	12	15	-	5	565

# AMEYA360

## Components Supply Platform

Authorized Distribution Brand :



Website :

Welcome to visit [www.ameya360.com](http://www.ameya360.com)

Contact Us :

➤ Address :

401 Building No.5, JiuGe Business Center, Lane 2301, Yishan Rd  
Minhang District, Shanghai , China

➤ Sales :

Direct +86 (21) 6401-6692

Email [amall@ameya360.com](mailto:amall@ameya360.com)

QQ 800077892

Skype [ameyasales1](#) [ameyasales2](#)

➤ Customer Service :

Email [service@ameya360.com](mailto:service@ameya360.com)

➤ Partnership :

Tel +86 (21) 64016692-8333

Email [mkt@ameya360.com](mailto:mkt@ameya360.com)