



TOP VIEW



SIDE VIEW



Specifications			Notes	Revision History					
Description	Value	Unit		Version	Description		Date	Approved	
Technology	Electro-Mechanical		1) All dimensions are in mm unless otherwise noted 2) All parts meet RoHS	1	Released from Engineering		10/21/2013	J.S	
Resonant Frequency	400	(Hz)							
Rated Voltage	3	(V)							
SPL @ 10cm	70	(dBA)							
Tone	Single Tone								
Mount Type	Flange								
Voltage Range	2 ~ 4	(V)							
Max Rated Current	3	(mA)							
Housing Material	ABS								
Operating Temperature	-10 ~ +60	°C							
Storage Temperature	-20 ~ +70	°C		Drawn by	Date	Checked by	Date	Approved by	Date
Weight	10	(g)		A.B.	10/21/2013	C.E.	10/21/2013	J.S	10/21/2013
DB UNLIMITED			Electro-Mechanical Indicator			IE330403-1			

AMEYA360

Components Supply Platform

Authorized Distribution Brand :



Website :

Welcome to visit www.ameya360.com

Contact Us :

➤ Address :

401 Building No.5, JiuGe Business Center, Lane 2301, Yishan Rd
Minhang District, Shanghai , China

➤ Sales :

Direct +86 (21) 6401-6692

Email amall@ameya360.com

QQ 800077892

Skype ameyasales1 ameyasales2

➤ Customer Service :

Email service@ameya360.com

➤ Partnership :

Tel +86 (21) 64016692-8333

Email mkt@ameya360.com