



## MT-10 Moisture Meter

Measure moisture content for wall board, wood or other building materials to determine places of harmful mold growth or unseen water damage.

Typical application also include checking moisture of concrete slab and wood before installation of floors, determining wood moisture content during drying process, and checking wood moisture before material is used for woodworking applications.

- Checks for moisture content in wood, paper or cardboard and building materials such as sheetrock, concrete, mortar, plaster etc...
- Measurement Ranges:
  - Wood/ Paper: 8 ~ 60%
  - Building Material: 0.3 - 2.0%
  - Temperature: 0°C ~ 40°C or 32°F ~ 99°F
- Used in indoor air quality applications for detecting moisture in the walls, floors and ceilings stimulating mold growth
- LCD Display provides moisture or temperature measurement
- Three color LED provides quick moisture indication:
  - Green - "air-dry" conditions
  - Yellow - increased moisture
  - Red - excess moisture
- Backlight for operation in dark areas
- Low battery indication
- Auto power off

### No hassle warranty

*No waiting.*

*No shipping  
charges.*



Our commitment to high-quality products and customer service is demonstrated by our industry exclusive "No Hassle" warranty. In the unlikely event that an Amprobe Test Tool requires warranty service, any of our local dealers are authorized to replace it, on the spot.

(note: \$500 MSLP limit)

## MT-10 Mini-vane Anemometer

## Data Sheet

### Specifications

<b>Measurement Range</b>	
Wood	8 ~ 60%
Building Material	0.3-2.0%
Temperature	0 ~ 40°C or 32 ~ 99°F
<b>Resolution</b>	
Wood	0.1%
Building Material	0.01%
Temperature	0.1°C / 0.2°F
<b>Accuracy</b>	
Wood	±2%
Building Material	±0.1%
Temperature	±1°C / ±2°F
<b>Low Battery Indication</b>	Symbol " " shown on the display (Automatic Power-Off)
<b>Battery</b>	9V, 6F22
<b>Operating Environment</b>	Temperature 0°C ~ 40°C (32°F to 104°F) Relative Humidity < 85%
<b>Storage Environment</b>	Temperature -10°C ~ -50°C (14°F to -58°F) Relative Humidity < 85%
<b>Dimensions</b>	145(L) × 60(W) × 31(H)mm ( 5.73 x 2.37 x 1.21 in)
<b>Weight</b>	Approx. 95g (0.37 lb)

### Amprobe® Test Tools

website: [www.Amprobe.com](http://www.Amprobe.com)  
email: [info@amprobe.com](mailto:info@amprobe.com)  
Everett, WA 98203  
Tel: 877-AMPROBE

### Amprobe® Test Tools Europe

In den Engematten 14  
79286 Glottertal, Germany  
Tel.: +49 (0) 7684 8009 - 0

# AMEYA360

## Components Supply Platform

Authorized Distribution Brand :



Website :

Welcome to visit [www.ameya360.com](http://www.ameya360.com)

Contact Us :

➤ Address :

401 Building No.5, JiuGe Business Center, Lane 2301, Yishan Rd  
Minhang District, Shanghai , China

➤ Sales :

Direct +86 (21) 6401-6692

Email [amall@ameya360.com](mailto:amall@ameya360.com)

QQ 800077892

Skype [ameyasales1](#) [ameyasales2](#)

➤ Customer Service :

Email [service@ameya360.com](mailto:service@ameya360.com)

➤ Partnership :

Tel +86 (21) 64016692-8333

Email [mkt@ameya360.com](mailto:mkt@ameya360.com)