



A. MATERIAL: 15% Glass Filled Supertough Nylon

B. The hygroscopic (readily accepts moisture) properties of Nylon will make this tool suitable for use around ESD sensitive components after a few minutes of handling the tool with bare hands. If used with gloves in a clean environment the tools must be dipped in a topical antistatic solution before use in sensitive areas. Topical treatment should be repeated at six month intervals. Without exposure to moisture or antistatic treatment, Nylon is in the insulative resistance range and charges will not be removed to ground.

C. Flat "screwdriver" surface for spudgng wire leads down flat on circuit boards.

D. Pointed end for forming wire leads or for use as pointer probe for holding objects for soldering.

Melting Point: 505°F (263°C)

Prober, Soldering Tool, Nylon

**MENDA**

3651 WALNUT AVE., CHINO, CA 91710  
PHONE: (909) 627-2453 • FAX: (951) 755-8848  
WEBSITE: MendaPump.com

DRAWING NUMBER  
35621

DATE:  
November  
2007

# AMEYA360

Components Supply Platform

Authorized Distribution Brand :



Website :

Welcome to visit [www.ameya360.com](http://www.ameya360.com)

Contact Us :

➤ Address :

401 Building No.5, JiuGe Business Center, Lane 2301, Yishan Rd  
Minhang District, Shanghai , China

➤ Sales :

Direct     +86 (21) 6401-6692  
  
Email       amall@ameya360.com  
  
QQ         800077892  
  
Skype      ameyasales1 ameyasales2

➤ Customer Service :

Email       service@ameya360.com

➤ Partnership :

Tel         +86 (21) 64016692-8333  
  
Email      mkt@ameya360.com