



## BAS316

### High Speed Switching Diode 400mW

## Features

- Lead Free Finish/RoHS Compliant ("P" Suffix designates RoHS Compliant. See ordering information)
- Epoxy meets UL 94 V-0 flammability rating
- Moisture Sensitivity Level 1
- Surface Mount Package Ideally Suited for Automatic Insertion
- High switching speed: max. 4ns
- Continuous reverse voltage: max. 100V
- Repetitive peak reverse voltage: max. 100V
- Repetitive peak forward current: max. 500mA
- Halogen free available upon request by adding suffix "-HF"

## Mechanical Data

- Marking: A6 -
- Polarity: Indicated by Cathode Band


Maximum Ratings @ 25°C Unless Otherwise Specified

Parameter	Symbol	Limits	Unit
DC Reverse Voltage	$V_R$	100	V
Forward Current	$I_F$	250	mA
Total Device Dissipation	$P_D$	400	mW
Junction and Storage temperature	$T_j, P_{stg}$	-65~+150	°C
Non-repetitive peak forward current $t=1\mu s$ $t=1ms$ $t=1s$	$I_{FSM}$	4 1 0.5	A

## Electrical Characteristics @ 25°C Unless Otherwise Specified


Parameter	Symbol	Test Conditions	MIN	MAX	UNIT
Reverse breakdown voltage	$V_{BR}$	$I_R=100\mu A$	100	...	V
Forward voltage	$V_F$	$I_F=1mA$	...	715	mV
		$I_F=10mA$	...	855	
		$I_F=50mA$	...	1000	
		$I_F=150mA$	...	1250	
Reverse leakage current	$I_R$	$V_R=25V$	...	0.03	uA
		$V_R=75V$	...	1	
Reverse recovery time	$T_{rr}$	$I_F=I_R=10mA, dI/dt=100A/s, R_L=100\Omega$	...	4	ns
Diode capacitance	$C_D$	$V_R=0V, f=1MHz$	...	1.5	pF

## SOD-323



DIMENSIONS					
DIM	INCHES		MM		NOTE
	MIN	MAX	MIN	MAX	
A	.090	.107	2.30	2.70	
B	.063	.071	1.60	1.80	
C	.045	.053	1.15	1.35	
D	.031	.045	0.80	1.15	
E	.010	.016	0.25	0.40	
G	.004	.018	0.10	0.45	
H	.004	.010	0.10	0.25	
J	-----	.006	-----	0.15	

### SUGGESTED SOLDER PAD LAYOUT



# BAS316




Fig.1 Maximum permissible continuous forward current as a function of soldering point temperature.





Fig.2 Forward current as a function of forward voltage.



Based on square wave currents.  
T<sub>j</sub> = 25 °C prior to surge.

Fig.3 Maximum permissible non-repetitive peak forward current as a function of pulse duration.

# BAS316





Fig.4 Reverse current as a function of junction temperature.



f = 1 MHz; T<sub>j</sub> = 25 °C.

Fig.5 Diode capacitance as a function of reverse voltage; typical values.

<sup>TM</sup>

Micro Commercial Components

## Ordering Information :

Device	Packing
Part Number-TP	Tape&Reel: 3Kpcs/Reel

Note : Adding "-HF" suffix for halogen free, eg. Part Number-TP-HF

### \*\*\*IMPORTANT NOTICE\*\*\*

**Micro Commercial Components Corp.** reserves the right to make changes without further notice to any product herein to make corrections, modifications , enhancements , improvements , or other changes . **Micro Commercial Components Corp.** does not assume any liability arising out of the application or use of any product described herein; neither does it convey any license under its patent rights ,nor the rights of others . The user of products in such applications shall assume all risks of such use and will agree to hold **Micro Commercial Components Corp.** and all the companies whose products are represented on our website, harmless against all damages.

### \*\*\*LIFE SUPPORT\*\*\*

MCC's products are not authorized for use as critical components in life support devices or systems without the express written approval of Micro Commercial Components Corporation.

### \*\*\*CUSTOMER AWARENESS\*\*\*

Counterfeiting of semiconductor parts is a growing problem in the industry. Micro Commercial Components (MCC) is taking strong measures to protect ourselves and our customers from the proliferation of counterfeit parts. MCC strongly encourages customers to purchase MCC parts either directly from MCC or from Authorized MCC Distributors who are listed by country on our web page cited below. Products customers buy either from MCC directly or from Authorized MCC Distributors are genuine parts, have full traceability, meet MCC's quality standards for handling and storage. **MCC will not provide any warranty coverage or other assistance for parts bought from Unauthorized Sources.** MCC is committed to combat this global problem and encourage our customers to do their part in stopping this practice by buying direct or from authorized distributors.

[www.mccsemi.com](http://www.mccsemi.com)

# AMEYA360

## Components Supply Platform

### Authorized Distribution Brand :



### Website :

Welcome to visit [www.ameya360.com](http://www.ameya360.com)

### Contact Us :

#### ➤ Address :

401 Building No.5, JiuGe Business Center, Lane 2301, Yishan Rd  
Minhang District, Shanghai , China

#### ➤ Sales :

Direct +86 (21) 6401-6692  
Email amall@ameya360.com  
QQ 800077892  
Skype ameyasales1 ameyasales2

#### ➤ Customer Service :

Email service@ameya360.com

#### ➤ Partnership :

Tel +86 (21) 64016692-8333  
Email mkt@ameya360.com