

E							DIMENSIONS IN INCHES (MILLIMETERS) DO NOT SCALE DRAWING		Dwg. No. CWR-281-XX-0203																														
D							NOTES: 1. Dimensions are in inches; dimensions in () are millimeters. 2. Metric equivalents are given for general information only, and are based upon 1.00 inches equals (25.4) millimeters. 3. Unless otherwise specified, tolerances are $\pm .005$ (.13) for three place decimals, and $\pm .01$ (.3) for two place decimals.																																
C							MATERIALS: PLASTIC PARTS — UL94V-0 thermoplastic (blue, standard) flame retardant. CONTACTS — Phosphor bronze. CONTACT PLATING— .000100 (Min.) Tin Plating All Over .000050 Min. Nickel																																
B							OPERATING STANDARDS: TEMPERATURE RATING — 125° CONTACT RATING — 1 ampere. DIELECTRIC STRENGTH — Over 500V.D.C. at sea level. CONDUCTORS ACCEPTED — 28-30 AWG solid or stranded. INSULATION RESISTANCE — Greater than 5×10^9 ohms.																																
A							<table border="1" style="width: 100%; border-collapse: collapse; text-align: center;"> <tr> <th>NO. CONTS.</th> <th>A</th> <th>B</th> <th>C</th> <th>D</th> <th>E</th> </tr> <tr> <td>9</td> <td>1.224 (31.09)</td> <td>.984 (24.99)</td> <td>.762 (19.35)</td> <td>.644 (16.36)</td> <td>.434 (11.02)</td> </tr> <tr> <td>15</td> <td>1.552 (39.42)</td> <td>1.312 (33.32)</td> <td>1.088 (27.64)</td> <td>.970 (24.64)</td> <td>.760 (19.30)</td> </tr> <tr> <td>25</td> <td>2.092 (53.14)</td> <td>1.852 (47.04)</td> <td>1.632 (41.45)</td> <td>1.514 (38.46)</td> <td>1.303 (33.10)</td> </tr> <tr> <td>37</td> <td>2.740 (69.60)</td> <td>2.500 (63.50)</td> <td>2.284 (58.01)</td> <td>2.166 (55.02)</td> <td>1.955 (49.66)</td> </tr> </table>			NO. CONTS.	A	B	C	D	E	9	1.224 (31.09)	.984 (24.99)	.762 (19.35)	.644 (16.36)	.434 (11.02)	15	1.552 (39.42)	1.312 (33.32)	1.088 (27.64)	.970 (24.64)	.760 (19.30)	25	2.092 (53.14)	1.852 (47.04)	1.632 (41.45)	1.514 (38.46)	1.303 (33.10)	37	2.740 (69.60)	2.500 (63.50)	2.284 (58.01)	2.166 (55.02)	1.955 (49.66)
NO. CONTS.	A	B	C	D	E																																		
9	1.224 (31.09)	.984 (24.99)	.762 (19.35)	.644 (16.36)	.434 (11.02)																																		
15	1.552 (39.42)	1.312 (33.32)	1.088 (27.64)	.970 (24.64)	.760 (19.30)																																		
25	2.092 (53.14)	1.852 (47.04)	1.632 (41.45)	1.514 (38.46)	1.303 (33.10)																																		
37	2.740 (69.60)	2.500 (63.50)	2.284 (58.01)	2.166 (55.02)	1.955 (49.66)																																		
CUSTOMER DRAWING																																							
12345678910																																							
REVISIONS FORM-B4 RELEASED: 9-18-2006 DGW SEP 20 2006 ATTENTION THIS DRAWING AND ITS ATTACHMENTS, IF ANY, ARE PROPRIETARY TO CW INDUSTRIES AND DESCRIBE DESIGNS THAT ARE CONFIDENTIAL AND MUST NOT BE DISCLOSED UNLESS AUTHORIZED, IN WRITING, BY AN OFFICER OF CW INDUSTRIES. CW INDUSTRIES Southampton, Pa. 18966 TOLERANCES UNLESS OTHERWISE SPECIFIED 2 Place Decimal $\pm .010$ METRIC 3 Place Decimal $\pm .005$ 1 Place Dec. $\pm .25$mm Angles $\pm 1^\circ$ 2 Place Dec. $\pm .13$mm Title: METAL SHROUD "D" CONNECTOR PLUG (FEMALE CONTACTS) Division: CONNECTOR Dwg. No. CWR-281-XX-0203																																							

MASTER

AMEYA360

Components Supply Platform

Authorized Distribution Brand :



Website :

Welcome to visit www.ameya360.com

Contact Us :

➤ Address :

401 Building No.5, JiuGe Business Center, Lane 2301, Yishan Rd
Minhang District, Shanghai , China

➤ Sales :

Direct +86 (21) 6401-6692

Email amall@ameya360.com

QQ 800077892

Skype ameyasales1 ameyasales2

➤ Customer Service :

Email service@ameya360.com

➤ Partnership :

Tel +86 (21) 64016692-8333

Email mkt@ameya360.com