



Converter - Brake - Inverter Module NPT IGBT

Single Phase Rectifier	Brake Chopper	Three Phase Inverter
$V_{RRM} = 1600 \text{ V}$	$V_{CES} = 600 \text{ V}$	$V_{CES} = 600 \text{ V}$
$I_{DAVM25} = 90 \text{ A}$	$I_{C25} = 29 \text{ A}$	$I_{C25} = 29 \text{ A}$
$I_{FSM} = 270 \text{ A}$	$V_{CE(sat)} = 2.1 \text{ V}$	$V_{CE(sat)} = 2.1 \text{ V}$

Part name (Marking on product)

MIAA20WB600TMH



E 72873

Pin configuration see outlines.

Features:

- High level of integration - only one power semiconductor module required for the whole drive
- Inverter with NPT IGBTs
 - low saturation voltage
 - positive temperature coefficient
 - fast switching
 - short tail current
- Epitaxial free wheeling diodes with hiperfast soft reverse recovery
- Temperature sense included

Application:

- AC motor drives
- Pumps, Fans
- Washing machines
- Air-conditioning system
- Inverter and power supplies

Package:

- "Mini" package
- Assembly height is 17 mm
- Insulated base plate
- Pins suitable for wave soldering and PCB mounting
- Assembly clips available
 - IXKU 5-505 screw clamp
 - IXRB 5-506 click clamp
- UL registered E72873

Output Inverter T1 - T6

				Ratings			
Symbol	Definitions	Conditions	min.	typ.	max.	Unit	
V _{CES}	collector emitter voltage	T _{VJ} = 150°C			600	V	
V _{GES}	max. DC gate voltage	continuous			±20	V	
V _{GEM}	max. transient collector gate voltage	transient			±30	V	
I _{C25}	collector current	T _C = 25°C			29	A	
I _{C80}		T _C = 80°C			20	A	
P _{tot}	total power dissipation	T _C = 25°C			100	W	
V _{CE(sat)}	collector emitter saturation voltage	I _C = 20 A; V _{GE} = 15 V		2.1 2.4	2.7	V V	
V _{GE(th)}	gate emitter threshold voltage	I _C = 0.5 A; V _{GE} = V _{CE}	T _{VJ} = 25°C 4.5	5.5	6.5	V	
I _{CES}	collector emitter leakage current	V _{CE} = V _{CES} ; V _{GE} = 0 V	T _{VJ} = 25°C T _{VJ} = 125°C	1.3	1.1	mA mA	
I _{GES}	gate emitter leakage current	V _{GE} = ±20 V			150	nA	
C _{ies}	input capacitance	V _{CE} = 25 V; V _{GE} = 0 V; f = 1 MHz		900		pF	
Q _{G(on)}	total gate charge	V _{CE} = 300 V; V _{GE} = 15 V; I _C = 20 A		76		nC	
t _{d(on)}	turn-on delay time	inductive load V _{CE} = 300 V; I _C = 20 A V _{GE} = ±15 V; R _G = 47 Ω	T _{VJ} = 25°C	35		ns	
t _r	current rise time			45		ns	
t _{d(off)}	turn-off delay time			155		ns	
t _f	current fall time			75		ns	
E _{on}	turn-on energy per pulse			0.39		mJ	
E _{off}	turn-off energy per pulse			0.4		mJ	
t _{d(on)}	turn-on delay time	inductive load V _{CE} = 300 V; I _C = 20 A V _{GE} = ±15 V; R _G = 47 Ω	T _{VJ} = 125°C	35		ns	
t _r	current rise time			45		ns	
t _{d(off)}	turn-off delay time			165		ns	
t _f	current fall time			150		ns	
E _{on}	turn-on energy per pulse			0.6		mJ	
E _{off}	turn-off energy per pulse			0.54		mJ	
RBSOA	reverse bias safe operating area	V _{GE} = ±15 V; R _G = 47 Ω; I _C = 30 A	T _{VJ} = 125°C	V _{CEK} ≤ V _{CES} - L _S ·di/dt		V	
I _{SC} (SCSOA)	short circuit safe operating area	V _{CE} = 360 V; V _{GE} = ±15 V; R _G = 47 Ω; t _p = 10 μs; non-repetitive	T _{VJ} = 125°C	90		A	
R _{thJC}	thermal resistance junction to case	(per IGBT)			1.3	K/W	
R _{thCH}	thermal resistance case to heatsink			0.45		K/W	

Output Inverter D1 - D6

				Ratings		
Symbol	Definitions	Conditions	min.	typ.	max.	Unit
V_{RRM}	<i>max. repetitive reverse voltage</i>		$T_{VJ} = 150^{\circ}\text{C}$		600	V
I_{F25}	<i>forward current</i>		$T_C = 25^{\circ}\text{C}$		37	A
I_{F80}			$T_C = 80^{\circ}\text{C}$		24	A
V_F	<i>forward voltage</i>	$I_F = 20\text{ A}; V_{GE} = 0\text{ V}$	$T_{VJ} = 25^{\circ}\text{C}$ $T_{VJ} = 125^{\circ}\text{C}$	1.95 1.65	2.2	V V
Q_{rr}	<i>reverse recovery charge</i>	$V_R = 300\text{ V}$ $di_F/dt = -370\text{ A}/\mu\text{s}$ $I_F = 20\text{ A}; V_{GE} = 0\text{ V}$	$T_{VJ} = 125^{\circ}\text{C}$	0.58		μC
I_{RM}	<i>max. reverse recovery current</i>			10.7		A
t_{rr}	<i>reverse recovery time</i>			110		ns
E_{rec}	<i>reverse recovery energy</i>			60		μJ
R_{thJC}	<i>thermal resistance junction to case</i>	(per diode)			1.6	K/W
R_{thCH}	<i>thermal resistance case to heatsink</i>			0.55		K/W

 $T_C = 25^{\circ}\text{C}$ unless otherwise stated

Brake T7

				Ratings		
Symbol	Definitions	Conditions	min.	typ.	max.	Unit
V_{CES}	collector emitter voltage	$T_{VJ} = 150^{\circ}\text{C}$			600	V
V_{GES}	max. DC gate voltage	continuous			± 20	V
V_{GEM}	max. transient collector gate voltage	transient			± 30	V
I_{C25}	collector current	$T_C = 25^{\circ}\text{C}$			29	A
I_{C80}		$T_C = 80^{\circ}\text{C}$			20	A
P_{tot}	total power dissipation	$T_C = 25^{\circ}\text{C}$			100	W
$V_{CE(sat)}$	collector emitter saturation voltage	$I_C = 20\text{ A}; V_{GE} = 15\text{ V}$		2.1 2.4	2.7	V V
$V_{GE(th)}$	gate emitter threshold voltage	$I_C = 0.5\text{ A}; V_{GE} = V_{CE}$	4.5	5.5	6.5	V
I_{CES}	collector emitter leakage current	$V_{CE} = V_{CES}; V_{GE} = 0\text{ V}$		0.8	1.0	mA mA
I_{GES}	gate emitter leakage current	$V_{GE} = \pm 20\text{ V}$			150	nA
C_{ies}	input capacitance	$V_{CE} = 25\text{ V}; V_{GE} = 0\text{ V}; f = 1\text{ MHz}$		900		pF
$Q_{G(on)}$	total gate charge	$V_{CE} = 300\text{ V}; V_{GE} = 15\text{ V}; I_C = 15\text{ A}$		76		nC
$t_{d(on)}$	turn-on delay time	inductive load $V_{CE} = 300\text{ V}; I_C = 20\text{ A}$ $V_{GE} = \pm 15\text{ V}; R_G = 47\ \Omega$	$T_{VJ} = 25^{\circ}\text{C}$	35		ns
t_r	current rise time			45		ns
$t_{d(off)}$	turn-off delay time			155		ns
t_f	current fall time			75		ns
E_{on}	turn-on energy per pulse			0.39		mJ
E_{off}	turn-off energy per pulse			0.4		mJ
$t_{d(on)}$	turn-on delay time	inductive load $V_{CE} = 300\text{ V}; I_C = 20\text{ A}$ $V_{GE} = \pm 15\text{ V}; R_G = 47\ \Omega$	$T_{VJ} = 125^{\circ}\text{C}$	35		ns
t_r	current rise time			45		ns
$t_{d(off)}$	turn-off delay time			165		ns
t_f	current fall time			150		ns
E_{on}	turn-on energy per pulse			0.6		mJ
E_{off}	turn-off energy per pulse			0.54		mJ
RBSOA	reverse bias safe operating area	$V_{GE} = \pm 15\text{ V}; R_G = 47\ \Omega; I_C = 40\text{ A}$	$T_{VJ} = 125^{\circ}\text{C}$	$V_{CEK} \leq V_{CES} - L_S \cdot di/dt$		V
I_{SC} (SCSOA)	short circuit safe operating area	$V_{CE} = 360\text{ V}; V_{GE} = \pm 15\text{ V};$ $R_G = 47\ \Omega; t_p = 10\ \mu\text{s};$ non-repetitive	$T_{VJ} = 125^{\circ}\text{C}$	90		A
R_{thJC}	thermal resistance junction to case	(per IGBT)			1.3	K/W
R_{thCH}	thermal resistance case to heatsink			0.45		K/W

Brake Chopper D7

				Ratings		
Symbol	Definitions	Conditions	min.	typ.	max.	Unit
V_{RRM}	max. repetitive reverse voltage	$T_{VJ} = 150^{\circ}\text{C}$			600	V
I_{F25}	forward current	$T_C = 25^{\circ}\text{C}$			22	A
I_{F80}		$T_C = 80^{\circ}\text{C}$			14	A
V_F	forward voltage	$I_F = 10\text{ A}; V_{GE} = 0\text{ V}$		1.7 1.4	2.2	V V
I_R	reverse current	$V_R = V_{RRM}$	$T_{VJ} = 25^{\circ}\text{C}$ $T_{VJ} = 125^{\circ}\text{C}$	0.2	0.1	mA mA
Q_{rr}	reverse recovery charge	$V_R = 300\text{ V}$ $di_F/dt = -300\text{ A}/\mu\text{s}$ $I_F = 10\text{ A}; V_{GE} = 0\text{ V}$	$T_{VJ} = 125^{\circ}\text{C}$	0.3		μC
I_{RM}	max. reverse recovery current			8.8		A
t_{rr}	reverse recovery time			95		ns
E_{rec}	reverse recovery energy			22		μJ
R_{thJC}	thermal resistance junction to case	(per diode)			2.5	K/W
R_{thCH}	thermal resistance case to heatsink			0.85		K/W

 $T_C = 25^{\circ}\text{C}$ unless otherwise stated

IXYS reserves the right to change limits, test conditions and dimensions.

20070425a

Input Rectifier Bridge D8 - D11

Symbol	Definitions	Conditions	min.	Ratings			Unit
				typ.	max.		
V_{RRM}	max. repetitive reverse voltage	$T_{VJ} = 25^{\circ}\text{C}$			1600		V
I_{FAV}	average forward current	sine 180°	$T_C = 80^{\circ}\text{C}$		22		A
I_{DAVM}	max. average DC output current	rect.; $d = 1/3$	$T_C = 80^{\circ}\text{C}$		62		A
I_{FSM}	max. forward surge current	$t = 10\text{ ms}$; sine 50 Hz	$T_{VJ} = 25^{\circ}\text{C}$ $T_{VJ} = 125^{\circ}\text{C}$		270 tbd		A A
I^2t	I^2t value for fusing	$t = 10\text{ ms}$; sine 50 Hz	$T_{VJ} = 25^{\circ}\text{C}$ $T_{VJ} = 125^{\circ}\text{C}$		365 tbd		A^2s A^2s
P_{tot}	total power dissipation		$T_C = 25^{\circ}\text{C}$		50		W
V_F	forward voltage	$I_F = 30\text{ A}$	$T_{VJ} = 25^{\circ}\text{C}$ $T_{VJ} = 125^{\circ}\text{C}$	1.35 1.35	1.6		V V
I_R	reverse current	$V_R = V_{RRM}$	$T_{VJ} = 25^{\circ}\text{C}$ $T_{VJ} = 125^{\circ}\text{C}$	0.3	0.01		mA mA
R_{thJC}	thermal resistance junction to case	(per diode)		0.7	2.1		K/W
R_{thCH}	thermal resistance case to heatsink	(per diode)					K/W


Temperature Sensor NTC

Symbol	Definitions	Conditions	min.	Ratings			Unit
				typ.	max.		
R_{25}	resistance	$T_C = 25^{\circ}\text{C}$	4.75	5.0	5.25		k Ω
$B_{25/50}$				3375			K

Module

Symbol	Definitions	Conditions	min.	Ratings			Unit
				typ.	max.		
T_{VJ}	operating temperature		-40		125		$^{\circ}\text{C}$
T_{VJM}	max. virtual junction temperature				150		$^{\circ}\text{C}$
T_{stg}	storage temperature		-40		125		$^{\circ}\text{C}$
V_{ISOL}	isolation voltage	$I_{ISOL} \leq 1\text{ mA}$; 50/60 Hz			2500		V~
CTI	comparative tracking index			-			
F_C	mounting force		40		80		N
d_S	creep distance on surface		12.7				mm
d_A	strike distance through air		12				mm
Weight				35			g

Equivalent Circuits for Simulation




Symbol	Definitions	Conditions	min.	Ratings			Unit
				typ.	max.		
V_0 R_0	rectifier diode	D8 - D13	$T_{VJ} = 125^{\circ}\text{C}$	0.9 12			V m Ω
V_0 R_0	IGBT	T1 - T6	$T_{VJ} = 125^{\circ}\text{C}$	1.1 40			V m Ω
V_0 R_0	free wheeling diode	D1 - D6	$T_{VJ} = 125^{\circ}\text{C}$	1.25 12			V m Ω
V_0 R_0	IGBT	T7	$T_{VJ} = 125^{\circ}\text{C}$	1.1 60			V m Ω
V_0 R_0	free wheeling diode	D7	$T_{VJ} = 125^{\circ}\text{C}$	1.25 25			V m Ω

IXYS reserves the right to change limits, test conditions and dimensions.

 $T_C = 25^{\circ}\text{C}$ unless otherwise stated


20070425a

Circuit Diagram




Outline Drawing

Dimensions in mm (1 mm = 0.0394")






Product Marking




Part number

M = Module
I = IGBT
A = IGBT (NPT)
A = Gen 1 / std
20 = Current Rating [A]
WB = 6-Pack + 3~ Rectifier Bridge & Brake Unit
600 = Reverse Voltage [V]
T = NTC
MH = MiniPack2


Ordering	Part Name	Marking on Product	Delivering Mode	Base Qty	Ordering Code
Standard	MIAA 20 WB 600 TMH	MIAA20WB600TMH	Box	20	503764


Typical output characteristics, $V_{GE} = 15\text{ V}$

Typical output characteristics (125 °C)



Typical transfer characteristics




Typical forward characteristics of freewheeling diode




Typical turn on gate charge




Typical switching energy versus collector current




Typical switching energy versus gate resistance




Typical turn-off characteristics of free wheeling diode




Typical turn-off characteristics of free wheeling diode



Typical forward characteristics of brake diode



Typical forward characteristics per rectifier



Typical thermistor resistance versus temperature

AMEYA360

Components Supply Platform

Authorized Distribution Brand :



Website :

Welcome to visit www.ameya360.com

Contact Us :

➤ Address :

401 Building No.5, JiuGe Business Center, Lane 2301, Yishan Rd
Minhang District, Shanghai , China

➤ Sales :

Direct +86 (21) 6401-6692
Email amall@ameya360.com
QQ 800077892
Skype ameyasales1 ameyasales2

➤ Customer Service :

Email service@ameya360.com

➤ Partnership :

Tel +86 (21) 64016692-8333
Email mkt@ameya360.com