SPECIFICATIONS Material: Silicone rubber conforms to A-A-59588, Class III, GR60, Gray (unless otherwise specified). Mounting Nut: Brass, nickel-plated **Temperature Range:** -94° F to $+400^{\circ}$ F (-70° C to $+204^{\circ}$ C). PUSHBUTTON-Pressure Range: Exceeds 15 psi internal and 1500 psi external. **BOOT** Operational Life: 50,000 actuations (minimum). Shelf Life: Excess of 25 years. **Resistant to:** Salt spray, sunlight, ozone, weather, fungus, and most acids and lubricating oils. Agency Recognition: UL & ULC Recognized to UL Std. 50 **CUSTOMER'S PANEL** Α **CUSTOMER'S BACKING FASTENER HEX** .375 [9.0]**CUSTOMER'S PUSHBUTTON SWITCH** Ø 0.188 **→ PUSHBUTTON** [4.78]BOOT CUSTOMER'S PANEL 0.203 [5.16]PERMISSIBLE RUBBER-0.313 OVERLAY .005 [0.127] MAX. [7.95]CUSTOMER'S BACKING FASTENER THREAD 1/4-40 NS-2B CUSTOMER'S PUSHBUTTON SWITCH TOLERANCES: UNLESS OTHERWISE NOTED \pm 1/32 [\pm 0.793]. CORRECTED I.D. PROFILE DWN: D. LAW CHKD BY: KF/FK 09.26.14 09.18.14 05.23.14 K CHANGED FORMAT **DAN LAW** REDRAWN FOR ACCURACY AND MAT'L CHANED S. GOK 06.29.09 CAD COMPUTER GENERATED 09.23.02 Н UPDATED, ADDED ORDER NUMBERS, DWG. NO. WAS 1231/SERIES W.P. 11.24.76 REV. DESCRIPTION DATE MAXIMUM AND MINIMUM MEASURE-TITLE: ENG. M. MORSE 01.21.60 MENTS ARE STATED DIRECTLY ON **BOOT, PUSH BUTTON** DWN: S. ANDREWS 01.21.60 EACH DIMENSION. SWITCH (N-5040R) MAT'L: CHKD. **B. GLICKSMAN** 01.21.60 SEE SPECIFICATION AND NOTES DWG.NO. **SCALE** FINISH: APM-HEXSEAL CORPORATION N5040R 6:1 SEE SPECIFICATION AND NOTES

AMEYA360 Components Supply Platform

Authorized Distribution Brand:

























Website:

Welcome to visit www.ameya360.com

Contact Us:

Address:

401 Building No.5, JiuGe Business Center, Lane 2301, Yishan Rd Minhang District, Shanghai , China

> Sales:

Direct +86 (21) 6401-6692

Email amall@ameya360.com

QQ 800077892

Skype ameyasales1 ameyasales2

Customer Service :

Email service@ameya360.com

Partnership :

Tel +86 (21) 64016692-8333

Email mkt@ameya360.com