

Features:



- D-Ring fastening is ideal for bundling trays and IC tubes
- Adjustable, releasable and reusable - easy to install
- Low charging hook and loop material meets ANSI/ESD S20.20
- Custom sizes available
- Operating Temperature: 300°F (149°C) max
- Melting Temperature: 459°F (237°C)
- Straps should be tested regularly to make sure they retain their ESD properties
- Made in America



35653	Low Charging Cable Tie, Non-Stretch D-Ring, 3/4 in (19 mm) x 18 in (457 mm)
35654	Low Charging Tie, Non-Stretch D-Ring, 3/4 in (19 mm) x 20 in (508 mm)
35655	Low Charging Cable Tie, Non-Stretch D-Ring, 3/4 in (19 mm) x 24 in (609 mm)
35656	Low Charging Cable Tie, Non-Stretch D-Ring, 3/4 in (19 mm) x 30 in (762 mm)

Specifications and procedures subject to change without notice.



Made in America



MENDA

LOW CHARGING CABLE TIES

3651 WALNUT AVE., CHINO, CA 91710
PHONE: (951) 627-2453 • FAX: (951) 755-8848
WEBSITE: MendaTools.com

**DRAWING
NUMBER:**
35653

DATE:
September
2012

AMEYA360

Components Supply Platform

Authorized Distribution Brand :



Website :

Welcome to visit www.ameya360.com

Contact Us :

➤ Address :

401 Building No.5, JiuGe Business Center, Lane 2301, Yishan Rd
Minhang District, Shanghai , China

➤ Sales :

Direct +86 (21) 6401-6692

Email amall@ameya360.com

QQ 800077892

Skype ameyasales1 ameyasales2

➤ Customer Service :

Email service@ameya360.com

➤ Partnership :

Tel +86 (21) 64016692-8333

Email mkt@ameya360.com