

# **SP-5**

#### **Description:**

Triad's high reliability audio transformers provide the durability and precision required in today's demanding designs. These transformers are available for a wide variety of applications.

#### **Electrical Specifications (@25C)**

Power	Matching Impedance		Max. Ma DC	DC Resistance (Ω)		Overall
level	Duinean	Saaan damu	Unbalance	Dulinaria	Sacardam.	Turns
(mW)	Primary	Secondary	in Primary	Primary	Secondary	Ratio
25	50,000 CT	1,000 CT	0.0	3,800.0	75.0	7.1:1.0


Frequency Response: + 2.0 DB, at 300 Hz to 100K Hz

Pri-Sec Hipot test (Pri-Sec): 1,000 VRMS for 1 sec.

Working voltage: 150VDC

#### **Construction:**


Plug-in terminals are precision spaced to provide fixed mounting centers. Epoxy molded case includes a .020" recess for ease of solder inspection. Leads are made of high strength Nickel alloy, gold plated and are .020" in diameter.




**RoHS Compliance:** As of manufacturing date February 2005, all standard products meet the requirements of 2002/95/EC, known as the RoHS initiative.

\*Upon printing, this document is considered "uncontrolled". Specifications are subjected to change without notice. Please contact Triad Magnetics' website for the most current version.

Web: www.TriadMagnetics.com Phone 951-277-0757 Fax 951-277-2757	22520B Temescal Canyon Road Corona, California 92883	Publish Date: June 19, 2006
---	--	-----------------------------





# **AMEYA360** Components Supply Platform

# Authorized Distribution Brand :



### Website :

Welcome to visit www.ameya360.com

# Contact Us :

#### > Address :

401 Building No.5, JiuGe Business Center, Lane 2301, Yishan Rd Minhang District, Shanghai , China

#### > Sales :

- Direct +86 (21) 6401-6692
- Email amall@ameya360.com
- QQ 800077892
- Skype ameyasales1 ameyasales2

#### > Customer Service :

Email service@ameya360.com

## > Partnership :

Tel +86 (21) 64016692-8333

Email mkt@ameya360.com