


# XPT™ 650V GenX3™ IXYN100N65C3H1 w/ Sonic Diode


Extreme Light Punch Through  
IGBT for 20-60kHz Switching



$$\begin{aligned} V_{CES} &= 650V \\ I_{C110} &= 90A \\ V_{CE(sat)} &\leq 2.30V \\ t_{fi(typ)} &= 50ns \end{aligned}$$

SOT-227B, miniBLOC

 E153432



G = Gate, C = Collector, E = Emitter

① either emitter terminal can be used as  
Main or Kelvin Emitter

| Symbol                        | Test Conditions                                                                                   | Maximum Ratings                         |                  |
|-------------------------------|---------------------------------------------------------------------------------------------------|-----------------------------------------|------------------|
| $V_{CES}$                     | $T_J = 25^\circ\text{C}$ to $175^\circ\text{C}$                                                   | 650                                     | V                |
| $V_{CGR}$                     | $T_J = 25^\circ\text{C}$ to $175^\circ\text{C}$ , $R_{GE} = 1M\Omega$                             | 650                                     | V                |
| $V_{GES}$                     | Continuous                                                                                        | $\pm 20$                                | V                |
| $V_{GEM}$                     | Transient                                                                                         | $\pm 30$                                | V                |
| $I_{C25}$                     | $T_C = 25^\circ\text{C}$                                                                          | 166                                     | A                |
| $I_{C110}$                    | $T_C = 110^\circ\text{C}$                                                                         | 90                                      | A                |
| $I_{F110}$                    | $T_C = 110^\circ\text{C}$                                                                         | 125                                     | A                |
| $I_{CM}$                      | $T_C = 25^\circ\text{C}$ , 1ms                                                                    | 440                                     | A                |
| $I_A$                         | $T_C = 25^\circ\text{C}$                                                                          | 50                                      | A                |
| $E_{AS}$                      | $T_C = 25^\circ\text{C}$                                                                          | 300                                     | mJ               |
| <b>SSOA</b><br><b>(RBSOA)</b> | $V_{GE} = 15V$ , $T_{VJ} = 150^\circ\text{C}$ , $R_G = 3\Omega$<br>Clamped Inductive Load         | $I_{CM} = 200$<br>$V_{CE} \leq V_{CES}$ | A                |
| $t_{sc}$<br><b>(SCSOA)</b>    | $V_{GE} = 15V$ , $V_{CE} = 360V$ , $T_J = 150^\circ\text{C}$<br>$R_G = 82\Omega$ , Non Repetitive | 8                                       | $\mu\text{s}$    |
| $P_C$                         | $T_C = 25^\circ\text{C}$                                                                          | 600                                     | W                |
| $T_J$                         |                                                                                                   | -55 ... +175                            | $^\circ\text{C}$ |
| $T_{JM}$                      |                                                                                                   | 175                                     | $^\circ\text{C}$ |
| $T_{stg}$                     |                                                                                                   | -55 ... +175                            | $^\circ\text{C}$ |
| $V_{ISOL}$                    | 50/60Hz                                                                                           | $t = 1\text{min}$                       | 2500 V~          |
|                               | $I_{ISOL} \leq 1\text{mA}$                                                                        | $t = 1\text{s}$                         | 3000 V~          |
| $M_d$                         | Mounting Torque                                                                                   | 1.5/13                                  | Nm/lb.in         |
|                               | Terminal Connection Torque                                                                        | 1.3/11.5                                | Nm/lb.in         |
| <b>Weight</b>                 |                                                                                                   | 30                                      | g                |

| Symbol        | Test Conditions<br>( $T_J = 25^\circ\text{C}$ , Unless Otherwise Specified) | Characteristic Values |      |                          |
|---------------|-----------------------------------------------------------------------------|-----------------------|------|--------------------------|
|               |                                                                             | Min.                  | Typ. | Max.                     |
| $BV_{CES}$    | $I_C = 250\mu\text{A}$ , $V_{GE} = 0V$                                      | 650                   |      | V                        |
| $V_{GE(th)}$  | $I_C = 250\mu\text{A}$ , $V_{CE} = V_{GE}$                                  | 3.5                   |      | 6.0 V                    |
| $I_{CES}$     | $V_{CE} = V_{CES}$ , $V_{GE} = 0V$<br>$T_J = 150^\circ\text{C}$             |                       |      | 50 $\mu\text{A}$<br>3 mA |
| $I_{GES}$     | $V_{CE} = 0V$ , $V_{GE} = \pm 20V$                                          |                       |      | $\pm 100$ nA             |
| $V_{CE(sat)}$ | $I_C = 70A$ , $V_{GE} = 15V$ , Note 1<br>$T_J = 150^\circ\text{C}$          | 1.85<br>2.05          |      | 2.30 V<br>V              |

## Features

- International Standard Package
- miniBLOC, with Aluminium Nitride Isolation
- 2500V~ Isolation Voltage
- Anti-Parallel Sonic Diode
- Optimized for 20-60kHz Switching
- Square RBSOA
- Short Circuit Capability
- High Current Handling Capability

## Advantages

- High Power Density
- Low Gate Drive Requirement

## Applications

- Power Inverters
- UPS
- Motor Drives
- SMPS
- PFC Circuits
- Battery Chargers
- Welding Machines
- Lamp Ballasts
- High Frequency Power Inverters


## Symbol Test Conditions

( $T_J = 25^\circ\text{C}$  Unless Otherwise Specified)

## Characteristic Values

|              |                                                                                                                                         | Min. | Typ. | Max.                    |
|--------------|-----------------------------------------------------------------------------------------------------------------------------------------|------|------|-------------------------|
| $g_{fs}$     | $I_C = 60\text{A}, V_{CE} = 10\text{V}, \text{Note 1}$                                                                                  | 30   | 52   | S                       |
| $C_{ies}$    | $V_{CE} = 25\text{V}, V_{GE} = 0\text{V}, f = 1\text{MHz}$                                                                              |      | 4980 | pF                      |
| $C_{oes}$    |                                                                                                                                         |      | 467  | pF                      |
| $C_{res}$    |                                                                                                                                         |      | 92   | pF                      |
| $Q_{g(on)}$  | $I_C = 70\text{A}, V_{GE} = 15\text{V}, V_{CE} = 0.5 \cdot V_{CES}$                                                                     |      | 164  | nC                      |
| $Q_{ge}$     |                                                                                                                                         |      | 39   | nC                      |
| $Q_{gc}$     |                                                                                                                                         |      | 73   | nC                      |
| $t_{d(on)}$  | Inductive load, $T_J = 25^\circ\text{C}$<br>$I_C = 50\text{A}, V_{GE} = 15\text{V}$<br>$V_{CE} = 400\text{V}, R_G = 3\Omega$<br>Note 2  |      | 28   | ns                      |
| $t_{ri}$     |                                                                                                                                         |      | 43   | ns                      |
| $E_{on}$     |                                                                                                                                         |      | 2.15 | mJ                      |
| $t_{d(off)}$ |                                                                                                                                         |      | 106  | ns                      |
| $t_{fi}$     |                                                                                                                                         |      | 50   | ns                      |
| $E_{off}$    |                                                                                                                                         |      | 0.84 | mJ                      |
| $t_{d(on)}$  | Inductive load, $T_J = 150^\circ\text{C}$<br>$I_C = 50\text{A}, V_{GE} = 15\text{V}$<br>$V_{CE} = 400\text{V}, R_G = 3\Omega$<br>Note 2 |      | 27   | ns                      |
| $t_{ri}$     |                                                                                                                                         |      | 45   | ns                      |
| $E_{on}$     |                                                                                                                                         |      | 2.40 | mJ                      |
| $t_{d(off)}$ |                                                                                                                                         |      | 136  | ns                      |
| $t_{fi}$     |                                                                                                                                         |      | 77   | ns                      |
| $E_{off}$    |                                                                                                                                         |      | 1.20 | mJ                      |
| $R_{thJC}$   |                                                                                                                                         |      |      | 0.25 $^\circ\text{C/W}$ |
| $R_{thCS}$   |                                                                                                                                         |      | 0.05 | $^\circ\text{C/W}$      |

## SOT-227B miniBLOC (IXYN)



| SYM | INCHES |       | MILLIMETERS |       |
|-----|--------|-------|-------------|-------|
|     | MIN    | MAX   | MIN         | MAX   |
| A   | 1.240  | 1.255 | 31.50       | 31.88 |
| B   | .307   | .323  | 7.80        | 8.20  |
| C   | .161   | .169  | 4.09        | 4.29  |
| D   | .161   | .169  | 4.09        | 4.29  |
| E   | .161   | .169  | 4.09        | 4.29  |
| F   | .587   | .595  | 14.91       | 15.11 |
| G   | 1.186  | 1.193 | 30.12       | 30.30 |
| H   | 1.489  | 1.505 | 37.80       | 38.23 |
| J   | .460   | .481  | 11.68       | 12.22 |
| K   | .351   | .378  | 8.92        | 9.60  |
| L   | .030   | .033  | 0.76        | 0.84  |
| M   | .496   | .506  | 12.60       | 12.85 |
| N   | .990   | 1.001 | 25.15       | 25.42 |
| O   | .078   | .084  | 1.98        | 2.13  |
| P   | .195   | .235  | 4.95        | 5.97  |
| Q   | 1.045  | 1.059 | 26.54       | 26.90 |
| R   | .155   | .174  | 3.94        | 4.42  |
| S   | .186   | .191  | 4.72        | 4.85  |
| T   | .968   | .987  | 24.59       | 25.07 |
| U   | -.002  | .004  | -0.05       | 0.1   |
| V   | .130   | .180  | 3.30        | 4.57  |
| W   | .780   | .830  | 19.81       | 21.08 |

## Reverse Sonic Diode (FRD)

## Symbol Test Conditions

( $T_J = 25^\circ\text{C}$  Unless Otherwise Specified)

## Characteristic Values

|            |                                                                                                                                   | Min. | Typ.       | Max.                    |
|------------|-----------------------------------------------------------------------------------------------------------------------------------|------|------------|-------------------------|
| $V_F$      | $I_F = 100\text{A}, V_{GE} = 0\text{V}, \text{Note 1}$<br>$T_J = 150^\circ\text{C}$                                               |      | 1.7<br>1.8 | V<br>V                  |
| $I_{RM}$   | $I_F = 100\text{A}, V_{GE} = 0\text{V},$<br>$-di_F/dt = 1500\text{A}/\mu\text{s}, V_R = 300\text{V}$<br>$T_J = 150^\circ\text{C}$ |      | 95         | A                       |
| $t_{rr}$   |                                                                                                                                   |      | 100        | ns                      |
| $R_{thJC}$ |                                                                                                                                   |      |            | 0.42 $^\circ\text{C/W}$ |

## Notes:







1. Pulse test,  $t \leq 300\mu\text{s}$ , duty cycle,  $d \leq 2\%$ .
2. Switching times & energy losses may increase for higher  $V_{CE}(\text{clamp})$ ,  $T_J$  or  $R_G$ .







## PRELIMINARY TECHNICAL INFORMATION







The product presented herein is under development. The Technical Specifications offered are derived from a subjective evaluation of the design, based upon prior knowledge and experience, and constitute a "considered reflection" of the anticipated result. IXYS reserves the right to change limits, test conditions, and dimensions without notice.

IXYS Reserves the Right to Change Limits, Test Conditions, and Dimensions.

IXYS MOSFETs and IGBTs are covered 4,835,592 4,931,844 5,049,961 5,237,481 6,162,665 6,404,065 B1 6,683,344 6,727,585 7,005,734 B2 7,157,338B2  
by one or more of the following U.S. patents: 4,860,072 5,017,508 5,063,307 5,381,025 6,259,123 B1 6,534,343 6,710,405 B2 6,759,692 7,063,975 B2  
4,881,106 5,034,796 5,187,117 5,486,715 6,306,728 B1 6,583,505 6,710,463 6,771,478 B2 7,071,537

**Fig. 1. Output Characteristics @  $T_J = 25^\circ\text{C}$** 

**Fig. 2. Extended Output Characteristics @  $T_J = 25^\circ\text{C}$** 

**Fig. 3. Output Characteristics @  $T_J = 150^\circ\text{C}$** 

**Fig. 4. Dependence of  $V_{CE(sat)}$  on Junction Temperature**

**Fig. 5. Collector-to-Emitter Voltage vs. Gate-to-Emitter Voltage**

**Fig. 6. Input Admittance**


**Fig. 7. Transconductance**

**Fig. 8. Gate Charge**

**Fig. 9. Capacitance**

**Fig. 10. Reverse-Bias Safe Operating Area**

**Fig. 11. Forward-Bias Safe Operating Area**

**Fig. 12. Maximum Transient Thermal Impedance (IGBT)**


**Fig. 13. Inductive Switching Energy Loss vs. Gate Resistance**

**Fig. 14. Inductive Switching Energy Loss vs. Collector Current**

**Fig. 15. Inductive Switching Energy Loss vs. Junction Temperature**

**Fig. 16. Inductive Turn-off Switching Times vs. Gate Resistance**

**Fig. 17. Inductive Turn-off Switching Times vs. Collector Current**

**Fig. 18. Inductive Turn-off Switching Times vs. Junction Temperature**






**Fig. 19. Inductive Turn-on Switching Times vs. Gate Resistance**

**Fig. 20. Inductive Turn-on Switching Times vs. Collector Current**

**Fig. 21. Inductive Turn-on Switching Times vs. Junction Temperature**

**Fig. 22. Maximum Peak Load Current vs. Frequency**


Fig. 23. Typ. Forward characteristics




Fig. 24. Typ. Reverse Recovery Charge  $Q_{rr}$  vs.  $-di_F/dt$




Fig. 25. Typ. Peak Reverse Current  $I_{RM}$  vs.  $-di_F/dt$




Fig. 26. Typ. Recovery Time  $t_{rr}$  vs.  $-di_F/dt$




Fig. 27. Typ. Recovery Energy  $E_{rec}$  vs.  $-di_F/dt$





Fig. 28. Maximum Transient Thermal Impedance ( Diode )



# AMEYA360

Components Supply Platform

Authorized Distribution Brand :



Website :

Welcome to visit [www.ameya360.com](http://www.ameya360.com)

Contact Us :

➤ Address :

401 Building No.5, JiuGe Business Center, Lane 2301, Yishan Rd  
Minhang District, Shanghai , China

➤ Sales :

Direct     +86 (21) 6401-6692  
  
Email       amall@ameya360.com  
  
QQ         800077892  
  
Skype       ameyasales1 ameyasales2

➤ Customer Service :

Email       service@ameya360.com

➤ Partnership :

Tel         +86 (21) 64016692-8333  
  
Email       mkt@ameya360.com