





CAVITY NO.	DIM. ACROSS HEX FLATS	GROOVE ACCOMMODATIONS
1	.178 +/- .003	RG174 (3 PC)
2	.324 +/- .003	RG6 (3 PC 179 BELDEN 8281), RG58, RG59, RG62 & PLENUM 58, 59, 62(2 PC).
3	.068 +/- .003	CENTER CONTACT

REF. CAD FILE: H:\DEPT611\TOOLS\CTL-

REMOVE ALL BURRS, BREAK CORNERS AND SHARP EDGES .005 MAXIMUM UNLESS OTHERWISE SPECIFIED

NOTICE — These drawings, specifications, or other data (1) are, and remain the property of Amphenol Corp. (2) must be returned upon request, and (3) are confidential and are not to be disclosed to any person other than those to whom they are given by Amphenol Corp. The furnishing of these drawings, specifications, or other data by Amphenol Corp., or by any other person to anyone for any purpose is not to be regarded by implication or otherwise as in any manner licensing, granting rights or permitting such holder or any other person to manufacture, use or sell any product, process or design, patented or otherwise, that may in any way be related to or disclosed by said drawings, specifications or other data

NEXT ASSY	USED ON	UNLESS OTHERWISE SPECIFIED ARE IN INCHES. TOLERANCES SPECIFIED ARE: 2 PLACE DECIMAL ±.015 (0.381 mm) 3 PLACE DECIMAL ±.005 (0.127 mm)
MATERIAL AS PURCHASED		REFERENCE D
SPECIFICATION -----		REF. EAR# 9
FINISH AS PURCHASED		



NOTES:

1. INITIAL TOOL SETTING REQUIRMENTS:

WITH DIES FIRMLY AFFIXED IN TOOL ON THE DIE MNT'G. SURFACES, CLOSE THE TOOL FULLY (UNTIL THE RATCHET RELEASES) WITH 25-35 LBS. HAND FORCE. THE DIES MUST BE 'BUTTED' (TOUCHING BOTH FRONT & REAR SURFACES). THE RATCHET ADJUSTER WHEEL SHOULD BE POSITIONED IN THE CENTER INDENT (+/- ONE INDENT POSITION).

2. NOTE: LABEL 999-307 MUST BE AFFIXED TO TOOL CONTAINER BOX.

CTL-2	
DRAWING NUMBER	ISSUE C

RFX PROGRAM

T611\TOOLS\CTL-2										
		PART NO.		QUAN	UOM	ITEM LINE NO.	DESCRIPTION		CODE	FINISH
LIST OF MATERIAL										
UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES. TOLERANCES NOT OTHERWISE SPECIFIED ARE: 2 PLACE DECIMAL ±.015 (0,381 mm) 3 PLACE DECIMAL ±.005 (0,127 mm) ANGLES ± 1° REFERENCE DRAWING NO. REF. EAR# 961726-1		DRAWN BY J. MULVEY		DATE 6-13-90		TITLE QUICK CRIMP TOOL FOR BNC & TNC CRIMP PLUGS- 2 & 3 PC. TYPES			Amphenol Corporation RF/Microwave Operations Danbury, Conn. U.S.A.	
		CHECKED D. ROYCE		DATE 6-15-90						
		ENGINEER D. ROYCE		DATE 6-15-90						
		QUALITY ASSURANCE W. JOHNSTON		DATE 6-19-90						
		MFG. ENG. H. FREDLUND		DATE 6-19-90		CODE IDENTIFICATION 74868	DRAWING SIZE C	DRAWING NO. CTL-2		ISSUE C

Amphenol Corporation
RF/Microwave Operations
Danbury, Conn. U.S.A.

AMEYA360

Components Supply Platform

Authorized Distribution Brand :



Website :

Welcome to visit www.ameya360.com

Contact Us :

➤ Address :

401 Building No.5, JiuGe Business Center, Lane 2301, Yishan Rd
Minhang District, Shanghai , China

➤ Sales :

Direct +86 (21) 6401-6692

Email amall@ameya360.com

QQ 800077892

Skype ameyasales1 ameyasales2

➤ Customer Service :

Email service@ameya360.com

➤ Partnership :

Tel +86 (21) 64016692-8333

Email mkt@ameya360.com