

**Micro Commercial Components** 



Micro Commercial Components 20736 Marilla Street Chatsworth CA 91311

Phone: (818) 701-4933 Fax: (818) 701-4939 60S05 thru **60S10** 

# 6 Amp Axial-Lead **Glass Passivated** Rectifier 50 - 1000 Volts

## **Features**

- Lead Free Finish/RoHS Compliant(Note 1) ("P" Suffix designates RoHS Compliant. See ordering information)
- Epoxy meets UL 94 V-0 flammability rating
- Moisture Sensitivity Level 1
- High Surge Current Capability and Low Leakage
- Glass Passivated Chip
- Halogen free available upon request by adding suffix "-HF"

- Maximum Ratings
  Operating Junction Temperature: -55°C to +150°C
- Storage Temperature: -55°C to +150°C


| MCC<br>Catalog<br>Number | Device<br>Marking | Maximum<br>Reccurrent<br>Peak<br>Reverse<br>Voltage | Maximum<br>RMS<br>Voltage | Maximum<br>DC<br>Blocking<br>Voltage |
|--------------------------|-------------------|---|---------------------------|--------------------------------------|
| 60S05                    | 60S05             | 50V   | 35V                       | 50V                                  |
| 60S1                     | 60S1              | 100V  | 70V                       | 100V                                 |
| 60S2                     | 60S2              | 200V  | 140V                      | 200V                                 |
| 60S4                     | 60S4              | 400V  | 280V                      | 400V                                 |
| 60S6                     | 60S6              | 600V  | 420V                      | 600V                                 |
| 60S8                     | 60S8              | 800V  | 560V                      | 800V                                 |
| 60S10                    | 60S10             | 1000V   | 700V                      | 1000V                                |

### Electrical Characteristics @ 25°C Unless Otherwise Specified

| Average Forward<br>Current                                       | I <sub>F(AV)</sub> | 6.0A         | T <sub>A</sub> = 100°C                            |
|--|--------------------|--------------|---|
| Peak Forward Surge<br>Current                                    | I <sub>FSM</sub>   | 200A         | 8.3ms, half sine                                  |
| Maximum<br>Instantaneous<br>Forward Voltage                      | V <sub>F</sub>     | 1.0V         | I <sub>FM</sub> = 6.0A;<br>T <sub>J</sub> = 25°C* |
| Maximum DC<br>Reverse Current At<br>Rated DC Blocking<br>Voltage | I <sub>R</sub>     | ξiΑ<br>100μΑ | T <sub>J</sub> = 25°C<br>T <sub>J</sub> = 100°C   |
| Typical Junction<br>Capacitance                                  | C <sub>J</sub>     | 150pF        | Measured at 1.0MHz, V <sub>R</sub> =4.0V          |

Notes: 1. High Temperature Solder Exemption Applied, see EU Directive Annex 7. 2.Pulse test: Pulse width 300 sec, Duty cycle 1%

## **DO-201AD**




| DIMENSIONS |        |      |       |      |      |  |  |
|------------|--------|------|-------|------|------|--|--|
|            |        |      |       |      |      |  |  |
|            | INCHES |      | MM    |      |      |  |  |
| DIM        | MIN    | MAX  | MIN   | MAX  | NOTE |  |  |
| Α          | .287   | .374 | 7.30  | 9.50 |      |  |  |
| В          | .189   | .208 | 4.80  | 5.30 |      |  |  |
| С          | .048   | .052 | 1.20  | 1.30 |      |  |  |
| D          | 1 000  |      | 25.40 |      |      |  |  |

### 60S05 thru 60S10




Figure 1
Typical Forward Characteristics




Instantaneous Forward Current - Amperesversus Instantaneous Forward Voltage - Volts

Figure 3
Maximum Non-Repetitive Forward Surge Current




Peak Forward Surge Current - Amperesversus Number Of Cycles At 60Hz - Cycles

**Micro Commercial Components** 



Average Forward Rectified Current - Amperes *versus* Ambient Temperature - °C

Figure 4
Typical Reverse Characteristics



Instantaneous Reverse Leakage Current - MicroAmperesversus Percent Of Rated Peak Reverse Voltage - Volts



### **Ordering Information:**

| Device         | Packing                        |  |
|----------------|--------------------------------|--|
| Part Number-TP | Tape&Reel: 1.2Kpcs/Reel        |  |
| Part Number-AP | Ammo Packing: 1.2Kpcs/Ammo Box |  |
| Part Number-BP | Bulk: 12Kpcs/Carton            |  |

Note: Adding "-HF" suffix for halogen free, eg. Part Number-TP-HF

### \*\*\*IMPORTANT NOTICE\*\*\*

**Micro Commercial Components Corp.** reserves the right to make changes without further notice to any product herein to make corrections, modifications, enhancements, improvements, or other changes. **Micro Commercial Components Corp.** does not assume any liability arising out of the application or use of any product described herein; neither does it convey any license under its patent rights, nor the rights of others. The user of products in such applications shall assume all risks of such use and will agree to hold **Micro Commercial Components Corp.** and all the companies whose products are represented on our website, harmless against all damages.

#### \*\*\*LIFE SUPPORT\*\*\*

MCC's products are not authorized for use as critical components in life support devices or systems without the express written approval of Micro Commercial Components Corporation.

### \*\*\*CUSTOMER AWARENESS\*\*\*

Counterfeiting of semiconductor parts is a growing problem in the industry. Micro Commercial Components (MCC) is taking strong measures to protect ourselves and our customers from the proliferation of counterfeit parts. MCC strongly encourages customers to purchase MCC parts either directly from MCC or from Authorized MCC Distributors who are listed by country on our web page cited below. Products customers buy either from MCC directly or from Authorized MCC Distributors are genuine parts, have full traceability, meet MCC's quality standards for handling and storage. MCC will not provide any warranty coverage or other assistance for parts bought from Unauthorized Sources. MCC is committed to combat this global problem and encourage our customers to do their part in stopping this practice by buying direct or from authorized distributors.

# AMEYA360 Components Supply Platform

## **Authorized Distribution Brand:**

























## Website:

Welcome to visit www.ameya360.com

### Contact Us:

### Address:

401 Building No.5, JiuGe Business Center, Lane 2301, Yishan Rd Minhang District, Shanghai , China

### > Sales:

Direct +86 (21) 6401-6692

Email amall@ameya360.com

QQ 800077892

Skype ameyasales1 ameyasales2

### Customer Service :

Email service@ameya360.com

## Partnership :

Tel +86 (21) 64016692-8333

Email mkt@ameya360.com