

**HEYCO**



## Heyco® Open/Closed Universal Bushings

Mounting Hole Diameter Range: .500" (12,7 mm) to 2.500" (63,5 mm)

- **Split design allows side entry** and encirclement of preassembled harnesses, power cords, capillary tubes or other assemblies that have segments larger than the bushing's ID.
- Parts can be assembled into holes that already contain cables or tubing.
- Only fingertip pressure required to snap-lock the bushing into its mounting hole.
- Locking fingers in fractional increments up to the maximum panel thickness.
- Flexible shutters adjust to accommodate and support any shape from .125" (3,2 mm) to a maximum inside diameter of 1.970" (43,2 mm).
- Absorb vibration, cushion and insulate cables, tubing, hoses or shafts.
- Available in multiple sizes for use in .500" (12,7 mm) to 2.500" (63,5 mm) diameter holes.

| MOUNTING HOLE DIAMETER |     | PART NO. | DESCRIPTION | PART DIMENSIONS         |     |                 |     |                  |     |
|------------------------|-----|----------|-------------|-------------------------|-----|-----------------|-----|------------------|-----|
|                        |     |          |             | Maximum Inside Diameter |     | A Head Diameter |     | B Overall Height |     |
| in.                    | mm. | Black    |             | in.                     | mm. | in.             | mm. | in.              | mm. |



### Multiple Locking Steps for Panel Thickness up to .125" (3,2 mm)

|       |      |        |           |       |      |       |      |      |      |
|-------|------|--------|-----------|-------|------|-------|------|------|------|
| .500  | 12,7 | 2055SP | OCUB 500  | .312  | 7,6  | .560  | 14,2 | .385 | 9,8  |
| .625  | 15,9 | 2077SP | OCUB 625  | .437  | 11,1 | .690  | 17,5 |      |      |
| .750  | 19,1 | 2089SP | OCUB 750  | .500  | 12,7 | .800  | 20,3 |      |      |
| .875  | 22,2 | 2119SP | OCUB 875  | .562  | 14,3 | .921  | 23,4 |      |      |
| 1.000 | 25,4 | 2137SP | OCUB 1000 | .750  | 19,1 | 1.050 | 26,7 | .406 | 10,3 |
| 1.093 | 27,8 | 2157SP | OCUB 1093 | .812  | 20,6 | 1.160 | 29,5 |      |      |
| 1.250 | 31,8 | 2196SP | OCUB 1250 | .937  | 23,8 | 1.440 | 36,6 |      |      |
| 1.375 | 34,9 | 2184SP | OCUB 1375 | 1.000 | 25,4 | 1.440 | 36,6 |      |      |
| 1.500 | 38,1 | 2213SP | OCUB 1500 | 1.062 | 26,9 | 1.560 | 39,6 | .421 | 10,7 |
| 2.000 | 50,8 | 2422SP | OCUB 2000 | 1.640 | 41,7 | 2.120 | 53,9 |      |      |

### Multiple Locking Steps for Panel Thickness up to .250" (6,4 mm)

|       |      |        |          |       |      |       |      |      |      |
|-------|------|--------|----------|-------|------|-------|------|------|------|
| 2.500 | 63,5 | 2440SP | OCUB 2.5 | 1.970 | 43,2 | 2.600 | 66,0 | .720 | 18,3 |
|-------|------|--------|----------|-------|------|-------|------|------|------|

Standard color black. Consult Heyco for white and other colors.



*Quick Specs*

**Material**  
**Certifications**

Nylon 6/6

Recognized under the Component Program of Underwriters' Laboratories, File E15331



Certified by the Canadian Standards Association, File 8919

**Flammability Rating**

94V-2

**Material Temperature Index**

257°F (125°C)–Maximum temperature on part not to exceed 221°F (105°C)

# AMEYA360

Components Supply Platform

Authorized Distribution Brand :



Website :

Welcome to visit [www.ameya360.com](http://www.ameya360.com)

Contact Us :

➤ Address :

401 Building No.5, JiuGe Business Center, Lane 2301, Yishan Rd  
Minhang District, Shanghai , China

➤ Sales :

Direct    +86 (21) 6401-6692  
  
Email     amall@ameya360.com  
  
QQ        800077892  
  
Skype     ameyasales1 ameyasales2

➤ Customer Service :

Email     service@ameya360.com

➤ Partnership :

Tel        +86 (21) 64016692-8333  
  
Email     mkt@ameya360.com