NPN/PNP Silicon AF Transistor Arrays

- For AF input stage and driver applications
- High current gain
- Low collector-emitter saturation voltage
- Two (galvanic) internal isolated NPN/PNP transistor in one package
- Pb-free (RoHS compliant) package
- Qualified according AEC Q101



BC846PN
BC846UPN
BC847PN



Type	Marking	Pin Configuration						Package
BC846PN	1Os	1=E1	2=B1	3=C2	4=E2	5=B2	6=C1	SOT363
BC846UPN	1Os	1=E1	2=B1	3=C2	4=E2	5=B2	6=C1	SC74
BC847PN	1Ps	1=E1	2=B1	3=C2	4=E2	5=B2	6=C1	SOT363

Maximum Ratings

Parameter	Symbol	Value	Unit
Collector-emitter voltage	V_{CEO}		V
BC846PN/UPN		65	
BC847PN		45	
Collector-emitter voltage	V_{CES}		
BC846PN/UPN		80	
BC847PN		50	
Collector-base voltage	V_{CBO}		
BC846PN/UPN		80	
BC847PN		50	
Emitter-base voltage	V_{EBO}	6	
Collector current	I_C	100	mA
Peak collector current, $t_p \leq 10$ ms	I_{CM}	200	
Total power dissipation-	P_{tot}		mW
$T_S \leq 115°C$, BC846PN, BC847PN		250	
$T_S \leq 118°C$, BC846UPN		250	
Junction temperature	T_j	150	°C
Storage temperature	T_{stg}	-65 ... 150	

Thermal Resistance

Parameter	Symbol	Value	Unit
Junction - soldering point[1)]	R_{thJS}		K/W
BC846PN, BC847PN		≤ 140	
BC846UPN		≤ 130	

[1]For calculation of R_{thJA} please refer to Application Note AN077 (Thermal Resistance Calculation)

Electrical Characteristics at T_A = 25°C, unless otherwise specified

Parameter	Symbol	Values			Unit
		min.	typ.	max.	
DC Characteristics					
Collector-emitter breakdown voltage	$V_{(BR)CEO}$				V
I_C = 10 mA, I_B = 0 , BC846PN/UPN		65	-	-	
I_C = 10 mA, I_B = 0 , BC847PN		45	-	-	
Collector-base breakdown voltage	$V_{(BR)CBO}$				
I_C = 10 µA, I_E = 0 , BC846PN/UPN		80	-	-	
I_C = 10 µA, I_E = 0 , BC847PN		50	-	-	
Collector-emitter breakdown voltage	$V_{(BR)CES}$				
I_C = 10 µA, V_{BE} = 0 , BC846PN/UPN		80	-	-	
I_C = 10 µA, V_{BE} = 0 , BC847PN		50	-	-	
Emitter-base breakdown voltage	$V_{(BR)EBO}$	6	-	-	
I_E = 1 µA, I_C = 0					
Collector-base cutoff current	I_{CBO}				µA
V_{CB} = 50 V, I_E = 0		-	-	0.015	
V_{CB} = 30 V, I_E = 0 , T_A = 150 °C		-	-	5	
DC current gain-	h_{FE}				-
I_C = 10 µA, V_{CE} = 5 V		-	250	-	
I_C = 2 mA, V_{CE} = 5 V		200	290	450	
Collector-emitter saturation voltage[1)]	V_{CEsat}				mV
I_C = 10 mA, I_B = 0.5 mA		-	90	300	
I_C = 100 mA, I_B = 5 mA		-	200	650	
Base emitter saturation voltage-[1)]	V_{BEsat}				
I_C = 10 mA, I_B = 0.5 mA		-	700	-	
I_C = 100 mA, I_B = 5 mA		-	900	-	
Base-emitter voltage-[1)]	$V_{BE(ON)}$				
I_C = 2 mA, V_{CE} = 5 V		580	660	750	
I_C = 10 mA, V_{CE} = 5 V		-	-	820	

[1]Pulse test: t 300µs, D = 2%

Electrical Characteristics at T_A = 25°C, unless otherwise specified

Parameter	Symbol	Values			Unit
		min.	typ.	max.	
AC Characteristics					
Transition frequency I_C = 10 mA, V_{CE} = 5 V, f = 100 MHz	f_T	-	250	-	MHz
Collector-base capacitance V_{CB} = 10 V, f = 1 MHz	C_{cb}	-	1.5	-	pF
Emitter-base capacitance V_{EB} = 0.5 V, f = 1 MHz	C_{eb}	-	8	-	
Short-circuit input impedance I_C = 2 mA, V_{CE} = 5 V, f = 1 kHz	h_{11e}	-	4.5	-	kΩ
Open-circuit reverse voltage transf. ratio I_C = 2 mA, V_{CE} = 5 V, f = 1 kHz	h_{12e}	-	2	-	10^{-4}
Short-circuit forward current transf. ratio I_C = 2 mA, V_{CE} = 5 V, f = 1 kHz	h_{21e}	-	330	-	-
Open-circuit output admittance I_C = 2 mA, V_{CE} = 5 V, f = 1 kHz	h_{22e}	-	30	-	µS

DC current gain $h_{FE} = f(I_C)$

V_{CE} = 5 V



Collector-emitter saturation voltage

$I_C = f(V_{CEsat})$, h_{FE} = 20



Base-emitter saturation voltage

$I_C = f(V_{BEsat})$, h_{FE} = 20



Collector cutoff current $I_{CBO} = f(T_A)$

V_{CBO} = 30 V



Transition frequency $f_T = f(I_C)$
V_{CE} = 5 V, f = 100 MHz



Collector-base capacitance $C_{cb} = f(V_{CB})$
Emitter-base capacitance $C_{eb} = f(V_{EB})$



Total power dissipation $P_{tot} = f(T_S)$
BC846PN, BC847PN



Total power dissipation $P_{tot} = f(T_S)$
BC846UPN



Permissible Pulse Load $R_{thJS} = f(t_p)$

BC846PN, BC847PN



Permissible Pulse Load

$P_{totmax}/P_{totDC} = f(t_p)$

BC846PN, BC847PN



Permissible Puls Load $R_{thJS} = f(t_p)$

BC846UPN



Permissible Pulse Load

$P_{totmax}/P_{totDC} = f(t_p)$

BC846UPN



Package Outline



Foot Print



Marking Layout (Example)

Small variations in positioning of
Date code, Type code and Manufacture are possible.



Standard Packing

Reel ø180 mm = 3.000 Pieces/Reel
Reel ø330 mm = 10.000 Pieces/Reel

For symmetric types no defined Pin 1 orientation in reel.



Package Outline



Foot Print



Marking Layout (Example)

Small variations in positioning of
Date code, Type code and Manufacture are possible.



Standard Packing

Reel ø180 mm = 3.000 Pieces/Reel
Reel ø330 mm = 10.000 Pieces/Reel

For symmetric types no defined Pin 1 orientation in reel.



Edition 2009-11-16

Published by
Infineon Technologies AG
81726 Munich, Germany

© 2009 Infineon Technologies AG
All Rights Reserved.

Legal Disclaimer

The information given in this document shall in no event be regarded as a guarantee of conditions or characteristics. With respect to any examples or hints given herein, any typical values stated herein and/or any information regarding the application of the device, Infineon Technologies hereby disclaims any and all warranties and liabilities of any kind, including without limitation, warranties of non-infringement of intellectual property rights of any third party.

Information

For further information on technology, delivery terms and conditions and prices, please contact the nearest Infineon Technologies Office (<www.infineon.com>).

Warnings

Due to technical requirements, components may contain dangerous substances. For information on the types in question, please contact the nearest Infineon Technologies Office.
Infineon Technologies components may be used in life-support devices or systems only with the express written approval of Infineon Technologies, if a failure of such components can reasonably be expected to cause the failure of that life-support device or system or to affect the safety or effectiveness of that device or system. Life support devices or systems are intended to be implanted in the human body or to support and/or maintain and sustain and/or protect human life. If they fail, it is reasonable to assume that the health of the user or other persons may be endangered.

AMEYA360
Components Supply Platform

Authorized Distribution Brand :

Website :

Welcome to visit www.ameya360.com

Contact Us :

Address :

401 Building No.5, JiuGe Business Center, Lane 2301, Yishan Rd
Minhang District, Shanghai , China

Sales :

Direct +86 (21) 6401-6692

Email amall@ameya360.com

QQ 800077892

Skype ameyasales1 ameyasales2

Customer Service :

Email service@ameya360.com

Partnership :

Tel +86 (21) 64016692-8333

Email mkt@ameya360.com