




## Silicon PIN Diode

- For low loss RF switches and attenuators
- Very low capacitance at zero volt reverse bias at frequencies above 1 GHz (typ. 0.25 pF)
- Low forward resistance (typ. 1.5  $\Omega$  @ 5mA)
- Low harmonics
- Pb-free (RoHS compliant) package



### BAR67-02V

### BAR67-04



| Type      | Package | Configuration | $L_S$ (nH) | Marking |
|-----------|---------|---------------|------------|---------|
| BAR67-02V | SC79    | single        | 0.6        | T       |
| BAR67-04  | SOT23   | series        | 1.8        | PMs     |

### Maximum Ratings at $T_A = 25^\circ\text{C}$ , unless otherwise specified

| Parameter                                | Symbol    | Value       | Unit             |
|------------------------------------------|-----------|-------------|------------------|
| Diode reverse voltage                    | $V_R$     | 150         | V                |
| Forward current                          | $I_F$     | 200         | mA               |
| Total power dissipation                  | $P_{tot}$ |             | mW               |
| $T_S \leq 118^\circ\text{C}$ , BAR67-02V |           | 250         |                  |
| $T_S \leq 25^\circ\text{C}$ , BAR67-04   |           | 250         |                  |
| Junction temperature                     | $T_j$     | 150         | $^\circ\text{C}$ |
| Operating temperature range              | $T_{op}$  | -55 ... 125 |                  |
| Storage temperature                      | $T_{stg}$ | -55 ... 150 |                  |

### Thermal Resistance

| Parameter                                | Symbol     | Value      | Unit |
|------------------------------------------|------------|------------|------|
| Junction - soldering point <sup>1)</sup> | $R_{thJS}$ |            | K/W  |
| BAR67-02V                                |            | $\leq 115$ |      |
| BAR67-04                                 |            | $\leq 290$ |      |


<sup>1)</sup>For calculation of  $R_{thJA}$  please refer to Application Note Thermal Resistance

**Electrical Characteristics at  $T_A = 25^\circ\text{C}$ , unless otherwise specified**

| Parameter                                                                                                                     | Symbol      | Values           |                              |                       | Unit |
|-------------------------------------------------------------------------------------------------------------------------------|-------------|------------------|------------------------------|-----------------------|------|
|                                                                                                                               |             | min.             | typ.                         | max.                  |      |
| DC Characteristics                                                                                                            |             |                  |                              |                       |      |
| Breakdown voltage<br>$I_{(BR)} = 5 \mu A$                                                                                     | $V_{(BR)}$  | 150              | -                            | -                     | V    |
| Reverse current<br>$V_R = 100 V$                                                                                              | $I_R$       | -                | -                            | 20                    | nA   |
| Forward voltage<br>$I_F = 50 mA$                                                                                              | $V_F$       | -                | 0.95                         | 1.2                   | V    |
| AC Characteristics                                                                                                            |             |                  |                              |                       |      |
| Diode capacitance<br>$V_R = 5 V, f = 1 MHz$<br>$V_R = 0 V, f = 100 MHz$<br>$V_R = 0 V, f = 1 GHz$<br>$V_R = 0 V, f = 1.8 GHz$ | $C_T$       | -<br>-<br>-<br>- | 0.35<br>0.35<br>0.25<br>0.23 | 0.55<br>0.9<br>-<br>- | pF   |
| Reverse parallel resistance<br>$V_R = 0 V, f = 100 MHz$<br>$V_R = 0 V, f = 1 GHz$<br>$V_R = 0 V, f = 1.8 GHz$                 | $R_P$       | -<br>-<br>-      | 25<br>4<br>2.5               | -<br>-<br>-           | kΩ   |
| Forward resistance<br>$I_F = 5 mA, f = 100 MHz$<br>$I_F = 10 mA, f = 100 MHz$                                                 | $r_f$       | -<br>-           | 1.5<br>1                     | 1.8<br>-              | Ω    |
| Charge carrier life time<br>$I_F = 10 mA, I_R = 6 mA$ , measured at $I_R = 3 mA$ ,<br>$R_L = 100 \Omega$                      | $\tau_{rr}$ | -                | 700                          | -                     | ns   |
| I-region width                                                                                                                | $W_I$       | -                | 13                           | -                     | μm   |


**Diode capacitance  $C_T = f(V_R)$**

$f$  = Parameter




**Reverse parallel resistance  $R_P = f(V_R)$**

$f$  = Parameter




**Forward resistance  $r_f = f(I_F)$**




$f$  = 100MHz




**Forward current  $I_F = f(V_F)$**

$T_A$  = Parameter




**Forward current  $I_F = f(T_S)$** 
**BAR67-02V**

**Forward current  $I_F = f(T_S)$** 
**BAR67-04**

**Permissible Puls Load  $R_{thJS} = f(t_p)$** 
**BAR67-02V**

**Permissible Pulse Load**

$$I_{Fmax}/I_{FDC} = f(t_p)$$

**BAR67-02V**


# Permissible Puls Load $R_{thJS} = f(t_p)$

BAR67-04



2005, June  
*Date code*

GF

BAR63-02V  
*Type code*

Cathode marking  
*Laser marking*


The image contains three technical drawings of cathode marking components. The first drawing, labeled 'Standard', shows a component with a width of 4, a height of 8, and a pitch of 1.33. It features two circular cathode markings and two rectangular markings. The second drawing, labeled 'Reel with 2 mm Pitch', shows a component with a width of 2 and a height of 0.66. It features two circular cathode markings and two rectangular markings. The third drawing shows a side view of the component with a width of 0.2 and a height of 0.66. The drawings are labeled 'Cathode marking' and 'Standard'.

Date Code marking for discrete packages with one digit (SCD80, SC79, SC75<sup>1)</sup>) CES-Code

| Month | 2003 | 2004 | 2005 | 2006 | 2007 | 2008 | 2009 | 2010 | 2011 | 2012 | 2013 | 2014 |
|-------|------|------|------|------|------|------|------|------|------|------|------|------|
| 01    | a    | p    | A    | P    | a    | p    | A    | P    | a    | p    | A    | P    |
| 02    | b    | q    | B    | Q    | b    | q    | B    | Q    | b    | q    | B    | Q    |
| 03    | c    | r    | C    | R    | c    | r    | C    | R    | c    | r    | C    | R    |
| 04    | d    | s    | D    | S    | d    | s    | D    | S    | d    | s    | D    | S    |
| 05    | e    | t    | E    | T    | e    | t    | E    | T    | e    | t    | E    | T    |
| 06    | f    | u    | F    | U    | f    | u    | F    | U    | f    | u    | F    | U    |
| 07    | g    | v    | G    | V    | g    | v    | G    | V    | g    | v    | G    | V    |
| 08    | h    | x    | H    | X    | h    | x    | H    | X    | h    | x    | H    | X    |
| 09    | j    | y    | J    | Y    | j    | y    | J    | Y    | j    | y    | J    | Y    |
| 10    | k    | z    | K    | Z    | k    | z    | K    | Z    | k    | z    | K    | Z    |
| 11    | l    | 2    | L    | 4    | l    | 2    | L    | 4    | l    | 2    | L    | 4    |
| 12    | n    | 3    | N    | 5    | n    | 3    | N    | 5    | n    | 3    | N    | 5    |


1) New Marking Layout for SC75, implemented at October 2005.

## Package Outline




1) Lead width can be 0.6 max. in dambar area

## Foot Print




## Marking Layout (Example)



## Standard Packing

Reel ø180 mm = 3.000 Pieces/Reel  
Reel ø330 mm = 10.000 Pieces/Reel





**Edition 2009-11-16**

**Published by  
Infineon Technologies AG  
81726 Munich, Germany**

**© 2009 Infineon Technologies AG  
All Rights Reserved.**

## **Legal Disclaimer**

The information given in this document shall in no event be regarded as a guarantee of conditions or characteristics. With respect to any examples or hints given herein, any typical values stated herein and/or any information regarding the application of the device, Infineon Technologies hereby disclaims any and all warranties and liabilities of any kind, including without limitation, warranties of non-infringement of intellectual property rights of any third party.

## **Information**

For further information on technology, delivery terms and conditions and prices, please contact the nearest Infineon Technologies Office ([<www.infineon.com>](http://www.infineon.com)).

## **Warnings**

Due to technical requirements, components may contain dangerous substances. For information on the types in question, please contact the nearest Infineon Technologies Office.

Infineon Technologies components may be used in life-support devices or systems only with the express written approval of Infineon Technologies, if a failure of such components can reasonably be expected to cause the failure of that life-support device or system or to affect the safety or effectiveness of that device or system. Life support devices or systems are intended to be implanted in the human body or to support and/or maintain and sustain and/or protect human life. If they fail, it is reasonable to assume that the health of the user or other persons may be endangered.

# AMEYA360

## Components Supply Platform

Authorized Distribution Brand :



Website :

Welcome to visit [www.ameya360.com](http://www.ameya360.com)

Contact Us :

➤ Address :

401 Building No.5, JiuGe Business Center, Lane 2301, Yishan Rd  
Minhang District, Shanghai , China

➤ Sales :

Direct +86 (21) 6401-6692

Email [amall@ameya360.com](mailto:amall@ameya360.com)

QQ 800077892

Skype ameyasales1 ameyasales2

➤ Customer Service :

Email [service@ameya360.com](mailto:service@ameya360.com)

➤ Partnership :

Tel +86 (21) 64016692-8333

Email [mkt@ameya360.com](mailto:mkt@ameya360.com)