

Specification Status: Released

BENEFITS


- Silicon ESD device in an EIA-0402 size rectangular passive component SMT package
- Standard PCB assembly and rework processes
- Bi-directional operation allows placement on PCB without orientation constraint
- Appropriate for ESD protection in space-constrained portable electronics and mobile handsets
- Suitable for +5V operating voltage applications
- Helps protect electronic circuits against damage from Electrostatic Discharge (ESD) events
- Assist equipment to pass IEC61000-4-2, level 4 testing
- RoHS compliant and Halogen Free

FEATURES


- Input capacitance – 4.5pF (typ)
- Low leakage current – 1.0μA (max)
- Low working reverse voltage – 6.0V (max)
- ESD maximum rating per IEC61000-4-2 standard
 - o ± 10kV contact discharge⁽¹⁾
 - o ± 16kV air discharge
- Capable of withstanding numerous ESD strikes
- Small package size: 1.10mm x 0.50mm (typ)
- Low package height: 0.50mm (typ)

APPLICATIONS

- Cellular phones and portable electronics
- Digital cameras and camcorders
- USB 2.0 and computer I/O ports
- Notebooks, set top boxes, motherboards
- Applications requiring high ESD performance



PART NUMBERING



MATERIALS INFORMATION

RoHS Compliant ELV Compliant Halogen Free *

Directive 2000/53/EC
Compliant

Directive 2002/95/EC
Compliant

HF

* Halogen Free refers to: Br≤900ppm, Cl≤900ppm, Br+Cl≤1500ppm
Terminal finish: 100% Matte Tin (Sn)

Device Characteristics @ T = 25°C	Min	Typ	Max	Unit
Input Capacitance @ $V_r = 0V$, $f = 1MHz$	--	4.5	5.5	pF
Working Reverse Voltage (peak) - V_{RWM}	--	--	6.0	V
Breakdown Voltage - V_{br} @ $I_t = 1mA$ ⁽²⁾	9.0	11.0	--	V
Leakage current @ $V_{RWM} = 6.0V$	--	--	1.0	μA
Clamping Voltage @ $I_{pp}=2A$, $t_p=(8/20\mu s)$	--	±10.0	±12.0	V
ESD contact discharge per IEC61000-4-2 standard ⁽¹⁾	--	--	±10	kV
ESD air discharge per IEC61000-4-2 standard	--	--	±16	kV
Operating ($T_{junction}$) and Storage Temperature Range	-40 to +125			°C


⁽¹⁾ 10kV @ 50 ± pulses under IEC61000-4-2; 8kV @ 1,000 pulses under IEC61000-4-2

⁽²⁾ V_{br} is measured at test current I_t

ChipSESD
Silicon ESD Protector
Overvoltage Protection Device
Circuit Protection Products

DOCUMENT: SCD 27764
REV LETTER: A
REV DATE: OCTOBER 22, 2010
PAGE NO.: Page 2 of 5

DEVICE DIMENSIONS




Drawings Not To Scale

Typical	A	B	C	D
mm	1.10 ± 0.1	0.50 ± 0.1	0.50 ± 0.1	0.25 ± 0.15
mils*	43.31 ± 4.0	19.69 ± 4.0	19.69 ± 4.0	9.84 ± 6.0

* Round off approximation

RECOMMENDED LANDING PATTERN:



Typical	L	S	W
mm	0.61 ± 0.05	0.52 ± 0.05	0.50 ± 0.05
mils*	24.0 ± 2.0	21.0 ± 2.0	20.0 ± 2.0

* Round off approximation

- Recommended solder thickness: 150 to 200 μm
- Recommended rework procedure:
 - o Soldering iron tip temperature should be less than 350°C
 - o Apply iron tip to solder for less than 5 seconds
 - o Do not apply solder iron tip to the body of this product directly

ChipSESD

Silicon ESD Protector

Overvoltage Protection Device

Circuit Protection Products


PRODUCT: SESD0402P1BN-0450-090

DOCUMENT: SCD 27764
REV LETTER: A
REV DATE: OCTOBER 22, 2010
PAGE NO.: Page 3 of 5

PACKAGING


Packaging	Tape & Reel	Standard Box
SESD0402P1BN-0450-090	10,000	50,000

REEL DIMENSIONS



Dimension	A	B	C	D	E	F	G
(mm)	178.0 ± 2.0	2.0 ± 0.5	13.0 ± 0.5	21.0 ± 0.8	62.0 ± 1.5	9.0 ± 0.5	13.0 ± 1.0

CARRIER TAPE DIMENSIONS



Dimension	A	B	D	E	F	W
(mm)	0.58 ± 0.03	1.20 ± 0.03	1.55 ± 0.05	1.75 ± 0.05	3.5 ± 0.05	8.0 ± 0.1

Dimension	P ₀	P ₁	P ₂	T
(mm)	4.0 ± 0.1	2.0 ± 0.05	2.0 ± 0.05	0.60 ± 0.03

FIGURE 1: TYPICAL IV CURVE




FIGURE 2: ESD CLAMPING VOLTAGE – 8kV Contact





FIGURE 3: ESD CLAMPING VOLTAGE – 8x20 μ s, 2A Surge



Information furnished is believed to be accurate and reliable. However, users should independently evaluate the suitability of each product for their applications. Tyco Electronics reserves the right to change or update, without notice, any information contained in this publication; to change, without notice, the design, construction, processing, or specification of any product; and to discontinue or limit production or distribution of any product. This publication supersedes and replaces all information previously supplied. Without expressed or written consent by an officer of Tyco Electronics, Tyco Electronics does not authorize the use of any of its products as components in nuclear facility applications, aerospace, or in critical life support devices or systems. Tyco Electronics' only obligations are those in the Tyco Electronics Standard Terms and Conditions of Sale and in no case will Tyco Electronics be liable for any incidental, indirect, or consequential damages arising from the sale, resale, use, or misuse of its products.

USB is a trademark of USB.org

TE Logo and Tyco Electronics are trademarks

© 2010 Tyco Electronics Corporation. All rights reserved.

AMEYA360

Components Supply Platform

Authorized Distribution Brand :



Website :

Welcome to visit www.ameya360.com

Contact Us :

➤ Address :

401 Building No.5, JiuGe Business Center, Lane 2301, Yishan Rd
Minhang District, Shanghai , China

➤ Sales :

Direct +86 (21) 6401-6692
Email amall@ameya360.com
QQ 800077892
Skype ameyasales1 ameyasales2

➤ Customer Service :

Email service@ameya360.com

➤ Partnership :

Tel +86 (21) 64016692-8333
Email mkt@ameya360.com