

1:1 Transmission Line Transformer 46 to 1002 MHz

Rev. V3

Features

- Surface mount
- Wide Frequency Range
- 260°C reflow compatible
- RoHS* compliant and lead free
- Available on Tape and Reel

Description


M/A-Com Technology Solutions MABA-010245-CT1160 is a 1:1 transmission line transformer. The windings are welded to the package substrate for improved reliability and to eliminate lead content. This transformer is ideally suited for CATV broadband AND Satellite STB/Subscriber applications.




Pin Configuration

Pin no.	Function	
1	Secondary Dot	
2	Not Connected	
3	Secondary	
4	Primary	
5	Primary Dot	

Schematic



Component dimensions



Dimensions in inches [mm] Tolerance: .xx ± .02, .xxx ± .010, unless otherwise stated

- India Tel: +91.80.43537383
- China Tel: +86.21.2407.1588

Visit www.macomtech.com for additional data sheets and product information.

^{*} Restrictions on Hazardous Substances, European Union Directive 2002/95/EC.



1:1 Transmission Line Transformer 46 to 1002 MHz

Rev. V3


Electrical Specifications: $T_A = 25$ °C, 0dBm, $Z_0 = 75\Omega$, $P_{in} = 0$ dBm

Parameter	Frequency	Units	Min	Тур	Max
Insertion Loss 1 (Pin 4 to Pin 3)	46 - 1002MHz	dB	-	0.1	0.6
Insertion Loss 2 (Pin 4 to Pin 1)	46 - 1002MHz	dB	-	0.4	0.7
Amplitude Balance (Nominal 0dB)	46 - 1002MHz	dB	-	0.3	±0.8
Phase Balance (Nominal 180°)	46 - 100MHz 100 - 1002MHz	0	-	2.4 1.2	±5.0 ±2.5
Input Return Loss (Pin4)	46 - 300 MHz 300 - 1002 MHz	dB dB	25 17.5	42 30	-

Recommended Maximum Ratings

Parameter	Value		
Input power	+24dBm (250mW)		
DC current (tested at 5V)	At least 600mA		
Operating Temperature	-40°C to +85°C		
Storage Temperature	-40°C to +100°C		

Application Circuit



• India Tel: +91.80.43537383


• China Tel: +86.21.2407.1588





1:1 Transmission Line Transformer 46 to 1002 MHz


Rev. V3


Typical Performance Curves: $T_A = 25^{\circ}C$, 0dBm, $Z_0 = 75\Omega$, $P_{in} = 0$ dBm












- India Tel: +91.80.43537383
- China Tel: +86.21.2407.1588



1:1 Transmission Line Transformer 46 to 1002 MHz

Rev. V3

Tape & Reel Information



Item	Dimension		
Ao	4.0mm +/- 0.1mm		
Во	4.0mm +/- 0.1mm		
Ko	2.90mm +/- 0.1mm		
W	12.0mm +/- 0.3mm		
P1	8.00mm +/- 0.1mm		

Ordering Information

Part number	Description	
MABA-010245-CT1160	2000 piece reel	
MABA-010245-CT11TB	Customer Test Board	

AMEYA360 Components Supply Platform

Authorized Distribution Brand:

























Website:

Welcome to visit www.ameya360.com

Contact Us:

Address:

401 Building No.5, JiuGe Business Center, Lane 2301, Yishan Rd Minhang District, Shanghai , China

> Sales:

Direct +86 (21) 6401-6692

Email amall@ameya360.com

QQ 800077892

Skype ameyasales1 ameyasales2

Customer Service :

Email service@ameya360.com

Partnership :

Tel +86 (21) 64016692-8333

Email mkt@ameya360.com