

1				2		3		4		5		6		7		8	
Circuit diagram										Dimensions (mm)							
Allgemeine Toleranzen		General tolerances		Tolérances en général		L + 20% - 20%		C ± 20%		R ± 10%							
Daten (single phase)				data				caractéristiques									
Nennstrom bei Umgebungstemp.		rated current at an ambient temp.		courant nominal à une température ambiante				2 A		40 °C							
Nennspannung		rated voltage		tension nominal		max.		250 V, 50/60Hz									
Betriebsfrequenz		operating frequency		fréquence de service		max.		100 kHz									
Ableitstrom nominal		Nominal operational leakage		courant nominal		Tol. (%)		Spannung P-E / Frequenz									
								230 VAC 50 Hz									
Berechnung mit C-Tol.		Calculation with C-tol.		Calculatation avec C-tol.		+20		I nom. -- mA									
Maximaler Ableitstrom		Max leakage current		courant maximale de fuite		Tol. (%)		Spannung P-E / Frequenz									
Unterbruch des Nullleiters		with interruption of the neutral conductor		avec l'interruption du conducteur neutre				230 VAC 50 Hz									
Berechnung mit C-Tol.		Calculation with C-tol.		Calculatation avec C-tol.		+20		I max. -- mA									
DC-Widerstand		DC-resistance		DC-résistance		Tol. (%)		@ 25 °C max. 2 x 84 mOhm									
						+15											
Pruefspannung 100% Schlusskontr.		test voltage 100% final test		tension d'essais contrôle final 100%				P/N->E kV/ s ≥ 2s									
								P->N 1,5 kV/50Hz s ≥ 2s									
Wiederholung mit 80% der angegebenen Werte		repetition with max. 80% of the specified values		répétition avec max. 80% des valeurs spécifiques													
Zulaessige Betriebstemp.		temperature range		gamme de température				- 40 °C bis/to/à + 125 °C									
Klimatische Pruefklasse		climatic test class		classe d'essais climatique				40/125/56 (IEC/CEI 60068-1)									
I III SCHAFFNER Type RS 622-2/02								484-418 E									
Zusatzangaben										additional information		informations supplémentaires					
Vergussmasse		potting compound		matière de moulage				Polyurethane									
Gewicht		weight		poids				30 g									
Pruefzeichen		approvals		homologations													
☐ CSA / C-US		UL 1283 C 22.2 No.8		☐ CSA C 22.2 No.8		☒ UL UL 1283		☐ SEMKO		☐ EN 133200 IEC 60939		☐ VDE		☐			
Zusätzliche Angaben:																	
Additional remarks:																	
Remarques additional:																	
Fuer Masse ohne Toleranz				for dimensions without tolerance				pour mesure sans tolérance				IS02768-m/EN22768-m					
Datenblatt (single phase)				data sheet				fiche technique									
Copyright by © SCHAFFNER EMV AG				projection				scale 2:1				Type RS 622-2/02					
www.schaffner.com				date 25.11.1998				name joe				Part.-No. 290-133					
E 114966 19.08.2003 MNY				ds proved 06.11.90				STU									
ind revision date name				doc. proved x				x									
SCHAFFNER EMV AG CH-4542 LUTERBACH				I III SCHAFFNER				DB3 484-418 E									
plot date				page 1 von 1													

Authorized Distribution Brand :



Website :

Welcome to visit www.ameya360.com

Contact Us :

➤ Address :

401 Building No.5, JiuGe Business Center, Lane 2301, Yishan Rd
Minhang District, Shanghai , China

➤ Sales :

Direct +86 (21) 6401-6692
Email amall@ameya360.com
QQ 800077892
Skype ameyasales1 ameyasales2

➤ Customer Service :

Email service@ameya360.com

➤ Partnership :

Tel +86 (21) 64016692-8333
Email mkt@ameya360.com