



## Heyco® Braided Sleeving

BUNDLE RANGE				PART NO.		DESCRIPTION	PART DIMENSIONS			
Minimum Diameter		Maximum Diameter		Black	FR Black		Nominal Diameter		Quantity Per Spool	
in.	mm.	in.	mm.			in.	mm.	ft.	mtrs.	
.09	2,3	.25	6,4	<b>8980</b>	<b>8983</b>	BS 125	.13	3,2	1000	305
.13	3,2	.44	11,1	<b>8985</b>	<b>8988</b>	BS 250	.25	6,4		
.25	6,4	.75	19,1	<b>8990</b>	<b>8993</b>	BS 500	.50	12,7	500	152
.50	12,7	1.25	31,8	<b>8995</b>	<b>8998</b>	BS 750	.75	19,1		
.75	19,1	1.75	44,5	<b>9000</b>	<b>9003</b>	BS 1250	1.25	31,8	250	76
1.25	31,8	2.75	69,9	<b>9005</b>	<b>9008</b>	BS 1750	1.75	44,5	200	61
1.50	38,1	3.50	88,9	<b>9010</b>	<b>9013</b>	BS 2.0	2.00	50,8		

Standard color black.  
FR sleeving flammability rating—UL VW-1.



- Braided sleeve slips on quickly and is self-fitting over irregular shapes and contours. No wire pulling compounds are required due to its low surface friction. Slight tensioning after application makes for an even tighter fit.
- Expandable up to three times its own diameter, the open-weave construction can fit many applications, simplifying inventory. The open-weave allows for easy inspection of sleeved components and easy break out of individual cables.
- Full cable flexibility is maintained in any direction, even at low temperatures. Wires encased in Heyco Braided Sleeving can flex and bend as readily as if they had no protective oversleeving. Bundles can be flexed repeatedly without damage.
- Tough, cut-resistant sleeving is designed for protecting wire bundles and harnesses, hoses, tubing, and cable assemblies from mechanical damage and environmental hazards.
- The high tensile strength, damage-resistant filament braid:
  - 1) protects against rough surfaces, sharp edges or corners
  - 2) resists scuffing and abrasion
  - 3) cushions against vibration and impact damage
  - 4) prevents condensation while allowing complete drainage
  - 5) dissipates heat and moisture
  - 6) does not degrade in most fluid environments
- Sleeved components are more organized and attractive!
- Preferred cutting method: hot knife.

Materials Polyester Monofilament Yarns or Flame Retardant Polyester Yarn  
 Certifications Recognized under the Component Program of Underwriters' Laboratories File E173954  
 Monofilament Diameter .010"  
 Temperature Range -103°F (-75°C) to 257°F (125°C)

Quick Specs

# AMEYA360

## Components Supply Platform

Authorized Distribution Brand :



Website :

Welcome to visit [www.ameya360.com](http://www.ameya360.com)

Contact Us :

➤ Address :

401 Building No.5, JiuGe Business Center, Lane 2301, Yishan Rd  
Minhang District, Shanghai , China

➤ Sales :

Direct +86 (21) 6401-6692

Email [amall@ameya360.com](mailto:amall@ameya360.com)

QQ 800077892

Skype [ameyasales1](#) [ameyasales2](#)

➤ Customer Service :

Email [service@ameya360.com](mailto:service@ameya360.com)

➤ Partnership :

Tel +86 (21) 64016692-8333

Email [mkt@ameya360.com](mailto:mkt@ameya360.com)