



CONTENTS:

- 6255** (m-f) Right Angle
- 6256** Type N (m) to DIN (m)
- 6257** Type N (f) to DIN (m)
- 6258** DIN (f-f)
- 6259** Type N (m) to DIN (f)
- 6260** Type N (f) to DIN (f)

FEATURES:

- Kit contains the most frequently needed adapters to fit between instruments or equipment with type N and DIN connectors
- Peak power rating of 40 kW
- Foam lined zipper case keeps adapters handy for instant use
- Replacement adapters are available individually

MATERIALS:

Pomona's 7/16 DIN adapters are made in the US and feature silver plated outer shells, Teflon insulation and silver plated, Beryllium Copper female and brass male center contacts.

RATINGS:

Impedance: 50 Ohms
Frequency Range: DC - 7.5 GHz
Insertion Loss: $-.01 \text{ dB} \sqrt{\text{Frequency GHz}}$
VSWR (Max): $< 1.10:1 @ \text{DC} - 7.5 \text{ GHz}$
Third Order IM: $-\text{dBc} > -150 \text{ dBc}$

ORDERING INFORMATION: Model 6254

All dimensions are in inches. Tolerances (except noted): $.xx = \pm .02''$ (.51 mm), $.xxx = \pm .005''$ (.127 mm).
All specifications are to the latest revisions. Specifications are subject to change without notice.
Registered trademarks are the property of their respective companies. Made in USA

Sales: 800-490-2361 Fax: 888-403-3360
Technical Assistance: 800-241-2060

PomonaACCESS 90512 (800) 444-6785 or (425) 446-6010
More drawings available at www.pomonaelectronics.com

AMEYA360

Components Supply Platform

Authorized Distribution Brand :



Website :

Welcome to visit www.ameya360.com

Contact Us :

➤ Address :

401 Building No.5, JiuGe Business Center, Lane 2301, Yishan Rd
Minhang District, Shanghai , China

➤ Sales :

Direct +86 (21) 6401-6692

Email amall@ameya360.com

QQ 800077892

Skype [ameyasales1](#) [ameyasales2](#)

➤ Customer Service :

Email service@ameya360.com

➤ Partnership :

Tel +86 (21) 64016692-8333

Email mkt@ameya360.com