



# HiPerDyn™ Schottky Diode (Electrically Isolated Back Surface)

$I_{FAV} = 17\text{ A}$   
 $V_{RRM} = 600\text{ V}$   
 $t_{rr} = 45\text{ ns}$

$V_{RSM}$	$V_{RRM}$	Type
V	V	
600	600	DSS 17-06CR



A = Anode, C = Cathode

\* Patent pending

Symbol	Conditions	Maximum Ratings	
$I_{FRMS}$		50	A
$I_{FAVM}$	$T_C = 95^\circ\text{C}$ ; rectangular, $d = 0.5$	17	A
$I_{FRM}$	$t_p < 10\ \mu\text{s}$ ; rep. rating, pulse width limited by $T_{VJM}$	tbd	A
$I_{FSM}$	$T_{VJ} = 45^\circ\text{C}$ ; $t_p = 10\text{ ms}$ (50 Hz), sine	200	A
$E_{AS}$	$I_{AS} = 2\text{ A}$ ; $L = 100\ \mu\text{H}$ ; $T_{VJ} = 25^\circ\text{C}$ ; non-repetitive	0.2	mJ
$I_{AR}$	$V_A = 1.5 \cdot V_R$ typ.; $f = 10\text{ kHz}$ ; repetitive	0.2	A
$T_{VJ}$		-55...+175	$^\circ\text{C}$
$T_{VJM}$		175	$^\circ\text{C}$
$T_{stg}$		-55...+150	$^\circ\text{C}$
$P_{tot}$	$T_C = 25^\circ\text{C}$	105	W
$V_{ISOL}$	50/60 Hz RMS; $I_{ISOL} \leq 1\text{ mA}$	2500	V~
$F_C$	mounting force with clip	20...120	N
Weight	typical	6	g

## Features

- Silicon chip on Direct-Copper-Bond substrate
- High power dissipation
- Isolated mounting surface
- 2500V electrical isolation
- Low cathode to tab capacitance (<25pF)
- International standard package
- Planar passivated chips
- Very short recovery time
- Extremely low switching losses
- Low  $I_{RM}$ -values
- Soft recovery behaviour
- Epoxy meets UL 94V-0
- Isolated and UL registered E153432

## Applications

- Antiparallel diode for high frequency switching devices
- Antisaturation diode
- Snubber diode
- Free wheeling diode in converters and motor control circuits
- Rectifiers in switch mode power supplies (SMPS)
- Inductive heating
- Uninterruptible power supplies (UPS)
- Ultrasonic cleaners and welders

## Advantages

- Avalanche voltage rated for reliable operation
- Soft reverse recovery for low EMI/RFI
- Low  $I_{RM}$  reduces:
  - Power dissipation within the diode
  - Turn-on loss in the commutating switch

Dimensions see Outlines.pdf

Symbol	Conditions	Characteristic Values	
		typ.	max.
$I_R$ ①	$T_{VJ} = 25^\circ\text{C}$ $V_R = V_{RRM}$ $T_{VJ} = 125^\circ\text{C}$ $V_R = V_{RRM}$		0.5 mA 5 mA
$V_F$ ②	$I_F = 15\text{ A}$ ; $T_{VJ} = 125^\circ\text{C}$ $T_{VJ} = 25^\circ\text{C}$		2.71 V 3.32 V
$R_{thJC}$			1.4 K/W
$R_{thCH}$		0.25	K/W
$t_{rr}$	$I_F = 10\text{ A}$ ; $-di/dt = 100\text{ A}/\mu\text{s}$ ; $V_R = 100\text{ V}$ ; $T_{VJ} = 25^\circ\text{C}$	45	ns
$I_{RM}$	$V_R = 100\text{ V}$ ; $I_F = 10\text{ A}$ ; $-di_F/dt = 100\text{ A}/\mu\text{s}$ $T_{VJ} = 25^\circ\text{C}$	4.0	A

Pulse test: ① Pulse Width = 5 ms, Duty Cycle < 2.0 %  
② Pulse Width = 300  $\mu\text{s}$ , Duty Cycle < 2.0 %

Data according to IEC 60747 and per diode unless otherwise specified.

IXYS reserves the right to change limits, test conditions and dimensions.

© 2004 IXYS All rights reserved




Fig. 1 Maximum forward voltage drop characteristics




Fig. 2 Typ. value of reverse current  $I_R$  versus reverse voltage  $V_R$




Fig. 3 Typ. junction capacitance  $C_T$  versus reverse voltage  $V_R$




Fig. 4 Average forward current  $I_{F(AV)}$  versus case temperature  $T_C$




Fig. 5 Forward power loss characteristics




Fig. 6 Transient thermal impedance junction to case at various duty cycles

Note: All curves are per diode

IXYS reserves the right to change limits, test conditions and dimensions.

© 2004 IXYS All rights reserved

# AMEYA360

## Components Supply Platform

### Authorized Distribution Brand :



### Website :

Welcome to visit [www.ameya360.com](http://www.ameya360.com)

### Contact Us :

#### ➤ Address :

401 Building No.5, JiuGe Business Center, Lane 2301, Yishan Rd  
Minhang District, Shanghai , China

#### ➤ Sales :

Direct +86 (21) 6401-6692

Email [amall@ameya360.com](mailto:amall@ameya360.com)

QQ 800077892

Skype [ameyasales1](#) [ameyasales2](#)

#### ➤ Customer Service :

Email [service@ameya360.com](mailto:service@ameya360.com)

#### ➤ Partnership :

Tel +86 (21) 64016692-8333

Email [mkt@ameya360.com](mailto:mkt@ameya360.com)