


**HDC insert
HDC S8/0 MAS**

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 16
D-32758 Detmold
Germany
Fon: +49 5231 14-0
Fax: +49 5231 14-292083
www.weidmueller.com



The MixMate series of connectors can simultaneously transmit high rated currents and voltages as well as signals. An axial screw can be used to secure the wire.
Axial screw connection TOP connection

General ordering data

Order No.	1023360000
Type	HDC S8/0 MAS
Version	HDC insert, Male, 690 V, 110 A, No. of poles: 8, Axial screw connection, Size: 8
GTIN (EAN)	4032248739509
Qty.	1 pc(s).

HDC insert HDC S8/0 MAS

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 16

D-32758 Detmold

Germany

Fon: +49 5231 14-0

Fax: +49 5231 14-292083

www.weidmueller.com

Technical data

Dimensions and weights

Length	111 mm	Width	34 mm
Height	48.5 mm	Net weight	300 g

Dimensions

Height of plug	48.5 mm	Total length base	111 mm
----------------	---------	-------------------	--------

General data

Size	8	Series	MixMate
Rated voltage (DIN EN 61984)	690 V	Rated voltage according to UL/CSA	600 V AC/DC
Rated impulse voltage (DIN EN 61984)	8 kV	Rated current (DIN EN 61984)	110 A
UL 94 flammability rating	V-0	Insulating material group	IIIa
Insulation resistance	10 ¹⁰ Ω	Insulating material	PC glass-fibre reinforced (UL-listed and railway-certified)
Conductor cross-section	25 mm ²	No. of poles	8
Plugging cycles, silver	≥ 500	Pollution severity	3
Type	Male		

Connection data PE

Stripping length PE connection	12 mm	Wire connection cross-section, finely stranded, min.	10 mm ²
Wire connection cross section, finely stranded, max.	25 mm ²	Wire connection cross section AWG, min.	AWG 8
Wire connection cross section AWG, max.	AWG 4	Connection type PE	Screw connection, Miscellaneous
Tightening torque, min. PE connection	6 Nm	Tightening torque, max. PE connection	7 Nm
Rated cross-section	25 mm ²		

Rating data

Rated current (DIN EN 61984)	110 A	Rated impulse voltage (DIN EN 61984)	8 kV
Rated voltage (DIN EN 61984)	690 V	Rated voltage according to UL/CSA	600 V AC/DC

Version

Wire connection cross section AWG, min.	AWG 8	Wire connection cross section AWG, max.	AWG 4
Stripping length, rated connection	12 mm	Type of connection	Axial screw connection
Min. torque for main contact	6 Nm	Max. torque for main contact	7 Nm
Size	8	Volume resistance	≤ 1 mΩ
Clamping screw	M 8 x 0.75 mm	Surface finish	Silver passivated
Material	Copper alloy		

Classifications

ETIM 3.0	EC002413	UNSPSC	30-21-18-01
eClass 6.2	27-26-12-90	eClass 7.1	27-44-02-90

Product information

Descriptive text technical data	Rated voltage 1000 V / 8 kV at pollution degree 2
Descriptive text accessories	Accessories, see chapter J - Tools, see chapter K

**HDC insert
HDC S8/0 MAS**

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 16
D-32758 Detmold
Germany
Fon: +49 5231 14-0
Fax: +49 5231 14-292083
www.weidmueller.com

Technical data

Approvals

Approvals



ROHS

Conform

AMEYA360

Components Supply Platform

Authorized Distribution Brand :



Website :

Welcome to visit www.ameya360.com

Contact Us :

➤ Address :

401 Building No.5, JiuGe Business Center, Lane 2301, Yishan Rd
Minhang District, Shanghai , China

➤ Sales :

Direct +86 (21) 6401-6692

Email amall@ameya360.com

QQ 800077892

Skype ameyasales1 ameyasales2

➤ Customer Service :

Email service@ameya360.com

➤ Partnership :

Tel +86 (21) 64016692-8333

Email mkt@ameya360.com