



## SSRM series

### 45-65A DIN Mount Solid State Relay With Paired SCR Output, Integral Heatsink

UL File E29244

Users should thoroughly review the technical data before selecting a product part number. It is recommended that users also seek out the pertinent approvals files of the agencies/laboratories and review them to confirm the product meets the requirements for a given application.

#### Features

- DIN mount design with integral heatsink.
- Choice of 45, 55 or 65A rms inverse-parallel connected SCR output.
- 48 - 660VAC output.
- 4 -32VDC or 90 - 140Vrms input control.
- 4,000V rms optical isolation.
- Green LED input status indicator.
- Finger-safe (IP20) screw clamp terminals for load and control.
- Ground terminal.

#### Engineering Data

**Form:** 1 Form A (SPST-NO).

**Duty:** Continuous.

**Isolation:** 4,000V rms input-to-output-to-ground.

**Insulation Resistance:** 10<sup>9</sup> Ohms, minimum, at 500VDC.

**Capacitance:** 8.0 pf maximum (input to output).

**Temperature Range:**

**Storage:** -40°C to +125°C

**Operating:** -40°C to + 80°C

**Case and Mounting:** Refer to outline dimension drawing.

**Termination:**

**Control:** Finger safe (IP20) screw clamps accepting wire size up to #12 AWG (2.5 mm).

**Load:** Finger safe (IP20) screw clamps accepting wire size up to #8 AWG (3.8 mm).

**Ground:** #10 screw with 5/16 in. hex/slotted head.

**Installation Spacing:** Minimum 0.8 in (20 mm) space between units.

**Approximate Weight:** 16.9 oz. (479 g).

#### Ordering Information

Sample Part Number ▶

**SSRM -600 A 55**

**1. Basic Series:** SSRM = Solid State Relay with Integral Heatsink for DIN Rail Mounting

**2. Line Voltage:** 600 = 48 - 660 VAC

**3. Input Type & Voltage:** A = 90 - 140VAC  
D = 4 - 32VDC

**4. Maximum Switching Rating/Output:** 45 = 45.0A rms  
55 = 55.0A rms  
65 = 65.0A rms

**Our authorized distributors are more likely to maintain the following items in stock for immediate delivery.**

SSRM-600A45  
SSRM-600D45

SSRM-600A55  
SSRM-600D55

SSRM-600A65  
SSRM-600D65

#### Input Specifications


Parameter	Conditions	AC Control Units	DC Control Units
Control Voltage Range $V_{IN}$	@ 25°C	90 - 140 Vrms	4.0 - 32 VDC
Reverse Voltage $V_{IN}(\text{Max.})$	@ 25°C	—	32 VDC
Must Operate Voltage $V_{IN(OPS)}(\text{Min.})$	@ 25°C	90 Vrms	4.0 VDC
Must Release Voltage $V_{IN(REL)}(\text{Min.})$	@ 25°C	10 Vrms	1.0 VDC
Input Current (Typ.)	@ 25°C	15 mA @ 120 Vrms	14 mA @ 5 VDC
Input Current (Max.)	@ 25°C	—	30 mA

## Output Specifications (@ 25° C, unless otherwise specified)


Parameter	Conditions	Units	45A Rated Units	55A Rated Units	65A Rated Units
Load Voltage Range $V_L$	$f = 47 - 63 \text{ Hz.}$	V rms	48 - 660	48 - 660	48 - 660
Repetitive Blocking Voltage (Min.)		V peak	$\pm 1200$	$\pm 1200$	$\pm 1200$
Load Current Range $I_L^*$		A rms	0.15 - 45.0	0.25 - 55.0	0.25 - 65.0
Single Cycle Surge Current (Min.)		A peak	625	1,000	1,200
Leakage Current (Off-State) (Max.)	$f = 60 \text{ Hz. } V_L = 600\text{Vrms}$	mA rms	1.0	1.0	1.0
Thermal Resistance Junction to Case $R_{\theta J-C}$ (Max.)		°C/W	0.63	0.31	0.28
On-State Voltage Drop (Max.)	$I_L = \text{Max.}$	V peak	1.7	1.7	1.7
Static dv/dt (Off-State) (Min.)	$V_L = \text{Max.}$	V/ $\mu\text{s}$	500	500	500
Turn-On Time (Max.)	$f = 60 \text{ Hz.}$	ms	8.3 for DC Input Models, 10.0 for AC Input Models		
Turn-Off Time (Max.)	$f = 60 \text{ Hz.}$	ms	8.3 for DC Input Models, 40.0 for AC Input Models		
$I^2 t$ Rating (Max.)	$t = 8.3 \text{ ms}$	A <sup>2</sup> Sec.	1,620	4,150	6,000
Load Power Factor Rating (Min.)	$I_L = \text{Max.}$		0.5	0.5	0.5

\*See Thermal Derating Curves.

## Electrical Characteristics (Thermal Derating Curves)



## Outline Dimensions



Recommended Torque Range for Terminal Screws:  
Control: 5 - 6 in lb (0.6 - 0.7 Nm).  
Output: 10 - 15 in lb (1.1 - 1.7 Nm).

## Disclaimer

While Tyco Electronics has made every reasonable effort to ensure the accuracy of the information in this document, Tyco Electronics does not guarantee that it is error-free, nor does Tyco Electronics make any other representation, warranty or guarantee that the information is accurate, correct, reliable or current.

Tyco Electronics reserves the right to make any adjustments to the information contained herein at any time without notice. Tyco Electronics expressly disclaims all implied warranties regarding the information contained herein, including, but not limited to, any implied warranties of merchantability or fitness for a particular purpose.

The dimensions in this catalog are for reference purposes only and are subject to change without notice. Specifications are subject to change without notice. Consult Tyco Electronics for the latest dimensions and design specifications.

# AMEYA360

Components Supply Platform

Authorized Distribution Brand :



Website :

Welcome to visit [www.ameya360.com](http://www.ameya360.com)

Contact Us :

➤ Address :

401 Building No.5, JiuGe Business Center, Lane 2301, Yishan Rd  
Minhang District, Shanghai , China

➤ Sales :

Direct     +86 (21) 6401-6692  
Email       amall@ameya360.com  
QQ          800077892  
Skype       ameyasales1 ameyasales2

➤ Customer Service :

Email       service@ameya360.com

➤ Partnership :

Tel          +86 (21) 64016692-8333  
Email       mkt@ameya360.com