

CONFIGURATION		PART NUMBER
Female Receptacle, 23 Pin, 16 Awg, Shell 18		RT001823SNH
DIMENSIONS		
<p>The technical drawing includes three views: a cross-section on the left, a front view on the top right, and a panel cut out reference on the bottom. The cross-section shows the O-Ring, Insert, Shell, and Seal Gasket. Dimensions include a shell diameter of 26.90, an insert diameter of 28.55, a shell length of 25.0, and a thread of UNEF 1"1/16-18. The front view shows a square footprint with dimensions 33.3 by 33.3, a central circular area of 26.95 by 26.95, and four mounting holes of diameter 3.20. The panel cut out reference shows a circular hole with a diameter of 27.80 for front panel mounting and 31.35 for rear panel mounting, with a 26.95 diameter for the main body.</p>		
TECHNICAL DATA		
TEMPERATURE RANGE:	-40°C to + 105°C	
PROTECTION:	IP67 in mated condition and in combination with sealed backshell	
VOLTAGE RATING:	250V	
HOUSING BODY:	Zinc Alloy, Nickel Plated	
COUPLING NUT:	-	
INSERT:	Glass-filled Thermoplastic UL94-V0	
SEAL:	NBR	
CURRENT:	13A	
CONTACT SIZE:	16Awg	
APPROVALS:	UL ECBT2	

AMEYA360

Components Supply Platform

Authorized Distribution Brand :



Website :

Welcome to visit www.ameya360.com

Contact Us :

➤ Address :

401 Building No.5, JiuGe Business Center, Lane 2301, Yishan Rd
Minhang District, Shanghai , China

➤ Sales :

Direct +86 (21) 6401-6692

Email amall@ameya360.com

QQ 800077892

Skype [ameyasales1](#) [ameyasales2](#)

➤ Customer Service :

Email service@ameya360.com

➤ Partnership :

Tel +86 (21) 64016692-8333

Email mkt@ameya360.com