



ISO9001:2008 Certified

Mechanical Specifications (mm)

D:	37.0	± max
T:	6.5	± max
Lead Diameter	9.5	± nom
S:	19.0	± nom
L:	40.0	± nom
Coating Lead Run Down (straight Leads)	7.0	± max
B:		±
C:	7.50	± nom



Electrical Specifications

Resistance:	2.0	Ω	± 25 %
Max Steady State Current upto 65°C:	35.00	A	
Max Rec. Energy Rating:	750	J	
Actual Failure Instantaneous Energy:		J	
Maximum Capacitance @ 120 VAC:	51,900	μf	
Maximum Capacitance @ 240 VAC:	13,024	μf	
Maximum Capacitance @ 440 VAC:	3,010	μf	
Maximum Capacitance @ 680 VAC:	1,500	μf	
Resistance @ 100% Max Current:	0.02	Ω	
Resistance @ 50% Max Current:	0.04	Ω	
Body Temperature at 100% Max Current:	235.00	°c	
Dissipation Constant:	96.0	mw/°c	
Thermal Time Constant:	65	Sec.	
Material Type (for Beta and Curve):	C		

MS35 2R035

Date: 02/05/2009	Drawn by: Erin Landis
Ametherm, Inc. 3111 N. Deer Run Road Carson City, Nevada USA 89701 www.ametherm.com	Approved By: Mehdi Samii
	Revision: A

AMEYA360

Components Supply Platform

Authorized Distribution Brand :



Website :

Welcome to visit www.ameya360.com

Contact Us :

➤ Address :

401 Building No.5, JiuGe Business Center, Lane 2301, Yishan Rd
Minhang District, Shanghai , China

➤ Sales :

Direct +86 (21) 6401-6692

Email amall@ameya360.com

QQ 800077892

Skype ameyasales1 ameyasales2

➤ Customer Service :

Email service@ameya360.com

➤ Partnership :

Tel +86 (21) 64016692-8333

Email mkt@ameya360.com