

SPECIFICATIONS

Model 1501

DESCRIPTION: 1.5V/3VDC, 3A Power Supply

INPUT VOLTAGE: 115VAC, 60Hz

ENVIRONMENTAL TEMPERATURE: 25°C

OUTPUT VOLTAGE NO LOAD:	Min.	Max.
1.5V Output Voltage	1.8V	3V
3V Output Voltage	3.5V	4.5V

OUTPOUT CURRENT: 3Amps, typical

OUTPUT VOLTAGE FULL LOAD:	Min.
1.5V Output Voltage	0.8V
3V Output Voltage	1.8V

No Load Input Current: 75mA, Max.

Full Load Input Current (3V, 3A): 180mA, Max

Fuse: 0.5A

Dimensions (W X D X H): 141 mm x 80 mm x 68 mm

Weight: 0.85 kgs

Description:

The 1501 is a dual voltage, high current battery eliminator. It has a unique design that allows for stable voltage and protection for your device built into the internal supplies of this unit. The output is separate and isolated from the power line, but they share a common ground.

Operations:

Plug model 1501 into AC outlet (unit is on as soon as it is plugged in). Select between 1.5V and 3V.

AMEYA360

Components Supply Platform

Authorized Distribution Brand :



Website :

Welcome to visit www.ameya360.com

Contact Us :

➤ Address :

401 Building No.5, JiuGe Business Center, Lane 2301, Yishan Rd
Minhang District, Shanghai , China

➤ Sales :

Direct +86 (21) 6401-6692

Email amall@ameya360.com

QQ 800077892

Skype ameyasales1 ameyasales2

➤ Customer Service :

Email service@ameya360.com

➤ Partnership :

Tel +86 (21) 64016692-8333

Email mkt@ameya360.com