




CUSTOMER TERMINAL	RoHS	LEAD(Pb)-FREE
Sn96%, Ag4%	Yes	Yes

more than you expect



PART MUST INSERT FULLY TO
SURFACE A IN RECOMMENDED GRID
.025 SQ.(4)
[.64]



RECOMMENDED
P.C. PATTERN, COMPONENT SIDE

ELECTRICAL SPECIFICATIONS @ 25°C unless otherwise noted:

PARAMETER	TEST CONDITIONS	VALUE
D.C. RESISTANCE	1-2 @20°C	3.03 ohms ±10%
D.C. RESISTANCE	4-3 @20°C	3.03 ohms ±10%
INDUCTANCE	1-2 10kHz, 50mVAC, Ls	70.0 +60%/-30% mH
INDUCTANCE	4-3 10kHz, 50mVAC, Ls	70.0 +60%/-30% mH
SATURATION CURRENT	1-4 tie(2+3), roll off 20% from initial	1.0A
LEAKAGE INDUCTANCE	1-4 tie(2+3), 10kHz, 50mVAC, Ls	2.0mH min.
DIELECTRIC	1-4 1875VAC, 1 second	1500VAC, 1 minute
DIELECTRIC	1-CORE tie(1+4), 1875VAC, 1 second	1500VAC, 1 minute
URNS RATIO	(1-2):(4-3)	1:1, ±2%

GENERAL SPECIFICATIONS:

OPERATING TEMPERATURE RANGE: -40°C to +125°C including temp rise.

Designed to meet UL Recognized Insulation System M7-130(B), E106391.

Wire insulation & RoHS status not affected by wire color.
Wire insulation color may vary depending on availability.

REV.	DATE	Packaging Specifications	Tolerances unless otherwise specified:	DRAWING TITLE	PART NO.
		Method: Tray	Angles: ±1°	CMC	750341781
		PKG-0822	Decimals: ±.005 [.13]		
		www.we-online.com/midcom	Fractions: ±1/64		
6B	12/14	SEE REVISION SHEET FOR	Footprint: ±.001 [.03]	eiSos p/n: 750341781	
6A	5/13	REVISION LEVEL	This drawing is dual dimensioned. Dimensions in brackets are in millimeters.		



SPECIFICATION SHEET 1 OF 2

AMEYA360

Components Supply Platform

Authorized Distribution Brand :



Website :

Welcome to visit www.ameya360.com

Contact Us :

➤ Address :

401 Building No.5, JiuGe Business Center, Lane 2301, Yishan Rd
Minhang District, Shanghai , China

➤ Sales :

Direct +86 (21) 6401-6692

Email amall@ameya360.com

QQ 800077892

Skype ameyasales1 ameyasales2

➤ Customer Service :

Email service@ameya360.com

➤ Partnership :

Tel +86 (21) 64016692-8333

Email mkt@ameya360.com