



MMCX and Reverse Polarity MMCX Specifications

Materials		
Connector Part	Material	Finish
Bodies	Brass	Nickel or Gold
Center contact	Male: Brass	Gold
	Female: Beryllium Copper	
Insulator	PTFE	N/A
Crimp ferrule	Annealed Copper	Nickel or Gold

Electrical	
Electrical Data	Detail
Impedance	50 ohm
Frequency range	0~6GHz
Working voltage	170 volts rms max. at sea level
Insulation resistance	1,000 megaohms min.
Dielectric withstanding voltage	500 volts rms min. at sea level
Contact resistance	Center contact: 5.0 milliohms max.
	Outer contact: 2.5 milliohms max.
VSWR: f(GHz)	Straight: 1.3 max.
	Right angle: 1.5 max.
Insertion loss	0.2dB max. at 1GHz (straight)
	0.3dB max. at 1GHz (right angle)

Mechanical	
Mechanical Data	Detail
Engagement force	3.4lbs max.
Disengagement force	1.4lbs ~ 3.4lbs
Connector durability	500 cycles min.
Cable retention force	RG174, 188, 316/U » 20lbs min.
	RG178/U » 6lbs min.

Environmental	
Environmental Data	Detail
Corrosion (salt spray)	MIL-STD-202 METHOD 101 TEST CONDITION B
Thermal shock	MIL-STD-202 METHOD 107 TEST CONDITION F
Vibration	MIL-STD-202 METHOD 204 TEST CONDITION C
Temperature Range	-65°C to 165°C

AMEYA360

Components Supply Platform

Authorized Distribution Brand :



Website :

Welcome to visit www.ameya360.com

Contact Us :

➤ Address :

401 Building No.5, JiuGe Business Center, Lane 2301, Yishan Rd
Minhang District, Shanghai , China

➤ Sales :

Direct +86 (21) 6401-6692

Email amall@ameya360.com

QQ 800077892

Skype ameyasales1 ameyasales2

➤ Customer Service :

Email service@ameya360.com

➤ Partnership :

Tel +86 (21) 64016692-8333

Email mkt@ameya360.com