


Electrical / Environmental

HM55

Shielded Drum Compact Package Low Cost Inductors

- Operating Temperature Range -40°C to +155°C
- Ambient Temperature, Maximum 100°C
- Temperature Rise, Maximum 50°C
- Insulation System Class F, 155°C
- Operating Frequency Up to 400kHz



Specifications

Part Number	Inductance			I _{rated} ⁽¹⁾ (Adc)	I _{sat} ⁽²⁾ (Adc)	DCR ⁽³⁾ mΩ ± 5%	Dim D. (mm ± 0.5)	Dim. E (mm ± 0.1)	Fig.
	100 kHz @ 0 Adc μH ± 10%	100 kHz, 0.1 V @ I _{rated} μH Min.	μH Typ.						
HM55-12R40LF	0.40	0.32	0.35	20	29	1.00	8.76	1.30	2
HM55-14R40LF	0.40	0.32	0.35	15	38	1.75	8.40	1.00	2
HM55-21R43LF	0.43	0.36	0.40	18	27	0.77	4.10	1.30	1
HM55-21R95LF	0.95	0.76	0.84	22.5	33	1.28	6.90	1.30	1
HM55-211R3LF	1.38	1.10	1.25	15	22	2.26	6.60	1.05	1
HM55-22R79LF	0.79	0.56	0.63	27	39	1.20	12.5	1.45	2
HM55-24R28LF	0.28	0.21	0.25	30	85	0.72	12.7	1.30	2
HM55-26R50LF	0.50	0.36	0.40	40	50	0.90	12.7	1.50	2
HM55-311R4LF	1.40	1.08	1.20	35	50	0.98	6.60	1.65	1
HM55-313R0LF	3.00	2.43	2.70	21	30	2.60	9.45	1.30	1
HM55-315R6LF	5.60	4.86	5.40	9	14	7.30	7.11	0.91	1
HM55-321R0LF	1.0	0.72	0.80	40	56	1.25	15.24	1.50	2

- Notes: (1) Rated current, I_{rated}, is the approximate DC current at which inductance will be decreased by 20% from its initial (zero DC) value or the current at which ΔT = 50°C, whichever is lower.
(2) I_{sat} is the saturation current at which inductance rolls off approximately 30% from its initial value.
(3) DC resistance is measured at 25°C.

Outline Dimensions (Inch/mm)

Figure 1





Figure 2



- Notes: (A) Refer to Specifications table for 'D' & 'E' dimensions of each model.
(B) For case size 12 & 14, only BI logo & datecode will be printed.

Case Size	Fig.	A	B	C
12	2	.295	.295	.433
		7.50	7.50	11.0
14	2	.295	.295	.295
		7.50	7.50	7.50
21	1	.413	.433	.413
		10.5	11.0	10.5
22	2	.413	.413	.413
		10.5	10.5	10.5
24	2	.413	.413	.295
		10.5	10.5	7.50
26	2	.413	.413	.355
		10.5	10.5	9.00
31	1	.532	.543	.532
		13.5	13.8	13.5
32	2	.532	.532	.492
		13.5	13.5	12.5



Packaging

Standard: Vacuum Tray

Case Size	Capacity Per Tray (Units)	Capacity Per Carton (Units)
12, 14, 21	40	560
22	44	660
24	50	600
26	45	630
31, 32	44	572



Electrical Characteristics @ 25°C

(A) Case size 12, 14, 21, 22 & 24



Electrical Characteristics @ 25°C (Cont'd)

(B) Case size 26, 31 & 32



Ordering Information

Model Series	HM55 - 21	1R3	LF	Lead-Free
Case Size:	12 = Figure 2 14 = Figure 2 21 = Figure 1 22 = Figure 2	24 = Figure 2 26 = Figure 2 31 = Figure 1 32 = Figure 2	Inductance Code: First 2 digits are significant. Last digit denotes the number of trailing zeros. For values below 10μH, "R" denotes the decimal point.	

AMEYA360

Components Supply Platform

Authorized Distribution Brand :



Website :

Welcome to visit www.ameya360.com

Contact Us :

➤ Address :

401 Building No.5, JiuGe Business Center, Lane 2301, Yishan Rd
Minhang District, Shanghai , China

➤ Sales :

Direct +86 (21) 6401-6692
Email amall@ameya360.com
QQ 800077892
Skype ameyasales1 ameyasales2

➤ Customer Service :

Email service@ameya360.com

➤ Partnership :

Tel +86 (21) 64016692-8333
Email mkt@ameya360.com