



## 80W Constant Voltage LED Driver PDA080 Series for Outdoor Lighting



### Features

- High Efficiency
- Class 2 per UL1310
- 5 Year Warranty
- OVP, Short and Open Circuit Protection
- IP67 - waterproof, Potted
- Wide Operating Temperature Range
- Brownout/Brownout Recovery
- 120V-277V AC Operation

### Applications

- General Lighting
- Street Lighting
- Outdoor Lighting
- Architectural Lighting

### Safety Approvals

- CE
- cUL/UL

### Mechanical Characteristics

- Length: 241mm (9.5in)
- Width: 43mm (1.7in)
- Height: 30.5mm (1.2in)
- Weight: 750g (1.65lbs)

### Output Specifications

Model <sup>(1)</sup>	Output Voltage	Output Current			Output Power <sup>(2)</sup>
		Min.	Typ.	Max.	
PDA080X-48VG	48V	0A	1.67A	1.70A	80W

Note (1): X is B for non-dimming or W for 0-10V Dimming

Note (2): Output power derated to 72W when input voltage is <100VAC

PhiHong is not responsible for any error, and reserves the right to make changes without notice. Please visit our website at [www.phihong.com](http://www.phihong.com) for the most up-to-date specifications and contact information.

**Input:****AC Input Voltage Rating**

90VAC to 304VAC

**AC Input Frequency**

47~63Hz

**Maximum Input Current** $\leq 2A$ **Leakage Current**

0.5mA maximum at 230VAC Input

**Inrush Current** $\leq 20A$ **OUTPUT:****Power Factor** $\geq 0.9$  at nominal**Ripple and Noise** $<7\%$  (p-p)**Efficiency (Target)**

87% at 277VAC

85% at 120VAC

**Turn-on Delay Time**

0.5s maximum at nominal AC Power ON

**Environmental:****Temperature**

Operation -40 to +60°C

Non-operation -40 to +85°C

Operating Humidity 10 to 95%

**Case Temperature**

80°C maximum

**Warranty**

5 Years

**Dimming Function: (W Models)****Dimming Control**

0-10VDC

**Dimming Output to Load**

PWM at 500Hz

**Dimming Grounding**

Dim(-) and Vout(-) must never be connected together to ensure proper operation and isolation requirements

**EMC**

EN55015/CISPR 15, FCC 47 CFR Part 15/18, Class A

**Immunity**

IEC61000-4-2

IEC61000-4-3

IEC61000-4-4

IEC61000-4-5\*

IEC61000-4-6

IEC61000-4-8

IEC61000-4-11

IEC61000-3-2 Class C

\*Surge Differential mode: 2.0kV, Common mode: 4.0kV

**Ring Wave Surge (ANSI C62.41.2 Cat A)**

Differential mode: 4.0kV

Common mode: 6.0kV

**Input Over Current Protection**

The input power line will be fused with a 3.15A fuse

**Short-Circuit Protection**

The PSU will withstand a short circuit across the outputs without damage

**Open Circuit Protection**


Once the circuit is opened, the output voltage should be less than 120% at nominal AC input conditions

**Dielectric Withstand (Hi-pot) Test**

Primary to secondary: 4242VDC for 1 minute, 5mA

**Insulation Resistance**Primary to secondary:  $>5M\ \Omega$  500VDC, 1 Minute**Design Life**50K hours at full power, ambient 50°C and  $T_{case} < \text{rating}$ **Wire Connections**

Position	Terminal Color	Specification
Line	Black	AWG18 solid wire
Neutral	White	AWG18 solid wire
Ground	Green/Yellow	AWG18 solid wire
Vout+	Red	AWG18 solid wire
Vout-	Blue	AWG18 solid wire
Dim+	Violet	AWG18 Solid wire
Dim-	Grey	AWG18 Solid Wire



# AMEYA360

Components Supply Platform

Authorized Distribution Brand :



Website :

Welcome to visit [www.ameya360.com](http://www.ameya360.com)

Contact Us :

➤ Address :

401 Building No.5, JiuGe Business Center, Lane 2301, Yishan Rd  
Minhang District, Shanghai , China

➤ Sales :

Direct     +86 (21) 6401-6692  
Email      amall@ameya360.com  
QQ         800077892  
Skype      ameyasales1 ameyasales2

➤ Customer Service :

Email      service@ameya360.com

➤ Partnership :

Tel         +86 (21) 64016692-8333  
Email      mkt@ameya360.com