

Customer Information Sheet

DRAWING No.: M20-615XX05

SHEET 2 OF 2



IF IN DOUBT - ASK

©


NOT TO SCALE

THIRD ANGLE PROJECTION

ALL DIMENSIONS IN mm




CONNECTOR DETAIL




SPECIFICATIONS:
MATERIAL:
MOULDING = PPS UL94V-0 BLACK
CONTACTS = PHOSPHOR BRONZE
FINISH:
CONTACTS = 0.25µ GOLD OVER NICKEL
ELECTRICAL:
CURRENT RATING = 1A MAX
CONTACT RESISTANCE = 30mΩ MAX
INSULATION RESISTANCE = 5,000 MΩ MIN
DIELECTRIC STRENGTH = 1000V AC FOR ONE MINUTE
MECHANICAL:
DURABILITY = 10 OPERATIONS
INSERTION FORCE (CONTACT) = 2N/PIN MAX
WITHDRAWAL FORCE (CONTACT) = 0.25N/PIN MIN
INSERTION FORCE (BOARD) = 80N/PIN MAX
WITHDRAWAL FORCE (BOARD) = 20N/PIN MIN
ENVIRONMENTAL:
TEMPERATURE RANGE = -55°C TO +105°C
PACKING:
TUBE FOR CONNECTOR & PLASTIC BAG FOR SPACER
FOR COMPLETE SPECIFICATION, SEE COMPONENT SPECIFICATION C039XX (LATEST ISSUE)


NOTES:
1. ALL TOLERANCES ARE ±0.20 UNLESS OTHERWISE STATED.
2. RECOMMENDED PCB PLATED-THROUGH HOLE SIZE:
DRILLED HOLE = Ø1.15±0.02mm,
PLATING THICKNESSES = 25-75µ COPPER, 3µ MIN NICKEL/GOLD,
FINAL PLATED HOLE = Ø1.09-1.00mm.



HOLE DETAIL FOR 04 CONTACT PER ROW SPACER



SPACER DETAIL



CONNECTOR/SPACER COMPONENT (04 SIZE SHOWN)

PART No.	No. OF CONTACTS PER ROW	DIM 'A'	DIM 'B'	DIM 'C'
M20-6150405	04	11.18	7.62	10.16
M20-6152005	20	51.82	48.26	50.80
M20-6153205	32	82.30	78.74	81.28

ORDER CODE:
M22-615XX05

No. OF CONTACTS PER ROW:
04, 20, 32

FINISH:
05 = GOLD ALL OVER NICKEL

SB	9	09.10.13	12212
NAME	ISS.	DATE	C/NOTE
APPROVED:		S.BENNETT	
CHECKED:		M.PLESTED	
DRAWN:		W. J. BOURNE	
CUSTOMER REF.:			
ASSEMBLY DRG:			

HARWIN

www.harwin.com
technical@harwin.com

THIS DRAWING AND ANY INFORMATION OR DESCRIPTIVE MATTER SET OUT HEREON ARE CONFIDENTIAL AND COPYRIGHT PROPERTY OF THE HARWIN GROUP AND MUST NOT BE DISCLOSED, LOANED, COPIED OR USED FOR MANUFACTURING, TENDERING OR FOR ANY OTHER PURPOSE WITHOUT THEIR WRITTEN PERMISSION.

TOLERANCES
X. = ±1mm
X.X = ±0.25mm
X.XX = ±0.10mm
X.XXX = ±0.01mm
ANGLES = ±5°
UNLESS STATED

MATERIAL:
SEE ABOVE
FINISH:
SEE ABOVE
S/AREA:
mm²

TITLE:
PCI04 PRESS-FIT CONNECTOR & SPACER (STACKTHROUGH)

DRAWING NUMBER:
M20-615XX05

SHT
2 OF 2

AMEYA360

Components Supply Platform

Authorized Distribution Brand :



Website :

Welcome to visit www.ameya360.com

Contact Us :

➤ Address :

401 Building No.5, JiuGe Business Center, Lane 2301, Yishan Rd
Minhang District, Shanghai , China

➤ Sales :

Direct +86 (21) 6401-6692

Email amall@ameya360.com

QQ 800077892

Skype ameyasales1 ameyasales2

➤ Customer Service :

Email service@ameya360.com

➤ Partnership :

Tel +86 (21) 64016692-8333

Email mkt@ameya360.com