



**A. MATERIAL:** 15% Glass Filled Supertough Nylon, UL94 Rated

**B.** The hygroscopic (readily accepts moisture) properties of Nylon will make this tool suitable for use around ESD sensitive components after a few minutes of handling the tool with bare hands. If used with gloves in a clean environment the tools must be dipped in a topical antistatic solution before use in sensitive areas. Topical treatment should be repeated at six month intervals. Without exposure to moisture or antistatic treatment, Nylon is in the insulative resistance range and charges will not be removed to ground.

**C.** Notch for hooking and pulling wires or components.

**D.** Flat "screwdriver" surface for spudging wire leads down flat on circuit boards.

**E.** Pointed end for forming wire leads or for use as pointer probe for holding objects for soldering.

**F.** Date Code (R=2006, S= 2007, T=2008, U=2009, V=2010, W=2011, X=2012, Y=2013, Z=2014)

Melting Point: 450°F (232°C)



Made in the  
United States of America

Specifications and procedures subject to change without notice.

## PROBER, SOLDERING TOOL, NYLON

# MENDA

3651 WALNUT AVE., CHINO, CA 91710  
PHONE: (909) 627-2453 FAX: (951) 755-8848  
WEBSITE: [MendaPump.com](http://MendaPump.com)

**DRAWING NUMBER**  
35622

**DATE:**  
February  
2014

# AMEYA360

## Components Supply Platform

Authorized Distribution Brand :



Website :

Welcome to visit [www.ameya360.com](http://www.ameya360.com)

Contact Us :

➤ Address :

401 Building No.5, JiuGe Business Center, Lane 2301, Yishan Rd  
Minhang District, Shanghai , China

➤ Sales :

Direct +86 (21) 6401-6692

Email [amall@ameya360.com](mailto:amall@ameya360.com)

QQ 800077892

Skype ameyasales1 ameyasales2

➤ Customer Service :

Email [service@ameya360.com](mailto:service@ameya360.com)

➤ Partnership :

Tel +86 (21) 64016692-8333

Email [mkt@ameya360.com](mailto:mkt@ameya360.com)