

MCX and Reverse Polarity MCX Specifications

Materials

Connector Part	Material	Finish
Bodies	Brass	Nickel or Gold
Center contact	Male: Brass	Gold
	Female: Beryllium Copper	
Insulator	PTFE	N/A
Crimp ferrule	Annealed Copper	Nickel or Gold

Electrical

Electrical Data	Detail		
Impedance	50 ohm		
Frequency range	0~6GHz		
Working voltage	RG178, 196/U » 250 volts rms max.		
	RG316/U, semi-rigid » 335 volts rms max.		
Insulation resistance	1,000 megaohms min.		
Dielectric withstanding voltage	RG178/U » 750 volts rms max.		
	RG316/U, semi-rigid » 1,000 volts rms max.		
Contact resistance	Center contact: 5.0 milliohms max.		
	Outer contact: 1.0 milliohms max.		
VSWR: f(GHz)		Straight	Right angle
	RG178/U	1.17+0.04f	1.07+0.06f
	RG316/U, semi rigid	1.13+0.04f	1.07+0.04f
Insertion loss	0.1dB max. (straight)		
	0.2dB max. (right angle)		

Mechanical

Mechanical Data	Detail
Engagement force	5.6lbs max.
Disengagement force	3lbs
Connector durability	500 matings
Cable retention force	RG178/U » 10lbs min.
	RG316/U » 20lbs min.
	semi-rigid » 30lbs min.

Environmental	
Environmental Data	Detail
Corrosion (salt spray)	MIL-STD-202 METHOD 101 TEST CONDITION B
Thermal shock	MIL-STD-202 METHOD 107 TEST CONDITION F
Vibration	MIL-STD-202 METHOD 204 TEST CONDITION B
Mechanical shock	MIL-STD-202 METHOD 213 TEST CONDITION B
Temperature Range	–65°C to 165°C

AMEYA360

Components Supply Platform

Authorized Distribution Brand :



Website :

Welcome to visit www.ameya360.com

Contact Us :

➤ Address :

401 Building No.5, JiuGe Business Center, Lane 2301, Yishan Rd
Minhang District, Shanghai , China

➤ Sales :

Direct +86 (21) 6401-6692
Email amall@ameya360.com
QQ 800077892
Skype ameyasales1 ameyasales2

➤ Customer Service :

Email service@ameya360.com

➤ Partnership :

Tel +86 (21) 64016692-8333
Email mkt@ameya360.com