


XBee® Wi-Fi

Embedded Wi-Fi Module for OEMs

Embedded Wi-Fi modules provide ultra low-power 802.11b/g/n communications in the flexible XBee hardware and software footprint.



Overview

XBee Wi-Fi embedded RF modules provide simple serial to IEEE 802.11 connectivity. By bridging the low-power/low-cost requirements of wireless device networking with the proven infrastructure of 802.11, the XBee Wi-Fi creates new wireless opportunities for energy management, process and factory automation, wireless sensor networks, intelligent asset management and more. Featuring easy provisioning methods and native iDigi® Device Cloud™ connectivity, XBee Wi-Fi modules give developers the fastest IP-to-device and device-to-cloud capability possible. Focused on the rigorous requirements of these wireless device networks, the module gives developers IP-to-device and device-to-cloud capability.

XBee modules offer developers tremendous flexibility and are available in surface mount and through-hole form factors. The XBee Wi-Fi shares a common footprint with other XBee modules. This allows different XBee technologies to be drop-in replacements for each other.

As a member of the XBee family, the XBee Wi-Fi combines hardware with software for a complete modular solution. XBee Wi-Fi modules are designed to communicate with access points in existing 802.11 infrastructures. Developers can use AT and API commands for advanced configuration options.

Related Products



Wi-Fi System-on-Modules




Wi-Fi Modules



iDigi® Solutions



Wireless Serial Servers




XBee Modules



Development Kits

Application Highlight



Features/Benefits

- Native iDigi Device Cloud integration for data acquisition and device management
- Hardware and software complete module easily joins existing 802.11 b/g/n (Wi-Fi) infrastructures
- Common XBee footprint allows OEMs to support a variety of wireless protocols
- Flexible SPI and UART serial interfaces
- Available in Surface Mount and Through-Hole form factors
- Support for low-power sleeping applications with $<6 \mu\text{A}$ power-down current
- Over-the-air data rates up to 72 Mbps
- Simple provisioning methods including Soft AP and Wi-Fi Protected Setup (WPS)



Platform

XBee® Wi-Fi (S6B)

Features	
Serial Data Interface	UART up to 1 Mbps, SPI up to 6 Mbps
Configuration Method	API or AT commands
Frequency Band	ISM 2.4 GHz
ADC Inputs	4 (12-bit)
Digital I/O	10
Form Factor	Through-Hole, Surface Mount
Antenna Options	Through-Hole: PCB (Embedded), U.FL, RPSMA, Integrated Wire SMT: PCB (Embedded), U.FL, RF Pad
Operating Temperature	-30° C to +85° C
Dimensions (L x W)	Through-Hole: 0.960 in x 1.297 in (2.438 cm x 3.294 cm) SMT: 0.87 in x 1.33 in x 0.12 in (2.20 cm x 3.40 cm x 0.30 cm)
Networking and Security	
Security	WPA-PSK, WPA2-PSK and WEP
Channels	13 channels
Wireless LAN	
Standard	802.11b/g/n
Data Rates	1 Mbps to 72 Mbps
Modulation	802.11b: CCK, DSSS 802.11g/n: OFDM with BPSK, QPSK, 16-QAM, 64-QAM
Transmit Power	Up to +16 dBm
Receiver Sensitivity	-93 to -71 dBm
Power Requirements	
Supply Voltage	3.14 - 3.46 VDC
Transmit Current	Up to 309 mA
Receive Current	100 mA
Power-Down Current	<6 µA @ 25° C
Regulatory Approvals	
FCC (USA)	Yes
IC (Canada)	Yes
CE/ETSI (Europe)	Yes
C-TICK (Australia)	Yes
Telec (Japan)	Yes
Anatel (Brazil)	Pending

Visit www.digi.com for part numbers.

DIGI SERVICE AND SUPPORT - You can purchase with confidence knowing that Digi is here to support you with expert technical support and a strong one-year warranty. www.digi.com/support

91001698
B2/213

**Digi International
Worldwide HQ**

877-912-3444
952-912-3444

**Digi International
France**

+33-1-55-61-98-98
www.digi.fr

**Digi International
Japan**

+81-3-5428-0261
www.digi-intl.co.jp

**Digi International
India**

+91-80-4287-9887

**Digi International
Singapore**

+65-6423-0015

**Digi International
China**

+86-21-5150-6898
www.digi.cn

BUY ONLINE • www.digi.com

© 2011-2013 Digi International Inc.
All rights reserved. Digi, Digi International, the Digi logo, the iDigi logo, DigiMesh, iDigi, iDigi Device Cloud and XBee are either trademarks or registered trademarks of Digi International Inc. in the United States and other countries worldwide. All other trademarks are the property of their respective holders. All information provided is subject to change without notice.

info@digi.com



AMEYA360

Components Supply Platform

Authorized Distribution Brand :



Website :

Welcome to visit www.ameya360.com

Contact Us :

➤ Address :

401 Building No.5, JiuGe Business Center, Lane 2301, Yishan Rd
Minhang District, Shanghai , China

➤ Sales :

Direct +86 (21) 6401-6692

Email amall@ameya360.com

QQ 800077892

Skype [ameyasales1](#) [ameyasales2](#)

➤ Customer Service :

Email service@ameya360.com

➤ Partnership :

Tel +86 (21) 64016692-8333

Email mkt@ameya360.com