



MATERIALS:

	CENTER CONTACT	DIELECTRIC	SHELL
1- TYPE `N` MALE	Gold Plated Brass	Teflon	Silver Plated Brass
2- BNC MALE	Gold Plated Phosphor Bronze	Teflon	Silver Plated Brass
3- TNC MALE	Gold Plated Phosphor Bronze	Teflon	Silver Plated Brass
4- SMA MALE	Gold Plated Phosphor Bronze	Teflon	Silver Plated Brass
5- TYPE `N` FEMALE	Gold Plated Phosphor Bronze	Teflon	Silver Plated Brass
6- BNC FEMALE	Gold Plated Phosphor Bronze	Teflon	Silver Plated Brass
7- TNC FEMALE	Gold Plated Phosphor Bronze	Teflon	Silver Plated Brass
8- SMA FEMALE	Gold Plated Phosphor Bronze	Teflon	Silver Plated Brass
9- COUPLING ADAPTER	Gold Plated Phosphor Bronze	Teflon	Silver Plated Brass
10- DOUBLE BANANA PLUG  SCHEMATIC	Spring:	Beryllium copper ASTM B194, alloy 172 cond. Ht.	
	Plug Body:	Brass per QQ-B-626, alloy 360, 1/2 hard.	
	Finish:	Nickel plated per QQ-N-290, class2, 200/300 microinches	
	Insulation:	ABS. Color: Black	
	Center Contact:	Gold plated brass	
	Dielectric:	Teflon	
	Shell:	Silver plated brass	

All dimensions are in inches. Tolerances (except noted): .xx = ±.02" (.51 mm), .xxx = ±.005" (.127 mm).

All specifications are to the latest revisions. Specifications are subject to change without notice.

Registered trademarks are the property of their respective companies. Made in USA

11- DOUBLE BINDING POST  SCHEMATIC	Body: Brass per QQ-B-626, alloy 360, ½ hard Finish: Nickel plated per QQ-N-290, class 2, 200/300 microinches Insulation: Polycarbonate. Color: one black, one red Insulation, Body: ABS. Color: Black Center Contact: Gold plated phosphor bronz Dielectric: Teflon Shell: Silver plated brass
--	--

	CENTER CONTACT	DIELECTRIC	SHELL
12- UHF MALE	Gold Plated Phosphor Bronze	Teflon	Silver Plated Brass
13- UHF FEMALE	Gold Plated Phosphor Bronze	Teflon	Silver Plated Brass
14- MINI UHF MALE	Gold Plated Phosphor Bronze	Teflon	Silver Plated Brass
15- MINI UHF FEMALE	Gold Plated Phosphor Bronze	Teflon	Silver Plated Brass
16- RCA PHONO MALE	Gold Plated Phosphor Bronze	Teflon	Silver Plated Brass
17- RCA PHONO FEMALE	Gold Plated Phosphor Bronze	Teflon	Silver Plated Brass
18- TYPE F MALE	Gold Plated Phosphor Bronze	Teflon	Silver Plated Brass
19- TYPE F FEMALE	Gold Plated Phosphor Bronze	Teflon	Silver Plated Brass
20- UNIDAPT SIGNAL SAMPLER	Gold Plated Phosphor Bronze	Teflon	Silver Plated Brass
21- LABEL, NOT SHOWN			
22- PLASTIC BOX W/ FOAMS			
23- PART CARD, NOT SHOWN			

RATINGS:

Operating Temp:

Items 1 through 9 and 12 through 20 : -67° F to +302° F (55° C to +150° C).

Items 10 and 11 : +122° F MAX. (+50° C MAX.)

Nomial Impedance:

Items 1 through 9 and 20: 50 Ohms.

Items 18 through 19: 75 Ohms.

Vswr Max.:

Items 1 through 9: 1.2: 1 (DC- 1GHz).

Items 12 through 15: 1.2: (DC- 300MHz).

Frequency Range:

Items 12 through 15: (500MHz MAX.)

Items 16 through 19: (DC to 300MHz).

Item 20: (50MHz to 3GHz).

Weight: 2.40 pounds.

All dimensions are in inches. Tolerances (except noted): .xx = ±.02" (.51 mm), .xxx = ± .005" (.127 mm).

All specifications are to the latest revisions. Specifications are subject to change without notice.

Registered trademarks are the property of their respective companies. Made in USA

AMEYA360

Components Supply Platform

Authorized Distribution Brand :



Website :

Welcome to visit www.ameya360.com

Contact Us :

➤ Address :

401 Building No.5, JiuGe Business Center, Lane 2301, Yishan Rd
Minhang District, Shanghai , China

➤ Sales :

Direct +86 (21) 6401-6692

Email amall@ameya360.com

QQ 800077892

Skype [ameyasales1](#) [ameyasales2](#)

➤ Customer Service :

Email service@ameya360.com

➤ Partnership :

Tel +86 (21) 64016692-8333

Email mkt@ameya360.com