

## **SP-4**

#### **Description:**

Triad's high reliability audio transformers provide the durability and precision required in today's demanding designs. These transformers are available for a wide variety of applications.

#### **Electrical Specifications (@25C)**

Power	Matching Impedance		Max. Ma DC	DC Resistance (Ω)		Overall
level	D	Saaan daara	Unbalance	D	Saaandarra	Turns
(mW)	Primary	Secondary	in Primary	Primary	Secondary	Ratio
10	200,000 CT	1,000 CT	0.0	5,300.0	100.0	14.1:1.0


Frequency Response: + 2.0 DB, at 300 Hz to 100K Hz

Pri-Sec Hipot test (Pri-Sec): 1,000 VRMS for 1 sec.

Working voltage: 150VDC

#### **Construction:**

Plug-in terminals are precision spaced to provide fixed mounting centers. Epoxy molded case includes a .020" recess for ease of solder inspection. Leads are made of high strength Nickel alloy, gold plated and are .020" in diameter.




**RoHS Compliance:** As of manufacturing date February 2005, all standard products meet the requirements of 2002/95/EC, known as the RoHS initiative.

\*Upon printing, this document is considered "uncontrolled". Specifications are subjected to change without notice. Please contact Triad Magnetics' website for the most current version.

Web: www.TriadMagnetics.com Phone 951-277-0757 Fax 951-277-2757	22520B Temescal Canyon Road Corona, California 92883	Publish Date: June 19, 2006
---	--	-----------------------------





# **AMEYA360** Components Supply Platform

## Authorized Distribution Brand :



### Website :

Welcome to visit www.ameya360.com

## Contact Us :

#### > Address :

401 Building No.5, JiuGe Business Center, Lane 2301, Yishan Rd Minhang District, Shanghai , China

#### > Sales :

- Direct +86 (21) 6401-6692
- Email amall@ameya360.com
- QQ 800077892
- Skype ameyasales1 ameyasales2

#### > Customer Service :

Email service@ameya360.com

## > Partnership :

Tel +86 (21) 64016692-8333

Email mkt@ameya360.com