

Single-Phase Auto Transfer Switch / Switched PDU 1.9kW 20A 120V, 1U Horizontal Rackmount, 16 5-15/20R outlets, 2 L5-20P / 5-20P inputs

MODEL NUMBER: PDUMH20ATNET



Specifications

OVERVIEW	
Style	Rackmount
PDU Type	Auto-Transfer Switch; Switched
OUTPUT	
Output Capacity Details	1.9kW (120V input), 2.0kW (127V input), 1.6kW (100V input); 20A maximum (Agency de-rated to 16A continuous)
Frequency Compatibility	60 Hz
Output (VA)	2400
Output Nominal Voltage	100-127V nominal, single phase
Outlet Quantity / Type	16 NEMA 5-15/20R
Number of Outlets	16
Outlet Type	NEMA 5-15R, NEMA 5-20R
Customized Load Management Receptacles	16 individually controlled load management receptacles
INPUT	
PDU Input Voltage	100; 120; 127
Maximum Input Amps	20
Maximum Input Amps Details	Agency de-rated to 16A continuous



Tripp Lite
1111 W. 35th Street
Chicago, IL 60609 USA
Telephone: 773.869.1234
www.tripplite.com

PDU Plug Type	NEMA 5-20P; NEMA L5-20P
Input Cord Length Details	Both input cables are 12 ft / 3.6m - the cables each terminate to a L5-20P locking plug on the input side. Two included 6 inch plug adapters convert the locking plugs to NEMA 5-20P plugs
Input Phase	Single-Phase
LEDS ALARMS & SWITCHES	
Front Panel LEDs	16 front panel LEDs display power on - off status for each outlet, plus 2 LEDs for power status on each input line cord. Digital current meter display shows the amount of power consumption in amps for entire output of PDU.
PHYSICAL	
Shipping Dimensions (hwd / in.)	6.25 x 22.5 x 23.5
Shipping Dimensions (hwd / cm)	15.9 x 57.2 x 59.7
Shipping Weight (lbs.)	16.4
Shipping Weight (kg)	7.4
Unit Dimensions (hwd / in.)	1.75 x 17.5 x 14.5
Unit Dimensions (hwd / cm)	4.44 x 44.4 x 36.8
Unit Weight (lbs.)	12.2
Unit Weight (kg)	5.5
Material of Construction	Steel
Form Factors Supported	1U rackmount
PDU Form Factor	Horizontal (1U, 2U, etc)
ENVIRONMENTAL	
Relative Humidity	Up to 95% (non-condensing)
COMMUNICATIONS	
SNMP Compatibility	Yes, via pre-installed SNMPWEBCARD . Provides remote monitoring, outlet control, and automatic power management configurations.
CERTIFICATIONS	
TAA Compliant Option	TAA Compliant Version Available - Order Tripp Lite PDUMH20ATNETAA
Certifications	Tested to UL 60950 (USA, Canada), Class A (Emissions), NOM (Mexico), RoHS Compliant
WARRANTY	
Product Warranty Period (Worldwide)	2-year limited warranty

AMEYA360

Components Supply Platform

Authorized Distribution Brand :



Website :

Welcome to visit www.ameya360.com

Contact Us :

➤ Address :

401 Building No.5, JiuGe Business Center, Lane 2301, Yishan Rd
Minhang District, Shanghai , China

➤ Sales :

Direct +86 (21) 6401-6692

Email amall@ameya360.com

QQ 800077892

Skype ameyasales1 ameyasales2

➤ Customer Service :

Email service@ameya360.com

➤ Partnership :

Tel +86 (21) 64016692-8333

Email mkt@ameya360.com