

# GLD140 Gold Performance Medical Switchers

## 140 Watt Multiple Output



### FEATURES:

- Compact size (4.5" x 8.5" x 1.95")
- Power factor corrected to IEC 1000-3-2 Class A
- Documented FMEA, WCA and EMC test results
- EMI compliance to CISPR11, FCC Class B, IEC601-1-2
- Approved to UL2601, IEC601-1 and CSA 22.2 No. 601.1-M90 and EN60601: 1990
- **CE** marked to LVD

### SPECIFICATIONS:

#### Ac Input

90-264 Vac, 47-63 Hz single phase.

#### Output Power

Continuous output power 140 W with unrestricted convection cooling, 180 W with 150 LFM of air.

#### Input Current

Active Power Factor Correction circuitry assures compliance with IEC1000-3-2, Class A. Maximum input current at minimum input voltage and full load is 3.0 A.

#### Efficiency

73 – 85 % at full rated load, nominal input voltage, depending on model and load distribution.

#### Hold-up Time

26 ms total. 16 ms minimum from loss of ac input at full load until activation of the power fail signal. Output voltages remain within specified regulation limits for an additional 9 ms minimum after power fail activates.

#### Overload Protection

Fully protected against short circuit and output overload. Short circuit protection is cycling type power limit.

#### Output Noise

0.5% rms, 1% pk-pk, 20 MHz Bandwidth, differential mode. Measured with noise probe directly across output terminals of the power supply.

#### Transient Response

500  $\mu$ s typical response time for return to within 0.5% of final value for a 45% load step from any load greater than 10% of full rated load,  $\Delta I/\Delta t < 0.2$  A  $\mu$ s. Maximum voltage deviation is 3.5%.

#### Remote Sense

Provided as a standard feature on V1 and V2.

#### Overvoltage Protection

Built in on V1, 2 and 3 outputs.

#### Voltage Adjustment

Factory set to specified voltage with user adjustable potentiometer on V1, 2 and 3. User can adjust V1, 2 and 3 at least  $\pm 5\%$  of nominal output voltage.

#### Output Regulation

Regulation for all outputs is the maximum deviation from initial set point under all line and load conditions. Initial set tolerance is measured with all outputs at 50 % of full rated load.

#### No Load Turn-On/Standby

A minimum load of 3 A on V1 is required for proper regulation. If not met, no degradation of reliability will occur.

#### Temperature Coefficient

0.03% /  $^{\circ}$ C typical on all outputs.

#### Input Protection

Internal ac fuses provided on both lines on all units.

#### Inrush Current

Inrush is limited by internal thermistors. The inrush at 240 Vac, averaged over the first ac half-cycle under cold start conditions will not exceed 37 A.

#### Thermal Shutdown

Provided as a standard feature. Designed to protect unit from prolonged over temperature.

#### Power Fail

TTL / CMOS compatible output goes low ( $< 0.5$  V) 10 ms before output voltage drops more than 4% below nominal voltage upon loss of ac power.

#### Power Good

TTL / CMOS compatible output rises high 100 to 300 ms after V1 reaches regulation and should assure that sufficient energy is stored in the input section to provide normal power fail / shutdown.

#### Inhibit

Inhibit signal when pulled to the V1 output common will inhibit all output voltages.

#### Fan Output

An additional thermally controlled 12 Vdc, 250 mA output suitable for powering a dc fan is included in all models (Factory installed cover with fan makes this output unavailable).

#### EMI/EMC Compliance

All models include built-in EMI filtering to meet the following requirements:

EMC SPECIFICATION	COMPLIANCE LEVEL
Conducted Emissions	EN55011, Class B; FCC Class B
Static Discharge	EN61000-4-2, 6 kV contact 8 kV air
RF Field Susceptibility	EN61000-4-3, 3V/meter
Fast Transients / Bursts	EN61000-4-4, 2 kV, 5 kHz
Surge Susceptibility	EN61000-4-5, 1 kV diff., 2 kV com.
Conducted RF Susceptibility	EN61000-4-6, 3V
Voltage Sags & Surges	EN61000-4-11
Line Frequency Harmonics	EN61000-3-2 Class A

#### EMC Compliance for Gold Series

Magnetic Emissions - Emissions will not exceed the limits of the Army curve in MIL-STD-461D, RE101 when measured at 7 cm from 30 Hz - 100 kHz over all nominal inputs and at full rated load.

#### Leakage Current

70  $\mu$ A under normal conditions 120 Vac @ 60 Hz  
Single fault conditions 280  $\mu$ A, 264 Vac @ 50 Hz.

#### SAFETY AGENCY APPROVALS:

All models are Certified to be in compliance with the applicable requirements of UL2601-1, CSA-C22.2 No. 601.1, IEC 601-1/60601-1.

#### DESIGN VERIFICATION DOCUMENTS

The "Gold" series has undergone rigorous review and design analysis. The following product documentation is available upon request: 1. Failure Mode and Effects analysis (FMEA), 2. DVT Data, 3. EMC / Susceptibility test results.



# AMEYA360

Components Supply Platform

Authorized Distribution Brand :



Website :

Welcome to visit [www.ameya360.com](http://www.ameya360.com)

Contact Us :

➤ Address :

401 Building No.5, JiuGe Business Center, Lane 2301, Yishan Rd  
Minhang District, Shanghai , China

➤ Sales :

Direct      +86 (21) 6401-6692  
Email        amall@ameya360.com  
QQ            800077892  
Skype        ameyasales1 ameyasales2

➤ Customer Service :

Email        service@ameya360.com

➤ Partnership :

Tel            +86 (21) 64016692-8333  
Email        mkt@ameya360.com