# **Product Data Sheet**

## 3M™ Ionized Air Gun 980/980E

The lonized Air Gun 980/980E is an excellent tool for blowing particulate contaminates off of most surfaces, even from static-sensitive products. It releases a constantly balanced stream of compressed ionized air or gas that neutralizes static charge that attracts particulates to a surface. A charge of 1000 volts is reduced to less than 100 volts in less than a second. The loose particles can then be easily blown away.

#### Self-balancing, maintenance-free

The unique ionization system used in the lonized Air Gun 980/980E is completely self-balancing; no adjustment or calibration is needed. It maintains balance to within <60V of 0V (at a distance of 6 inches). The unit is also virtually maintenance-free; all that is required is occasional cleaning of the housing and the emitter points.

#### Unique ergonomic design

The lonized Air Gun 980/980E was designed to be a lightweight, comfortable, and easy-to-use ionizing air gun. All components of the system – the hand unit and power supply, air hose and power line, and the mounting console – are extremely lightweight. Unlike the heavy power supplies of some systems that must be tied to the hand unit by means of a bulky high-voltage cable, the compact power supply of the lonized Air Gun 980/980E is actually molded into the housing of the air gun. The power to the hand unit is supplied via a thin, low-voltage wire that runs from the console inside the flexible polyurethane air hose. Thus, the lonized Air Gun 980/980E has only a single flexible, lightweight hose between the base and the gun, making it easier to handle. The total weight of the hand unit and the 7' long air/power hose is only 12 ounces. The nozzle on the tip of the gun is specially designed to provide efficient, uniform delivery of ionized air while minimizing audible noise and air or gas usage.

#### Safe, low-voltage power

The lonized Air Gun 980/980E uses safe, efficient, low-voltage power. Each unit includes a transformer that converts line power from a standard outlet (120V for the 980, 230V for the 980E) to 24 volts. lonized Air Gun 980/980E units meet existing industry requirements and carry the UL, C-UL, and CE marks, as appropriate.

#### **Durable Construction**

The hand unit and console are molded of rugged, dissipative polycarbonate for exceptional impact resistance. The static-dissipative properties make them safe to use around sensitive electronic components. The air hose is made of tough, flexible polyurethane and is also static-dissipative.

#### **Convenient Mounting Console**

The mounting console contains connections for the air lines and power lines and houses the filter attached to the air line. It weighs just 11.5 ounces, measures  $8.5^{\circ}L \times 3.0^{\circ}W \times 1.6^{\circ}H$  (21.6 x 7.6 x 4.1 cm), and is easily mounted in a convenient location at the workstation. Hardware is included for either permanent (using a metal backplate) or semipermanent (using hook and loop type strips) mounting.

#### **Replacement/Optional Parts**

The air line filter and the emitter points at the tip of the hand unit are the only replaceable parts of the lonized Air Gun 980/980E. When necessary, each can be replaced in just seconds without any special tools.





3M™ Ionized Air Gun 980/980E



# **Product Data Sheet**

## 3M™ Ionized Air Gun 980/980E

Typical Properties	
Source power	120VAC (980), 230VAC (980E)
Input Power	24VAC, < 10W (both models)
Ion output	Steady state DC
Performance (per ANSI/ESD-S3.1) Discharge time (1000V to 100V) Ion balance Audible noise Ozone	< 1 sec @ 6 in, 30 psi <60V 73 dBA @ 1 m, 30 psi < 0.005 ppm (24 hr accumulation)
Console Construction Size  Weight Gas input Air fittings Power connections	Dissipative rigid polycarbonate 8.5 L x 3.0 W x 1.6 H in (21.6 x 7.6 x 4.1 cm) 11.5 ounces (326 g) 20-65 psi, clean dry air or nitrogen Standard 1/4 in industrial RJ-11 telephone snap-in connector

**Typical Properties** Hand Unit Construction Dissipative rigid polycarbonate Size 8.0 L x 3.0 W x 1.0 D in (20.3 x 7.6 x 2.5 cm) 12.0 oz (341 g) with 7 ft air hose Weight **Emitter points** Tungsten alloy Air Hose Construction Dissipative flexible polyurethane 7 ft long, 0.38" OD Size Filter efficiency 99.9% for 0.1 micron particle size

3M is a trademark of 3M Company. All other trademarks are owned by their respective companies.

#### **Important Notice**

All statements, technical information, and recommendations related to 3M's products are based on information believed to be reliable, but the accuracy or completeness is not guaranteed. Before using this product, you must evaluate it and determine if it is suitable for your intended application. You assume all risks and liability associated with such use. Any statements related to the product which are not contained in 3M's current publications, or any contrary statements contained on your purchase order shall have no force or effect unless expressly agreed upon, in writing, by an authorized officer of 3M.

#### Warranty; Limited Remedy; Limited Liability.

This product will be free from defects in material and manufacture for one year from the time of purchase. 3M MAKES NO OTHER WARRANTIES INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. If this product is defective within the warranty period stated above, your exclusive remedy shall be, at 3M's option, to replace or repair the 3M product or refund the purchase price of the 3M product. Except where prohibited by law, 3M will not be liable for any indirect, special, incidental or consequential loss or damage arising from this 3M product, regardless of the legal theory asserted.



**Electronics Materials Solutions Division Static Control Products** 

926 JR Industrial Drive Sanford, NC 27332-9733 Toll-Free: 866-722-3736 International: 919-718-0000 Email: 3mstaticinfo@mmm.com www.3Mstatic.com

# AMEYA360 Components Supply Platform

# Authorized Distribution Brand:

























# Website:

Welcome to visit www.ameya360.com

## Contact Us:

# > Address:

401 Building No.5, JiuGe Business Center, Lane 2301, Yishan Rd Minhang District, Shanghai , China

## ➤ Sales:

Direct +86 (21) 6401-6692

Email amall@ameya360.com

QQ 800077892

Skype ameyasales1 ameyasales2

## Customer Service :

Email service@ameya360.com

# Partnership :

Tel +86 (21) 64016692-8333

Email mkt@ameya360.com