



## **PTC thermistors for overcurrent protection**

Leaded disks, coated, 230 V

**Series/Type:**      **B598\*\***

**Date:**              December 2007

## Overcurrent protection

### Leaded disks, coated, 230 V

C810 ... C890

#### Applications

- Overcurrent and short-circuit protection

#### Features

- Lead-free terminals
- Manufacturer's logo and type designation stamped on in black or red for  $T_{ref} = 80\text{ °C}$  and for  $T_{ref} = 120\text{ °C}$  and  $130\text{ °C}$  stamped on in white
- Short response times
- UL approval for  $T_{ref} = 130\text{ °C}$  to UL 1434 with  $V_{max} = 220\text{ V}$  and  $V_R = 220\text{ V}$  (file number E69802)
- UL approval for  $T_{ref} = 120\text{ °C}$  to UL 1434 with  $V_{max} = 230\text{ V}$  and  $V_R = 220\text{ V}$  (file number E69802)
- UL approval for  $T_{ref} = 80\text{ °C}$  to UL 1434 with  $V_{max} = 165\text{ V}$  and  $V_R = 145\text{ V}$  (file number E69802)
- VDE approval (license number 104843 E)
- RoHS-compatible

#### Options

- Leadless disks and leaded disks without coating available on request
- Thermistors with diameter  $b \leq 11.0\text{ mm}$  are also available on tape (to IEC 60286-2)

#### Delivery mode


- Cardboard strips (standard)
- Cardboard tape reeled or in Ammo pack on request

## Overcurrent protection

Leaded disks, coated, 230 V

C810 ... C890

### Dimensional drawing



TPT0648-4

### Dimensions (mm)

| Type | T <sub>ref</sub><br>°C | b <sub>max</sub> | h <sub>max</sub> | Ød  |
|------|------------------------|------------------|------------------|-----|
| C810 | 130                    | 22.0             | 25.5             | 0.8 |
| C830 | 80                     | 22.0             | 25.5             | 0.6 |
| C830 | 120                    | 22.0             | 25.5             | 0.6 |
| C830 | 130                    | 17.5             | 21.0             | 0.8 |
| C840 | 80                     | 17.5             | 21.0             | 0.6 |
| C840 | 120                    | 17.5             | 21.0             | 0.6 |
| C840 | 130                    | 13.5             | 17.0             | 0.6 |
| C850 | 80                     | 13.5             | 17.0             | 0.6 |
| C850 | 120                    | 13.5             | 17.0             | 0.6 |
| C850 | 130                    | 11.0             | 14.5             | 0.6 |
| C860 | 80                     | 11.0             | 14.5             | 0.6 |
| C860 | 120                    | 11.0             | 14.5             | 0.6 |
| C860 | 130                    | 9.0              | 12.5             | 0.6 |

| Type | T <sub>ref</sub><br>°C | b <sub>max</sub> | h <sub>max</sub> | Ød  |
|------|------------------------|------------------|------------------|-----|
| C870 | 80                     | 9.0              | 12.5             | 0.6 |
| C870 | 120                    | 9.0              | 12.5             | 0.6 |
| C870 | 130                    | 6.5              | 10.0             | 0.6 |
| C872 | 120                    | 9.0              | 12.5             | 0.6 |
| C873 | 120                    | 9.0              | 12.5             | 0.6 |
| C874 | 120                    | 9.0              | 12.5             | 0.6 |
| C875 | 120                    | 9.0              | 12.5             | 0.6 |
| C880 | 80                     | 6.5              | 10.0             | 0.6 |
| C880 | 120                    | 6.5              | 10.0             | 0.6 |
| C880 | 130                    | 4.0              | 7.5              | 0.6 |
| C883 | 120                    | 6.5              | 10.0             | 0.6 |
| C890 | 80                     | 4.0              | 7.5              | 0.5 |
| C890 | 120                    | 4.0              | 7.5              | 0.5 |

### General technical data

|                             |                                      |                  |          |            |
|-----------------------------|--------------------------------------|------------------|----------|------------|
| Max. operating voltage      | (T <sub>A</sub> = 60 °C)             | V <sub>max</sub> | 265      | VDC or VAC |
| Rated voltage               |                                      | V <sub>R</sub>   | 230      | VDC or VAC |
| Switching cycles            |                                      | N                | 100      |            |
| Tolerance of R <sub>R</sub> | (T <sub>ref</sub> = 80 °C or 120 °C) | ΔR <sub>R</sub>  | ±25      | %          |
| Tolerance of R <sub>R</sub> | (T <sub>ref</sub> = 130 °C)          | ΔR <sub>R</sub>  | ±20      | %          |
| Operating temperature range | (V = 0)                              | T <sub>op</sub>  | -40/+125 | °C         |
| Operating temperature range | (V = V <sub>max</sub> )              | T <sub>op</sub>  | 0/+60    | °C         |

## Overcurrent protection

Leaded disks, coated, 230 V

C810 ... C890

### Electrical specifications and ordering codes

| Type | $I_R$<br>mA | $I_S$<br>mA | $I_{Smax}$<br>( $V = V_{max}$ )<br>A | $I_r$<br>( $V = V_{max}$ )<br>typ.<br>mA | $T_{ref}$<br>°C | $R_R$<br>$\Omega$ | $R_{min}$<br>$\Omega$ | Ordering code   |
|------|-------------|-------------|--------------------------------------|--|-----------------|-------------------|-----------------------|-----------------|
| C810 | 650         | 980         | 7.0                                  | 20                                       | 130             | 3.5               | 2.3                   | B59810C0130A070 |
| C830 | 460         | 920         | 7.0                                  | 20                                       | 120             | 3.7               | 2.4                   | B59830C0120A070 |
| C830 | 450         | 680         | 4.1                                  | 15                                       | 130             | 5                 | 3.3                   | B59830C0130A070 |
| C840 | 330         | 500         | 2.2                                  | 13                                       | 130             | 9                 | 5.9                   | B59840C0130A070 |
| C840 | 330         | 660         | 4.1                                  | 15                                       | 120             | 6                 | 3.8                   | B59840C0120A070 |
| C830 | 250         | 510         | 7.0                                  | 15                                       | 80              | 3.7               | 2.2                   | B59830C0080A070 |
| C850 | 200         | 320         | 1.5                                  | 10                                       | 130             | 13                | 8.6                   | B59850C0130A070 |
| C850 | 200         | 400         | 2.2                                  | 13                                       | 120             | 10                | 6.4                   | B59850C0120A070 |
| C840 | 170         | 350         | 4.1                                  | 10                                       | 80              | 6                 | 3.6                   | B59840C0080A070 |
| C860 | 140         | 230         | 1.0                                  | 9  | 130             | 25                | 16.5                  | B59860C0130A070 |
| C860 | 140         | 280         | 1.5                                  | 10                                       | 120             | 15                | 9                     | B59860C0120A070 |
| C850 | 110         | 230         | 2.2                                  | 8  | 80              | 10                | 6                     | B59850C0080A070 |
| C870 | 100         | 150         | 0.4                                  | 6  | 130             | 50                | 33                    | B59870C0130A070 |
| C870 | 100         | 200         | 1.0                                  | 9  | 120             | 25                | 15                    | B59870C0120A070 |
| C860 | 90          | 180         | 1.5                                  | 6  | 80              | 15                | 7.8                   | B59860C0080A070 |
| C872 | 80          | 160         | 1.0                                  | 9  | 120             | 35                | 21                    | B59872C0120A070 |
| C873 | 70          | 140         | 1.0                                  | 9  | 120             | 45                | 27                    | B59873C0120A070 |
| C870 | 60          | 130         | 1.0                                  | 5  | 80              | 25                | 13                    | B59870C0080A070 |
| C874 | 60          | 125         | 1.0                                  | 9  | 120             | 55                | 31                    | B59874C0120A070 |
| C875 | 55          | 110         | 1.0                                  | 9  | 120             | 65                | 36                    | B59875C0120A070 |
| C880 | 55          | 90          | 0.2                                  | 5  | 130             | 160               | 106                   | B59880C0130A070 |
| C880 | 55          | 110         | 0.4                                  | 6  | 120             | 70                | 39                    | B59880C0120A070 |
| C883 | 35          | 70          | 0.4                                  | 5  | 120             | 120               | 67                    | B59883C0120A070 |
| C880 | 30          | 70          | 0.4                                  | 4  | 80              | 70                | 36.7                  | B59880C0080A070 |
| C890 | 30          | 60          | 0.2                                  | 5  | 120             | 150               | 84                    | B59890C0120A070 |
| C890 | 15          | 40          | 0.2                                  | 3  | 80              | 150               | 78.7                  | B59890C0080A070 |

**Overcurrent protection**
**Leaded disks, coated, 230 V**
**C810 ... C890**
**Reliability data**

| Test                           | Standard    | Test conditions   | $ \Delta R_{25}/R_{25} $ |
|--------------------------------|-------------|---|--------------------------|
| Electrical endurance, cycling  | IEC 60738-1 | Room temperature, $I_{Smax}, V_{max}$<br>Number of cycles: 100  | < 25%                    |
| Electrical endurance, constant | IEC 60738-1 | Storage at $V_{max}/T_{op}$<br>Test duration : 1000 h   | < 25%                    |
| Damp heat                      | IEC 60738-1 | Temperature of air: 40 °C<br>Relative humidity of air: 93%<br>Duration: 56 days<br>Test according to IEC 60068-2-78   | < 10%                    |
| Rapid change of temperature    | IEC 60738-1 | $T = T_{LCT}, T = T_{UCT}$<br>Number of cycles: 5<br>Test duration: 30 min<br>Test according to IEC 60068-2-14, Test Na   | < 10%                    |
| Vibration                      | IEC 60738-1 | Frequency range: 10 to 55 Hz<br>Displacement amplitude: 0.75 mm<br>Test duration: 3 · 2 h<br>Test according to IEC 60028-2-6, Test Fc   | < 5%                     |
| Bump                           | IEC 60738-1 | Pulse shape: half-sine<br>Acceleration: 50 g<br>Pulse duration: 1 ms; 6 · 3 pulses<br>Test according to IEC 60068-2-29  | < 5%                     |
| Climatic sequence              | IEC 60738-1 | Dry heat: $T = T_{UCT}$<br>Test duration: 16 h<br>Damp heat first cycle<br>Cold: $T = T_{LCT}$<br>Test duration: 2 h<br>Damp heat 5 cycles<br>Tests performed according to IEC 60068-2-30 | < 10%                    |

## Overcurrent protection

Leaded disks, coated, 230 V


C810 ... C890

### Characteristics (typical) for $T_{ref} = 80\text{ °C}$

PTC resistance  $R_{PTC}$  versus


PTC temperature  $T_{PTC}$

(measured at low signal voltage)




PTC current  $I_{PTC}$  versus PTC voltage  $V_{PTC}$

(measured at 25 °C in still air)




Switching time  $t_s$  versus switching current  $I_s$

(measured at 25 °C in still air)



Rated current  $I_R$  versus ambient temperature  $T_A$

(measured in still air)



## Overcurrent protection

Leaded disks, coated, 230 V


C810 ... C890

### Characteristics (typical) for $T_{ref} = 80\text{ }^{\circ}\text{C}$

PTC resistance  $R_{PTC}$  versus


PTC temperature  $T_{PTC}$

(measured at low signal voltage)




PTC current  $I_{PTC}$  versus PTC voltage  $V_{PTC}$

(measured at 25 °C in still air)




Switching time  $t_s$  versus switching current  $I_s$

(measured at 25 °C in still air)



Rated current  $I_R$  versus ambient temperature  $T_A$

(measured in still air)



## Overcurrent protection

Leaded disks, coated, 230 V


C810 ... C890

### Characteristics (typical) for $T_{ref} = 120\text{ }^{\circ}\text{C}$


PTC resistance  $R_{PTC}$  versus

PTC temperature  $T_{PTC}$

(measured at low signal voltage)




Switching time  $t_s$  versus switching current  $I_s$   
(measured at 25  $^{\circ}\text{C}$  in still air)




PTC current  $I_{PTC}$  versus PTC voltage  $V_{PTC}$

(measured at 25  $^{\circ}\text{C}$  in still air)



Rated current  $I_R$  versus ambient temperature  $T_A$   
(measured in still air)





## Overcurrent protection

Leaded disks, coated, 230 V


C810 ... C890

### Characteristics (typical) for $T_{ref} = 120\text{ }^{\circ}\text{C}$

PTC resistance  $R_{PTC}$  versus


PTC temperature  $T_{PTC}$

(measured at low signal voltage)




PTC current  $I_{PTC}$  versus PTC voltage  $V_{PTC}$


(measured at 25 °C in still air)



Switching time  $t_s$  versus switching current  $I_s$   
(measured at 25 °C in still air)



Rated current  $I_R$  versus ambient temperature  $T_A$   
(measured in still air)



## Overcurrent protection

Leaded disks, coated, 230 V


C810 ... C890

### Characteristics (typical) for $T_{ref} = 120\text{ }^{\circ}\text{C}$


PTC resistance  $R_{PTC}$  versus

PTC temperature  $T_{PTC}$


(measured at low signal voltage)




Switching time  $t_s$  versus switching current  $I_s$   
(measured at 25  $^{\circ}\text{C}$  in still air)



PTC current  $I_{PTC}$  versus PTC voltage  $V_{PTC}$   
(measured at 25  $^{\circ}\text{C}$  in still air)



Rated current  $I_R$  versus ambient temperature  $T_A$   
(measured in still air)



## Overcurrent protection

Leaded disks, coated, 230 V


C810 ... C890

### Characteristics (typical) for $T_{ref} = 130\text{ }^{\circ}\text{C}$

PTC resistance  $R_{PTC}$  versus


PTC temperature  $T_{PTC}$

(measured at low signal voltage)




PTC current  $I_{PTC}$  versus PTC voltage  $V_{PTC}$

(measured at 25  $^{\circ}\text{C}$  in still air)




Switching time  $t_s$  versus switching current  $I_s$

(measured at 25  $^{\circ}\text{C}$  in still air)



Rated current  $I_R$  versus ambient temperature  $T_A$

(measured in still air)



## Overcurrent protection

Leaded disks, coated, 230 V


C810 ... C890

### Characteristics (typical) for $T_{ref} = 130\text{ °C}$

PTC resistance  $R_{PTC}$  versus


PTC temperature  $T_{PTC}$

(measured at low signal voltage)




PTC current  $I_{PTC}$  versus PTC voltage  $V_{PTC}$

(measured at 25 °C in still air)




Switching time  $t_s$  versus switching current  $I_s$

(measured at 25 °C in still air)



Rated current  $I_R$  versus ambient temperature  $T_A$

(measured in still air)



## **Cautions and warnings**

### **General**

- EPCOS thermistors are designed for specific applications and should not be used for purposes not identified in our specifications, application notes and data books unless otherwise agreed with EPCOS during the design-in-phase.
- Ensure suitability of thermistor through reliability testing during the design-in phase. The thermistors should be evaluated taking into consideration worst-case conditions.

### **Storage**

- Store thermistors only in original packaging. Do not open the package before storage.
- Storage conditions in original packaging: storage temperature  $-25\text{ }^{\circ}\text{C} \dots +45\text{ }^{\circ}\text{C}$ , relative humidity  $\leq 75\%$  annual mean, maximum 95%, dew precipitation is inadmissible.
- Avoid contamination of thermistors surface during storage, handling and processing.
- Avoid storage of thermistor in harmful environment with effect on function on long-term operation (examples given under operation precautions).
- Use thermistor within 6 months after delivery.

### **Handling**

- PTCs must not be dropped. Chip-offs must not be caused during handling of PTCs.
- Components must not be touched with bare hands. Gloves are recommended.
- Avoid contamination of thermistor surface during handling.

### **Soldering (where applicable)**

- Use rosin-type flux or non-activated flux.
- Insufficient preheating may cause ceramic cracks.
- Rapid cooling by dipping in solvent is not recommended.
- Complete removal of flux is recommended.
- Standard PTC heaters are not suitable for soldering.

### **Mounting**

- Electrode must not be scratched before/during/after the mounting process.
- Contacts and housing used for assembly with thermistor have to be clean before mounting. Especially grease or oil must be removed.
- When PTC thermistors are encapsulated with sealing material, the precautions given in chapter "Mounting instructions", "Sealing and potting" must be observed.
- When the thermistor is mounted, there must not be any foreign body between the electrode of the thermistor and the clamping contact.
- The minimum force of the clamping contacts pressing against the PTC must be 10 N.
- During operation, the thermistor's surface temperature can be very high. Ensure that adjacent components are placed at a sufficient distance from the thermistor to allow for proper cooling at the thermistors.
- Ensure that adjacent materials are designed for operation at temperatures comparable to the surface temperature of thermistor. Be sure that surrounding parts and materials can withstand this temperature.
- Avoid contamination of thermistor surface during processing.

**Overcurrent protection****Leaded disks, coated, 230 V****C810 ... C890****Operation**

- Use thermistors only within the specified temperature operating range.
- Use thermistors only within the specified voltage and current ranges.
- Environmental conditions must not harm the thermistors. Use thermistors only in normal atmospheric conditions. Avoid use in deoxidizing gases (chlorine gas, hydrogen sulfide gas, ammonia gas, sulfuric acid gas etc), corrosive agents, humid or salty conditions. Contact with any liquids and solvents should be prevented.
- Be sure to provide an appropriate fail-safe function to prevent secondary product damage caused by abnormal function (e.g. use VDR for limitation of overvoltage condition).

## Important notes

The following applies to all products named in this publication:

1. Some parts of this publication contain **statements about the suitability of our products for certain areas of application**. These statements are based on our knowledge of typical requirements that are often placed on our products in the areas of application concerned. We nevertheless expressly point out **that such statements cannot be regarded as binding statements about the suitability of our products for a particular customer application**. As a rule, EPCOS is either unfamiliar with individual customer applications or less familiar with them than the customers themselves. For these reasons, it is always ultimately incumbent on the customer to check and decide whether an EPCOS product with the properties described in the product specification is suitable for use in a particular customer application.
2. We also point out that **in individual cases, a malfunction of passive electronic components or failure before the end of their usual service life cannot be completely ruled out in the current state of the art, even if they are operated as specified**. In customer applications requiring a very high level of operational safety and especially in customer applications in which the malfunction or failure of a passive electronic component could endanger human life or health (e.g. in accident prevention or life-saving systems), it must therefore be ensured by means of suitable design of the customer application or other action taken by the customer (e.g. installation of protective circuitry or redundancy) that no injury or damage is sustained by third parties in the event of malfunction or failure of a passive electronic component.
3. **The warnings, cautions and product-specific notes must be observed.**
4. In order to satisfy certain technical requirements, **some of the products described in this publication may contain substances subject to restrictions in certain jurisdictions (e.g. because they are classed as hazardous)**. Useful information on this will be found in our Material Data Sheets on the Internet ([www.epcos.com/material](http://www.epcos.com/material)). Should you have any more detailed questions, please contact our sales offices.
5. We constantly strive to improve our products. Consequently, **the products described in this publication may change from time to time**. The same is true of the corresponding product specifications. Please check therefore to what extent product descriptions and specifications contained in this publication are still applicable before or when you place an order. We also **reserve the right to discontinue production and delivery of products**. Consequently, we cannot guarantee that all products named in this publication will always be available. The aforementioned does not apply in the case of individual agreements deviating from the foregoing for customer-specific products.
6. Unless otherwise agreed in individual contracts, **all orders are subject to the current version of the “General Terms of Delivery for Products and Services in the Electrical Industry” published by the German Electrical and Electronics Industry Association (ZVEI)**.
7. The trade names EPCOS, BAOKE, Alu-X, CeraDiode, CSSP, MiniBlue, MKK, MLSC, MotorCap, PCC, PhaseCap, PhaseMod, SIFERRIT, SIFI, SIKOREL, SilverCap, SIMDAD, SIMID, SineFormer, SIOV, SIP5D, SIP5K, ThermoFuse, WindCap are **trademarks registered or pending** in Europe and in other countries. Further information will be found on the Internet at [www.epcos.com/trademarks](http://www.epcos.com/trademarks).

# AMEYA360

## Components Supply Platform

Authorized Distribution Brand :



Website :

Welcome to visit [www.ameya360.com](http://www.ameya360.com)

Contact Us :

➤ Address :

401 Building No.5, JiuGe Business Center, Lane 2301, Yishan Rd  
Minhang District, Shanghai , China

➤ Sales :

Direct +86 (21) 6401-6692

Email [amall@ameya360.com](mailto:amall@ameya360.com)

QQ 800077892

Skype ameyasales1 ameyasales2

➤ Customer Service :

Email [service@ameya360.com](mailto:service@ameya360.com)

➤ Partnership :

Tel +86 (21) 64016692-8333

Email [mkt@ameya360.com](mailto:mkt@ameya360.com)