




CUSTOMER TERMINAL	RoHS	LEAD(Pb)-FREE
Sn96%, Ag4%	Yes	Yes



PART MUST INSERT FULLY TO SURFACE A IN RECOMMENDED GRID .025 SQ.(4) [.64]



6C ELECTRICAL SPECIFICATIONS @ 25°C unless otherwise noted:

PARAMETER	TEST CONDITIONS	VALUE
D.C. RESISTANCE	1-2 @20°C	0.510 ohms max.
D.C. RESISTANCE	4-3 @20°C	0.510 ohms max.
INDUCTANCE	1-2 10kHz, 50mVAC, Ls	10.0mH +60%/-30%
INDUCTANCE	4-3 10kHz, 50mVAC, Ls	10.0mH +60%/-30%
SATURATION CURRENT	1-4 tie(2+3), roll off 20% from initial	3.0A
LEAKAGE INDUCTANCE	1-4 tie(2+3), 10kHz, 50mVAC, Ls	300uH min.
DIELECTRIC	1-CORE tie(1+4), 1875VAC, 1 second	1500VAC, 1 minute
URNS RATIO	(1-2):(4-3)	1:1, ±2%

GENERAL SPECIFICATIONS:
 OPERATING TEMPERATURE RANGE: -40°C to +125°C including temp rise.
 Designed to meet UL Recognized Insulation System M7-130(B), E106391.
 Current Rating: 1.00A

Wire insulation & RoHS status not affected by wire color.
 Wire insulation color may vary depending on availability.

REV.	DATE	Packaging Specifications	Tolerances unless otherwise specified: Angles: ±1° Fractions: ±1/64	Decimals: ±.005 [.13] Footprint: ±.001 [.03]	DRAWING TITLE	PART NO.
6D	3/15	Method: Tray			CMC	750341634
6C	10/13	PKG-0822				
6B	6/13	www.we-online.com/midcom				
6A	5/13	SEE REVISION SHEET FOR REVISION LEVEL				
CONVENTION PLACEMENT			This drawing is dual dimensioned. Dimensions in brackets are in millimeters.		eiSos p/n: 750341634	SPECIFICATION SHEET 1 OF 2



AMEYA360

Components Supply Platform

Authorized Distribution Brand :



Website :

Welcome to visit www.ameya360.com

Contact Us :

➤ Address :

401 Building No.5, JiuGe Business Center, Lane 2301, Yishan Rd
Minhang District, Shanghai , China

➤ Sales :

Direct +86 (21) 6401-6692
Email amall@ameya360.com
QQ 800077892
Skype ameyasales1 ameyasales2

➤ Customer Service :

Email service@ameya360.com

➤ Partnership :

Tel +86 (21) 64016692-8333
Email mkt@ameya360.com