Product Data Sheet

3M[™] Overhead Air Ionizer 991A

The Overhead Air Ionizer 991A is designed for use with sensitive electronic components where electrostatic discharge (ESD) is a problem. This Ionizer 991A provides fast static charge decay efficiency over an entire work surface area. Equipped with task lighting, an ionization indicator light and an integrated heater, it offers user-friendly operation while helping protect even the most sensitive components from ESD damage.

- Rapidly neutralizes static charges
- Covers an extended area with ionized air
- Inherently balanced to 0 ±6V
- Integrated heater and task lights
- Ionization indicator light
- AC technology for stable performance
- Built-in emitter cleaner for easy maintenance





The 3M[™] Overhead Air Ionizer 991A offers a user-friendly experience with variable fan speeds, as well as task lights and and an integrated heater.



3M[™] Overhead Air Ionizer 991A

Description	Typical Value	Method
Input Voltage	120VAC, 60Hz, 0.5A (fan low, heater/light off) 2.5A (fan high, heater/light on); 230VAC, 50Hz, 0.2A (fan low, heater/light off) 1.5A (fan high, heater/light on)	
Power Consumption	200W (heater)	
Emitter Points	Stainless Steel	
Ion Emission	AC Ionization	
Balance Voltage	±6V @ 18" from blower face	ANSI/ESD STM3.1-2006
Decay Time	${<}4.0~\text{sec} @$ 18" center blower position; fan high-no diffusers	ANSI/ESD STM3.1-2006
Air Speed	200-240 ft./min. (low to high), combined 3 fan output	
Audible Noise	50 dBA fan low; 60 dBA fan high	
Indicator	Orange light for Ionization status	
Ozone Level	0.02 ppm, measured @ 12" in front of unit 2	EPS EQQA-9577-019 using Dashibi Ozone Monitor Model 1003 AE
Operating Env	Temperature 32-122°F (0-80°C): humidity 30-70% RH non- condensing	
Lamp	13W twin tube, compact fluorescent	
Air Filter	30 ppi open cell polyurethane foam (optional)	
Dimensions	42.75W x 4H x 6.75D in. (108.6 x 10.2 x 17.1 cm)	
AC Power Cable Length	56 inches	
Weight	16 lb (7.3 kg)	
Enclosure	Powder-coated white enamel aluminum	
Mounting	Adjustable brackets and S-hooks provided	
Warranty	One year from date of purchase	

_51VI

Electronics Materials Solutions Division Static Control Products 926 JR Industrial Drive Sanford, NC 27332-9733 Toll-Free: 866-722-3736 International: 919-718-0000 Email: 3mstaticinfo@mmm.com www.3Mstatic.com

Please recycle. Printed in USA. © 3M 2014. All rights reserved. 78-9102-1631-2 JHA

Parts and Accessories	;
80-0014-0216-5	991A Overhead Air Ionizer with 110V North American Power Cord
80-0014-0217-3	991A Overhead Air Ionizer with 230V UK Power Cord
80-0014-0218-1	991A Overhead Air Ionizer with 230V European Power Cord
80-0014-0219-9	991A Replaceable Filters, 6 filters/box
80-0014-0220-7	991A Air Filters Retainer (1 per fan)
80-0014-0221-5	991A Task Light Fluorescent Lamp (2 per blower)

3M is a trademark of 3M Company. All other trademarks are owned by their respective companies.

Important Notice

All statements, technical information, and recommendations related to 3M's products are based on information believed to be reliable, but the accuracy or completeness is not guaranteed. Before using this product, you must evaluate it and determine if it is suitable for your intended application. You assume all risks and liability associated with such use. Any statements related to the product which are not contained in 3M's current publications, or any contrary statements contained on your purchase order shall have no force or effect unless expressly agreed upon, in writing, by an authorized officer of 3M.

Warranty; Limited Remedy; Limited Liability.

This product will be free from defects in material and manufacture for one year from the time of purchase. **3M MAKES NO OTHER WARRANTIES INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE**. If this product is defective within the warranty period stated above, your exclusive remedy shall be, at 3M's option, to replace or repair the 3M product or refund the purchase price of the 3M product. Except where prohibited by law, 3M will not be liable for any indirect, special, incidental or consequential loss or damage arising from this 3M product, regardless of the legal theory asserted.

AMEYA360 Components Supply Platform

Authorized Distribution Brand :



Website :

Welcome to visit www.ameya360.com

Contact Us :

> Address :

401 Building No.5, JiuGe Business Center, Lane 2301, Yishan Rd Minhang District, Shanghai , China

> Sales :

- Direct +86 (21) 6401-6692
- Email amall@ameya360.com
- QQ 800077892
- Skype ameyasales1 ameyasales2

> Customer Service :

Email service@ameya360.com

> Partnership :

- Tel +86 (21) 64016692-8333
- Email mkt@ameya360.com